MILITARY SPECIFICATION

CHLORPHENIRAMINE MALEATE, ISOPROPAMIDE IODIDE, AND PHENYLPROPANOLAMINE HYDROCHLORIDE CAPSULES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Chlorpheniramine Maleate, Isopropamide Iodide, and Phenylpropanolamine Hydrochloride Capsules (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-C-186	-	Containers, Packaging and Packing for Drugs, Chemicals, and Pharmaceuticals. (see 6.3)

STANDARDS

FEDERAL

FED-STD-00285	-	Capsules (For Medicinal Purposes).

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U.S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE,
FOOD AND DRUG ADMINISTRATION

Federal Food, Drug, and Cosmetic Act and
Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, DC 20204.)

U. S. PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia.

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

National Formulary.

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

3. REQUIREMENTS

3.1 Material. Shall be Chlorpheniramine Maleate, Isopropamide Iodide, and Phenylpropanolamine Hydrochloride Capsules and shall be in accordance with all applicable requirements of FED-STD-00285 and as specified herein:

S2. Classification. Shall be type I or II.

S5.4 The following is added to this paragraph:

Shall be sustained release capsules containing in each capsule, within the designated assay limit for the capsules, 8 mg of chlorpheniramine maleate and 50 mg of phenylpropanolamine hydrochloride, so prepared that an initial dose is released promptly and the remaining medication is released gradually over a prolonged period; and isopropamide iodide equivalent to 2.5 mg of isopropamide. The isopropamide iodide component is not in sustained release form. The capsules shall assay to contain not less than 95.0 percent and not more than 110.0 percent of the required amount of the active ingredients when assayed as specified in 4.3.1 and subparagraphs thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

3.2 Identification. The active ingredients in the finished capsules, when extracted, shall comply with the identity tests for each active ingredient, as specified herein.

3.2.1 Phenylpropanolamine hydrochloride. The maxima and minima absorbance at the wavelengths specified in the assay method shall be considered as an identity test.

3.2.2 Chlorpheniramine maleate. The maximum and minimum absorbance at the wavelengths specified in the assay method shall correspond to those obtained from U.S.P. reference standard chlorpheniramine maleate similarly treated.

3.2.3 Isopropamide iodide. The wavelengths of maximum absorption of the sample in 4.3.1.1 shall be identical to that of the standard sample.

3.3 Disintegration (release rate). The release rate for chlorpheniramine malteate, and phenylpropanolamine hydrochloride in the finished capsules shall be in accordance with table I when tested as described in 4.3.2.

TABLE I. Release rate for chlorpheniramine maleate and phenylpropanolamine hycrochloride

Time interval	Disintegration conditions	% released
1/2 hour	G.F. 1/	20-35
2 hours	1-1/2 hrs. G.F. + 1/2 hr. I.F. 2/	40-60
4-1/2 hours	1-1/2 hrs. G.F. + 3 hrs. I.F.	60-80
7 hours	1-1/2 hrs. G.F. + 5-1/2 hrs. I.F.	Not less than 80

1/ Gastric Fluid, Simulated, U.S.P.
2/ Intestinal Fluid, Simulated, U.S.P.

3.4 Ingredients. All ingredients used in the manufacture of the capsules shall comply with S5.2 of FED-STD-00285.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and, (i) as to any expiration dated item, for the expiration dating period (potency period) specified by the contractor for such item, or such longer period as may be required by regulation of any federal agency; or (ii) as to non-dated item, for not less than 3 years after delivery of the items to the Government.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facility for the performance of any inspection requirements specified herein.

4.2 Sampling. The sampling as shown in FED-STD-00285 shall be applicable.

4.3 Tests.

4.3.1 Assay of finished capsules. The filled capsules shall be assayed as specified below:

4.3.1.1 Isopropamide iodide.

Reagents.

Phosphate buffer (pH 10.2). Dissolve 87 grams of K_2HPO_4 and 42 grams of $Na_2CO_3.H_2O$ in about 1500 ml of purified water. Adjust to pH 10.2 ± 0.1, if necessary, with the appropriate salt. If more than 2 grams of salt are required, carefully complete the pH adjustment with 85 percent phosphoric acid or saturated sodium hydroxide solution. Dilute to 2000 ml with purified water and mix well.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Buffered methyl orange. Add 1.5 grams of reagent grade methyl orange to 1500 ml of phosphate buffer (pH 10.2) in a 2 liter flask. Heat the flask for 1/2 hour on a steam bath. Agitate the solution for 1/2 hour on a shaker while it is cooling. Allow the solution to stand overnight and shake it again for 1/2 hour. Filter through a Whatman No. 4 filter paper. Extract with chloroform, using 50 ml portions for each 50 ml portions for each 500 ml of buffered methyl orange. Repeat the extractions until the chloroform layer gives no more than 0.01 unit absorbance at 525 nm when compared with reagent grade chloroform, measured on a suitable Spectrophotometer using 5 cm cells.

Allow the solution to stand until clear and decant it from any chloroform which settles out. Store in a tightly stoppered bottle.

Stock standard isopropamide iodide solution. Dissolve about 100 mg of isopropamide iodide NF Reference Standard accurately weighed, in about 800 ml of 1 percent v/v HCl in a 1000 ml volumetric flask. Add 5 ml of 0.5 percent aqueous $NaHSO_3$ solution and dilute to volume with 1 percent v/v HCl, and mix well.

Working standard isopropamide iodide solutions. Pipet a 15 ml and a 20 ml aliquot of Stock Standard Solution into two 50 ml volumetric flasks. Dilute to volume with 1 percent v/v HCl and mix well. (Con. approximately 0.03 mg/ml and 0.04 mg/ml.)

Hydrochloric acid in methanol. Add 15 ml of concentrated HCl to about 150 ml of reagent grade methanol in a 200 ml volumetric flask. Dilute to volume with methanol and mix well. This solution should be prepared fresh daily.

Procedure. Conduct in duplicate.

Transfer an accurately weighed, well-mixed sample (3.5 $\pm$ 0.2 grams) obtained by pooling the contents of 50 capsules to a 1000 ml volumetric flask. Add about 500 ml of 1 percent v/v HCl and shake the flask for 1/2 hour, dilute to volume with 1 percent v/v HCl and mix well. Allow to settle for a few minutes. Pipet a 5 ml aliquot of supernatant solution into a 125 ml separatory funnel . Pipet 15 ml of buffered methyl orange reagent into this funnel. Extract the contents of the funnel with three 25-ml portions of chloroform. Filter the chloroform layers through a small pledget of cotton which has been wetted with chloroform and collect the filtrate in a 100 ml volumetric flask. Rinse the cotton with 10 ml of chloroform. Add 10 ml of hydrochloric acid in methanol. Mix well and dilute to volume with chloroform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Pipet 5 ml aliquots of each Working Standard Isopropamide Iodide Solution into 125-ml separatory funnels. Follow the procedure for the samples above, starting with "Pipet 15 ml of buffered methyl orange...".

Pipet 5 ml of 1 percent v/v HCl into a 125-ml separatory funnel. Treat in the same manner as the standards. This will serve as a reagent blank.

Measure the optical density of each solution on a suitable spectrophotometer using approximately the following operating conditions: visible range, 5 cm cells, reagent blank in the reference cell. Scan through the region of the absorption maximum, 500 through 535 nm. Record a baseline using the same operating conditions with the reagent blank in both cells.

Calculations:

$$\frac{A(max) \times \text{Std. Factor } \underline{1/} \times 1000 \times 100}{\text{Sample Wt. (gram)} \times 5} = \text{mg isopropamide iodide/gram}$$

1/ Standard factor is obtained for the two 5 ml aliquots of Working Standard Isopropamide Iodide Solutions and averaged.

Calculate the percent of required amount on the basis of the capsule fill (Av. Net Contents in gram/capsule) and the assay value obtained.

$$\frac{\text{Capsule fill (gram/cap.)}}{3.4} \times \text{Assay Value (mg/gram)} \times 100 = \% \text{ of required amount}$$

4.3.1.2 Phenylpropanolamine hydrochloride. Transfer an accurately weighed, well mixed sample (2.0 ± 0.1 grams) obtained by pooling the contents of 50 capsules to a 200 ml volumetric flask. Add about 50 ml of 1 percent v/v HCl and heat the flask on a steam bath for a minimum period of time (about 5 minutes), with occasional swirling. When the wax is melted and the capsule contents are disintegrated, place the flask in a cold water bath and cool to room temperature, with swirling. Dilute to volume with 1 percent v/v HCl and mix well. Transfer a 20 ml aliquot to a 250 ml separatory funnel and add 5 ml of 15 percent NaOH and 40 ml of cyclohexane. Shake thoroughly and allow the layers to separate. Drain the lower aqueous layer into a second 250 ml separatory funnel. Add 20 ml of cyclohexane to this aqueous layer and shake thoroughly. Allow the layers to separate and then run in the 40 ml of cyclohexane from the first separatory funnel. Rinse the first funnel with 10 ml of cyclohexane and add this to the combined cyclohexane layers. Drain the lower aqueous layer into the rinsed funnel. Extract the combined cyclohexane layers with two 10 ml portions of 1 percent NaOH and add the extracts to the aqueous layer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Save the cyclohexane layer for the chlorpheniramine maleate assay.

Extract the alkaline aqueous layer with three 50-ml portions of chloroform. Filter the chloroform layers through a pledget of chloroform-wet cotton and collect the filtrate in a 250 ml separatory funnel. Extract the combined chloroform layers with four 20 ml portions of 2 percent v/v HCl. Collect the HCl layers in a 100 ml volumetric flask and dilute to volume with 2 percent v/v HCl. Using 5 cm absorption cells, record the ultraviolet absorption spectrum of this solution on a suitable spectrophotometer from 265 to 250 nm, using approximately the following operating conditions: slit width - not more than 0.15 mm at 257 nm, with 2 percent v/v HCl in the reference cell. Draw a baseline connection the minima at 253 and 261 nm. Draw a line, perpendicular to the zero line of the chart paper, which passes through the wavelength of maximum absorption and intersects the baseline connection the minima. Subtract the absorbance of the baseline at this wavelength (approximately 257 nm) from the absorbance of the curve maximum. Denote the average of the values so obtained as $\triangle$ A.

Calculations:

$$\frac{\triangle \text{ A} \times 3.043^{1/} \times 100 \times 200}{\text{Sample Wt. (gram)} \times 20 \times 5} = \text{mg phenylpropanolamine hydrochloride/gram}$$

1/ 3.043 mg phenylpropanolamine Hydrochloride/ml/unit $\triangle$ A

Calculate the percent of required amount on the basis of the capsule fill (Average net contents in Gram/cap.) and the assay value obtained.

$$\frac{\text{Capsule Fill (fram/cap.)} \times \text{Assay Value (mg/gram)}}{50} \times 100 = \% \text{ of required amount}$$

4.3.1.3 Chlorpheniramine maleate. Extract the cyclohexane layer (from the phenylpropanolamine hydrochloride assay) with three 30-ml portions of 2 percent v/v H_2SO_4. Collect the acid layers in a 100-ml volumetric flask. Dilute to volume with 2 percent v/v H_2SO_4 and mix well. Record the ultraviolet absorption spectrum of this solution from 295 to 240 nm on a suitable spectrophotometer using approximately the following operating conditions: slit width - not more than 0.15 mm at 257 nm, 1 cm cells with 2 percent v/v H_2SO_4 in the reference cell. Draw a baseline connecting the points on the curve at 290 and 242.5 nm. Draw a line, perpendicular to the zero line of the chart paper, which passes through the curve maximum at 264.3 nm and intersects the drawn baseline. Subtract the absorbance of the baseline at this wavelength from the absorbance of the curve maximum; denote as $\triangle$A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Calculations:

$$\frac{\triangle A \times 0.06084^{1/} \times 250 \times 100}{\text{Sample Wt. (gram)} \times 20} = \text{mg chlorpheniramine maleate/gram}$$

1/ 0.06084 mg chlorpheniramine maleate/ml/unit $\triangle$ A (1 cm cells)

Calculate the percent of required amount on the basis of capsule fill (average Net Contents in gram/cap.) and the assay value obtained.

$$\frac{\text{Capsule Fill (gram/cap.)}}{8} \times \text{Assay Value (mg/gram)} \times 100 = \% \text{ of required amount.}$$

4.3.2 Disintegration (release rate). Apparatus shall be of the type described in Drug Standards, page 77, May-June, 1958 issue. Transfer 4 accurately weighed, well-mixed samples (1.0 ± 0.1 gram) obtained by pooling the contents of 50 capsules to 4 screwcap disintegration bottles. Add 60 ml of Gastric Fluid, Simulated, U.S.P. previously warmed to 37° C., to each bottle. Rotate the bottles in a 44 r.p.m. disintegration apparatus maintained at 37° C. Remove one bottle at the end of 1/2 hour and collect the capsule contents on a 40 mesh screen. Wash free of disintegration fluid with purified water and partially dry by suction.

At the end of 1-1/2 hours remove the three remaining sample bottles and decant the disintegration fluid through three 40 mesh screens. (Leave as much capsule contents in the bottles as conveniently possible.) Rinse each sample bottle once with about 25 ml of purified water by swirling the capsule contents in the wash water. Decant the wash water through the respective screen in each case. If any capsule contents remain on the bottle caps, rinse them onto their respective screens with a small quantity of water. Quantitatively transfer each of the samples back to its respective bottle with the aid of 60 ml of Intestinal Fluid, Simulated, U.S.P., previously warmed to 37° C. Rotate the sample bottles at the end of 1/2, 3, and 5-1/2 hours, and collect the residual capsule contents on 40 mesh screens. Wash free of disintegration medium with purified water and partially dry by suction.

Transfer the capsule contents to volumetric flasks of the sizes indicated below, using 1 percent v/v HCl to wash them from the screens.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Total Time Interval	Flask Size for capsule contents	Cell Size for Chlorpheniramine Maleate	Cell Size for Phenylpropanolamine hydrochloride
1/2 hour	200 ml	2 cm	5 cm
2 hours	100 ml	2 cm	5 cm
4-1/2 hours	100 ml	2 cm	5 cm
7 hours	100 ml	2 cm	5 cm

Add about 50 ml of 1 percent v/v HCl and heat the flask on a steam bath for a minimum period of time (about 5 minutes), with occasional swirling. When the wax is melted and the capsule contents are disintegrated, place the flask in a cold water bath and cool to room temperature with swirling. Dilute to volume with 1 percent v/v HCl and mix well. Filter through a Whatman No. 4 filter paper, discarding the first 10-15 ml of filtrate. Transfer a 20 ml aliquot to a 250 ml separatory funnel. Add 5 ml of 15 percent NaOH and 40 ml of cyclohexane. Shake thoroughly and allow the layers to separate. Drain the lower aqueous layer into a second 250 ml separatory funnel. Add 20 ml of cyclohexane to this aqueous layer and shake thoroughly. Allow the layers to separate and then run in the 40 ml of cyclohexane from the first separatory funnel. Rinse the first funnel with 10 ml of cyclohexane and add this to the combined cyclohexane layers. Drain the lower aqueous layer into the rinsed funnel. Extract the combined cyclohexane layers with two 15 ml portions of 1 percent NaOH and add them to the aqueous layer.

Transfer the alkaline aqueous layer quantitatively to a 100 ml volumetric flask with the aid of purified water.

Save the cyclohexane layer for the chlorpheniramine maleate assay.

Add 4 ml of concentrated HCl, dilute almost to volume with purified water and mix well. Cool the flask to room temperature in a cold water bath with swirling. Dilute to volume with purified water and mix well. Record the ultraviolet absorption spectrum of this solution on a suitable spectrophotometer from 265 to 250 nm, scan three times, using approximately the following operating conditions: slit width - not more than 0.15 mm at 257 nm, 5 cm cells with 2 percent v/v HCl in the reference cell. Draw a baseline connecting the minima at 253 and 261 nm. Draw a line, perpendicular to the zero line of the chart paper, which passes through the wavelength of maximum absorption and intersects the baseline connecting the minima. Subtract the absorbance of the baseline at this wavelength (approximately 257 nm) from the absorbance of the curve maximum. Denote the average of the three values so obtained as $\triangle A$ (Phenylpropanolamine Hydrochloride.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

Assay (chlorpheniramine maleate).

Extract the cyclohexane layer (from the phenylpropanolamine hydrochloride assay) with three 30 ml portions of 2 percent v/v H_2SO_4. Collect the acid layers in a 100 ml volumetric flask. Dilute to volume with 2 percent v/v H_2SO_4 and mix well. Record the ultraviolet absorption spectrum of this solution from 295 to 240 nm on a suitable spectrophotometer using approximately the following operating conditions: slit width - not more than 0.15 mm at 257 nm, 2 cm cells with 2 percent v/v H_2SO_4 in the reference cell. Draw a baseline connecting the points on the curve at 290 and 242.5 nm. Draw a line, perpendicular to the zero line of the chart paper, which passes through the curve maximum at 264.3 nm and intersects the drawn baseline. Subtract the absorbance of the baseline at this wavelength from the absorbance of the curve maximum; denote as $\triangle$ A.

Calculations:

a. Phenylpropanolamine Hydrochloride:

$$\frac{\triangle A \times 3.043 \times \text{Flask size for residual pellets} \times 100}{\text{Sample Wt. (gram)} \times 20 \times \text{cell thickness (cm)}} = \text{mg/gram remaining}$$

b. Chlorpheniramine Maleate:

$$\frac{\triangle A \times 0.03042 \times \text{Flask size for residual pellets} \times 100}{\text{Sample Wt. (gram)} \times 20} = \text{mg/gram remaining}$$

In each case:

$$\frac{\frac{\text{mg}}{\text{gram}}\ \text{Original} - \frac{\text{mg}}{\text{gram}}\ \text{Remaining}}{\frac{\text{mg}}{\text{gram}}\ \text{Original}} \times 100 = \%\ \text{released}$$

Note: If the absorbance of the phenylpropanolamine hydrochloride curve at the 253 nm minimum is less than the absorbance at the 261 nm minimum, proceed as follows:

Transfer a 50 ml aliquot of the solution to a 250 ml separatory funnel and add 5 ml of 15 percent NaOH. Proceed as in 4.3.1.2, starting with..."Extract the alkaline aqueous layer with three 50 ml portions of chloroform...". Multiply the mg/gram obtained by 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

4.4 Packaging inspection. The inspection of the unit, intermediate package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.5 Labeling inspection. Sampling shall be in accordance with MIL-STD-105 and the unit of product shall be the unit of issue. The inspection lot shall be the number of units of issue of each batch, lot, control number, etc., offered for inspection at one time. The inspection level for labeling shall be S-2 and the acceptance number shall be zero.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with all applicable requirements of PPP-C-186 (see 6.3) and as specified herein.

5.2 Packaging. Packaging shall be level A or C as specified (see 6.1).

5.2.1 Unit of issue. One bottle containing five hundred capsules, as specified, constitutes one unit of issue.

5.2.2 Level A.

5.2.2.1 Immediate container. The immediate container shall be a commercially available bottle considered acceptable by the Food and Drug Administration (FDA) for the product contained therein and shall be of such compatibility that neither the contents nor the container are altered in any way be each other.

5.2.2.2 Unit package. At the option of the contractor, a unit package may be furnished. If a unit package is furnished, each bottle shall be packaged as specified in paragraph 5.2.5 of PPP-C-186.

5.2.2.3 Intermediate package. Twelve units of issue shall be packaged as specified in 5.2.9 of PPP-C-186.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.3 Packing. Packing shall be level A, B or C as specified (see 6.1).

5.3.1 Level A. Two intermediate packages (24 units) shall be packed in an exterior container as specified in 5.4.4 of PPP-C-186.

5.3.2 Level B. Two intermediate packages (24 units) shall be packed in an exterior container as specified in 5.4.3.2 of PPP-C-186.

5.3.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.4 Marking.

5.4.1 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug and Cosmetic Act and shall include the information required below:

5.4.1.1 Immediate container. Each immediate container label shall bear the following information:

(a) label information in accordance with commercial practice.
(b) The date of manufacture prefixed by "MFD".

5.4.1.2 Unit package. Each unit package label shall bear the following:

(a) labeling information in accordance with commercial practice.
(b) the National Stock Number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

NOTES: (1) The National Stock Number shall not be preceded by any prefix.

(2) Strip labeling may be used.

(3) Labeling adhesion test shall not apply.

(4) If a unit package is not supplied, the National Stock Number shall appear on the immediate container.

5.4.2 Intermediate package. Each intermediate package shall be marked in accordance with paragraph 5.5.3 of PPP-C-186 except that the date of manufacture shall be shown in lieu of the date packed. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)".

5.4.3 Exterior container. Exterior containers shall be marked as specified in 5.5.4 of PPP-C-186 except that the date of manufacture shall be shown in lieu of the date packed. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE (59° - 86° F.)".

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) the National Stock Number.
(c) Selection of applicable levels of packaging and packing (see 5.2 and 5.3).

6.2 This specification covers the following item:

National Stock No.	Item Identification
6505-00-014-1028	CHLORPHENIRAMINE MALEATE, ISOPROPAMIDE IODIDE, AND PHENYLPROPANOLAMINE HYDROCHLORIDE CAPSULES, 500s

6.3 All references to PPP-C-186 refer to Interim Federal Specification PPP-C-00186B which is mandatory for use unitl superseded by a revision.

6.4 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification or those which are commercially available, but is intended to cover the types which are normally procured to meet Military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
DSA-DM

Project No. 6505-1454

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-C-37306 CHLORPHENIRAMINE MALEATE, ISOPROPAMIDE IODIDE, AND PHENYLPROPANOLAMINE HYDROCHLORIDE CAPSULES

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, PA 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:24Z
Check the source to verify that this is the current version before use.