INCH-POUND
MIL-DTL-49285/26A
w/AMENDMENT 1
31 August 2018
SUPERSEDING
MIL-DTL-49285/26A
1 March 2010

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, ONE INDIVIDUALLY SHIELDED PAIR OF 16 (19 X 29) AWG

Inactive for new design after 16 June 1997.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-49285.

Engineering information: See table I.

Not recommended for shipboard or aerospace applications due to toxic smoke release in the event of a fire. PVC is not recommended in other applications (i.e. confined spaces, low ventilation) where there is the potential for human smoke exposure in a fire.

TABLE I. Description, electrical.

Electrical characteristics	Requirements
Nominal capacitance between conductors	24 pF/ft (picofarads/foot)
Nominal capacitance between the conductor and the shield with one conductor tied to the shield	47 pF/ft
Continuous working voltage	600 V rms maximum between conductors
Shield dc resistance	6.0 ohms/1,000 feet maximum

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

TABLE II. Description, physical.

Components	Construction details
Number of pairs	One individually shielded
Conductor type and wire size	Stranded tinned copper 16 AWG
Conductor stranding	19 X 29 AWG
Conductor insulation	Polyethylene
Conductor insulation thickness	0.032 inch nominal thickness
Drain wire type and size	Stranded tinned copper 18 AWG
Drain wire stranding	16 X 30 AWG
Jacket material	Polyvinyl chloride
Jacket thickness	0.031 inch
Finished cable diameter	0.334 inch maximum outside diameter
Cable style (UL)	2106
Tensile strength (jacket)	2,000 pounds per square inch minimum
Elongation (jacket)	150 percent minimum
Overall cabling lay length	8.0 twists per foot ± 10 percent

REQUIREMENTS:

Design and construction: (see table II):

Shield color code. The shield color shall be blue.

Shield location and orientation. The polyester aluminum shield is to be located on the outer circumference of the pair, with the aluminum foil side outward. Insulation on the interior of the shield is to be complete with no aluminum available for contact.

Drain wire location. The drain wire is to be spirally located between the shield and jacket, and is to be in continuous contact with the aluminum surface of the foil shield throughout the cable.

Cable temperature rating. The cable temperature rating shall be -20°C to +80°C.

Conductor color coding. The first conductor is black, the second conductor is natural (clear).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

Shield integrity test.*

Frequency	Response
100 kHz	114 dB or more below reference
500 kHz	104 dB or more below reference
1 MHz	99 dB or more below reference
5 MHz	77 dB or more below reference
10 MHz	66 dB or more below reference
15 MHz	58 dB or more below reference
20 MHz	53 dB or more below reference
25 MHz	48 dB or more below reference
30 MHz	45 dB or more below reference

* Any two readings may deviate to a value of 0.9 times the stated limits.

Fixture resonance will occur between 40 and 70 MHz.

At 100 MHz: At least 26 dB below reference.

Crosstalk test limits. Crosstalk testing is not required for this configuration.

Durometer hardness. The cable jacket shall have a “Shore A” hardness of 82 $\pm$ 5.

Part or Identifying Number (PIN): The PIN shall be M49285/26.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced document. This document references MIL-DTL-49285.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – SH
Air Force – 85
DLA – CC

Preparing activity:
DLA - CC

Review activities:
Army – MI
Air Force - 71
DLA – CQ

(Project 6145-2018-042)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change. You should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.