INCH-POUND
MIL-DTL-49285/32B
31 August 2018
SUPERSEDING
MIL-DTL-49285/32A
10 February 2010

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, (LOW NOISE) ONE INDIVIDUALLY SHIELDED PAIR OF 24 (19 X 36) AWG

Inactive for new design after 16 June 1997.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-49285.

Engineering information: See table I.

Not recommended for shipboard or aerospace applications due to toxic smoke release in the event of a fire. PVC is not recommended in other applications (i.e. confined spaces, low ventilation) where there is the potential for human smoke exposure in a fire.

TABLE I. Description, electrical.

Electrical characteristics	Requirements
Nominal capacitance between conductors	30 pF/ft (picofarads/foot)
Nominal capacitance between the conductor and the shield with one conductor tied to the shield	58 pF/ft
Continuous working voltage	200 V rms maximum between conductors
Shield dc resistance	21.0 ohms/1,000 feet maximum

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

TABLE II. Description, physical.

Components	Construction details
Number of pairs	One individually shielded
Conductor type and wire size	Stranded tinned copper 24 AWG
Conductor stranding	19 X 36 AWG
Conductor insulation	Polypropylene
Conductor insulation thickness	0.008 inch nominal thickness
Noise reducing tape	Nylon cloth tape, carbon impregnated
Drain wire type and size	Stranded tinned copper 24 AWG
Drain wire stranding	19 X 36 AWG
Jacket material	Polyvinyl chloride
Jacket thickness	0.020 inch
Finished cable diameter	0.142 inch maximum outside diameter
Cable style (UL)	Not applicable
Tensile strength (jacket)	2,000 pounds per square inch minimum
Elongation (jacket)	150 percent minimum
Overall cabling lay length	16.0 twists per foot ± 10 percent

REQUIREMENTS:

Design and construction: (see table II):

Shield color code. The shield color shall be blue.

Noise reducing tape. The noise reducing tape is carbon impregnated nylon cloth tape. The tape is located beneath the foil shield over the insulated conductors.

Thickness:	.0035 inch to .004 inch.
Weight:	11 pounds per 100 square yards
Material:	50 denier nylon 100 x 7 threads per inch
Coating:	Semiconductor lacquer
Breaking strength:	50 pounds per inch width minimum
Elongation:	20 percent
Color:	Black
Conductivity:	5,000 ohms per unit square maximum value
Location:	Between the insulated conductors and the polyester aluminum shield

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

Shield location and orientation. The polyester aluminum shield is to be located on the outer circumference of the pair, with the aluminum foil side inward. Insulation on the exterior of the shield is to be complete with no aluminum available for contact.

Drain wire location. The drain wire is to be spirally located beneath the shield with the insulated conductors. It is to be in continuous contact with the aluminum surface of the foil shield throughout the cable.

Cable temperature rating. The cable temperature rating shall be -20°C to +80°C.

Shield integrity test.*

Frequency	Response
100 kHz	110 dB or more below reference
500 kHz	102 dB or more below reference
1 MHz	96 dB or more below reference
5 MHz	79 dB or more below reference
10 MHz	71 dB or more below reference
15 MHz	65 dB or more below reference
20 MHz	60 dB or more below reference
25 MHz	56 dB or more below reference
30 MHz	52 dB or more below reference

* Any two readings may deviate to a value of 0.9 times the stated limits.

Fixture resonance will occur between 40 and 70 MHz.

At 100 MHz: At least 36 dB below reference.

Crosstalk test limits. Crosstalk testing is not required for this configuration.

Durometer hardness. The cable jacket shall have a “Shore A” hardness of 77 ± 5.

Part or Identifying Number (PIN): The PIN shall be M49285/32.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced document. This document references MIL-DTL-49285.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – SH
Air Force – 85
DLA – CC

Preparing activity:
DLA - CC

Review activity:
Army – MI
Air Force - 71
DLA – CQ

(Project 6145-2018-046)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change. You should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:00Z
Check the source to verify that this is the current version before use.