UU-C-128F
January 6, 1969
SUPERSEDING
Int. Fed. Spec. UU-C-128E (GSA-FSS)
May 2, 1968 and
Fed. Spec. UU-C-128D
November 15, 1962

FEDERAL SPECIFICATION

CARD, INDEX

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers cotton or linen and chemical wood index cards, white and colored.

1.2 Classification.

1.2.1 Grades. Index cards shall be of the following grades, as specified (see 6.1):

Grade C. 25 percent cotton or linen, white and colored.
Grade D. Chemical wood, white and colored.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-P-258 - Paper; Index.
PPP-B-576 - Boxes, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.)

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:20Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547 - Liners Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI):

T 409 os-61 - Machine Direction of Paper.
T 455 ts-57 - Identification of Wire Side of Paper.

(Copies may be obtained from the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, New York 10017.)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago, Illinois 60606.)

National Motor Freight Classification.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Grade C. Grade C index cards shall be made from paper conforming to the requirements of UU-P-258, Grade B index paper.

3.1.2 Grade D. Grade D index cards shall be made from paper conforming to the requirements of UU-P-258, Grade C, index paper.

3.2 Basis weight. Index cards shall have a basis weight (substance) of 220, 280, or 340 pounds per 1000 sheets of a basic ream size of 25-1/2 by 30-1/2 inches, as specified (see 6.1).

3.3 Color.

3.3.1 Grade C. Grade C index cards shall be white, except that cards in basis weights of 220 and 280 pounds shall also be blue, buff, green, pink, salmon, or yellow, as specified (see 6.1).

3.3.2 Grade D. Grade D index cards shall be white, except that cards in basis weight of 220 pounds shall also be blue, buff, green, pink, salmon, or yellow as specified (see 6.1).

3.3.3 Color standards. Colors shall conform to the standard samples as adopted by the Joint Committee on Printing for index paper in accordance with UU-P-258 (see 6.3).

3.4 Grain direction. The grain direction shall be parallel to the long dimension of the card.

3.5 Size. Unless otherwise specified, index cards in accordance with this specification shall be 3 by 5, 4 by 6, or 5 by 8 inches, as specified (see 6.1). The vertical dimension is named first. Index cards shall be furnished in the size(s) specified and shall be trimmed square on four sides with clean, smooth edges. A plus or minus tolerance of 1/16 inch in each direction shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

permitted. Cards shall be considered square if the difference in length between two diagonals does not exceed 1/32 inch.

3.6 Form. Cards shall be unruled, ruled one side, or ruled two sides, as specified (see 6.1). When specified, rulings shall be parallel to the horizontal dimension of the cards and shall be in accordance with standard commercial practice. Ruled lines shall be clear and visually continuous.

3.7 Curl. The maximum curl of the cards, when exposed to 80 ± 3 percent relative humidity and 90 ± 2° F. for 24 hours and then allowed to come to equilibrium at 50 ± 2 percent relative humidity and 73 ± 3.5° F. shall not exceed 0.25 inch when tested as specified in 4.3.2.

3.8 Workmanship. Index cards shall be free from lint, fuzz, or loose particles. Cards shall be clean cut with smooth edges free from nicks.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated. For sampling purposes, the lot shall consist of all index cards of one grade, size, color, and form offered for delivery at one time.

4.2 Inspection of components and materials. In accordance with 4.1, the supplier is responsible for insuring that components and materials used were manufactured, examined, and tested in accordance with this specification or referenced subsidiary specifications and standards.

4.2.1 In lieu of using his own facilities, the contractor may submit a report of analysis of the component materials from a laboratory acceptable to the Government as evidence of compliance with the specification requirements. The report of analysis shall include, in addition to the actual test data, the manufacturers name, name and address of the testing laboratory, date of test, and quantity of material represented by the test report.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) shown in table I.

TABLE I. Sampling procedure

Examination paragraph	Lot size units	Sample unit	Inspection level	AQL defects per hundred units
4.3.1.1	Shipping containers	Shipping container	S-2	2.5
4.3.1.2	Packages	Package	S-2	N.A.
4.3.1.3	Cards	One card	S-4	1.0
4.3.1.4	Cards	One card	S-4	2.5

4.3.1.1 Examination of preparation for delivery. An examination shall be made to determine that markings, materials, workmanship, contents, and weight comply with the requirements of section 5. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. An equal number of shipping containers, fully prepared for delivery shall be examined for closure defects.

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

Examine (cont'd.)	Defect (cont'd.)
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose or inadequate sealing, strapping, or stapling. Bulged or distorted container.
Contents	Number of intermediate containers more or less than specified. Number of packages per intermediate container more or less than specified.
Weight	Gross or net weight exceeds requirement.

4.3.1.2 Examination of the end item for count. The packages selected for this examination shall be taken from the shipping containers selected under 4.3.1.1. The lot shall be unsatisfactory if the average number of cards per package, of all the packages inspected, is less than specified.

4.3.1.3 Examination of the end item for dimensional defects. The cards selected for this examination shall be taken from the packages selected under 4.3.1.2. Not more than one card shall be taken from a package of one hundred cards.

Examine	Defect
Length and width	Length or width varies more than 1/16 inch from dimension specified.
Squareness	Not trimmed square; difference between two diagonals exceeds 1/32 inch.

4.3.1.4 Examination of the end item for visual defects. Not more than one card shall be selected from any one package of one hundred cards.

Examine	Defect
Appearence	Not form specified. Rulings, as applicable, not clear; not continuous. Presence of scuff marks, tears, or ink blots. Ragged, uneven, or crushed edge. Color not as specified; does not compare favorably with the standard sample. Presence of fuzz, lint, or loose particles.

4.3.2 Testing of the end item. The end item shall be tested for the applicable characteristics in table II. The methods of testing as listed in table II shall be followed. The lot size shall be expressed in units of packages of cards of the same grade, size, color, and form. The sample unit shall consist of 21 consecutive cards selected from a single package. The inspection level shall be S-2 and there shall be no failures to meet the sample unit requirements.

TABLE II. Testing of the end item

Characteristic	Requirement paragraph	Test method	Number of determinations per sample unit	Results reported as
Grain	3.4	4.4.1	1	Pass or fail
Curl	3.7	4.4.2	Average of 2	To nearest 0.01 inch

4.4 Test methods.

4.4.1 Grain. The grain direction shall be determined on one card in each sample unit in accordance with TAPPI method T 409 os-61. Report the grain direction in relation to the long dimension of the card.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

4.4.2 Curl. Place two decks of 10 cards each on a smooth horizontal surface, one deck with the wire side up and one deck with the wire side down. The wire side of the card may be determined in accordance with TAPPI method T 455 ts-57. Expose the decks for 24 hours to a relative humidity of 80 ± 3 percent relative humidity and 90 ± 2° F. Remove the decks and turn, if necessary, so that the concave side is up and allow to come to equilibrium at 50 ± 2 percent relative humidity and 73 ± 3.5° F. Measure the amount of curl by allowing a straight edge, weighing 2.5 ± 0.1 grams to be supported by the two high points in the deck of cards and measure from the bottom of the straight edge to the low point on the top card of the deck. Report the average of the two measurements to the nearest 0.01 inch.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level B or C, as specified (see 6.1).

5.1.1 Level B. One hundred index cards of the same grade, size, color, and form shall be banded with kraft wrapping paper, minimum 3 inches wide and secured with a suitable adhesive, or shall be wrapped in a transparent plastic film.

5.1.1.1 Intermediate container. Ten banded packages (see 5.1.1), shall be intermediately packaged in a set-up paperboard box conforming to PPP-B-676, or in a corrugated fiberboard box made of 125 pound test "B" flute corrugated board of a type normally used for cards.

5.1.2 Level C. Index cards shall be packaged in accordance with the manufacturer's standard commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Index cards packaged as specified in 5.1.1 and 5.1.1.1, shall be packed in overseas-type wood-cleated fiberboard, nailed wood, wirebound wood, fiberboard, wood-cleated paper overlaid, or wood-cleated plywood boxes, PPP-B-591, PPP-B-621, PPP-B-585, PPP-B-636, PPP-B-576, and PPP-B-601, respectively, at the option of the contractor. Shipping containers shall have case liners conforming to MIL-L-10547 closed and sealed in accordance with the appendix thereto. Case liners are not required for boxes conforming to PPP-B-636, class weatherproof, closed, waterproofed, and reinforced in accordance with appendix to PPP-B-636. Boxes shall be closed and strapped in accordance with the box specifications or appendix thereto. Gross weight of wood boxes shall not exceed 200 pounds. Fiberboard boxes shall not exceed the weight limitations of the applicable box specification.

5.2.2 Level B. Ten intermediate packages of cards sizes 3 x 5 or 4 x 6, or five intermediate packages of cards sizes 5 x 8, shall be packed in a fiberboard shipping container conforming to PPP-B-636, class domestic, minimum grade 275.

5.2.3 Level C. Packing shall be in accordance with the manufacturer's standard commercial practice. Shipping containers shall comply with the requirements of the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. Containers shall be marked in accordance with Fed. Std. No. 123, or as specified in the contract or order.

5.3.2 Military agencies. Containers shall be marked in accordance with MIL-STD-129, or as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Grade and size required (see 1.2.1 and 3.5).
(c) Weight and color (see 3.2 and 3.3).
(d) Form required (see 3.6).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(f) Special markings required (see 5.3.1 and 5.3.2).

6.2 Former classification. The following grades have been deleted from this specification:

Grade A - 100 percent cotton or linen.
Grade B - 50 percent cotton or linen.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

6.3 Standard comparison samples may be obtained upon application to the procuring agency issuing the invitation for bids.

Preparing activity:
GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.