UU-P-63J
May 30, 1972
SUPERSEDING
Int. Fed. Spec. UU-P-0063H(GSA-FSS)
February 7, 1972 and
Fed. Spec. UU-P-63F
December 1, 1965

FEDERAL SPECIFICATION

PAPER, BLOTTING

This specification was approved by the Commissioner, Federal Supply Sevice, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The specification covers white and colored blotting paper.

1.2 Classification. Blotting paper shall be of one grade.

Grade B - White and colored blotting paper.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-P-25 - Printing and Stationery Paper, Packaging and Packing of.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Forth Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:19Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Asssociation, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Technical Association of the Pulp and Paper Industry (TAPPI) Standards:

T402 - Standard Conditioning and Testing Atmosphere for Paper, Board, Pulp Handsheets and related Products.
T403 - Bursting Strength of Paper.
T410 - Weight per Unit Area (Basis Weight or Substance) of Paper and Paperboard.
T431 - Ink Absorbency of Blotting Paper.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, One Dunwoody Park, Atlanta, GA 30341.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard sample. The color, finish, and formation shall conform to the standard sample as furnished by the contracting officer.

3.2 Material. Blotting paper shall be made from fibrous, cellulosic material which may include reclaimed fiber.

3.3 Color. Blotting paper shall be brown, light green, moss green, or white as specified (see 6.2) and shall conform to the standard sample (see 3.1).

3.4 Physical requirements. The blotting paper shall conform to the physical requirements set forth in Table I.

TABLE I. Physical requirements

Characteristic	Grade B
Basis weight, 19 × 24-1000	200 pounds ± 5 percent
Burst, average not less than	25 pounds per square inch (psi)
Absorption of 1 milliliter (ml.) inks, not more than	50 seconds

3.5 Size and trim. Blotting paper shall be furnished in the size(s) ordered and must be flat, trimmed square on four sides with clean, smooth edges and evenly jogged. Paper must not be undersize and not more than 1/8 inch oversize in either direction, except for sheets 8-1/2 × 14 inches or smaller. On sheets up to and including 8-1/2 × 14 inches, paper shall not be undersize and not more than 1/16 inch oversize in either direction, and no successive sheets within any package shall differ from each other by more than 1/32 inch. Paper shall be considered square if the diagonal variation does not exceed 1/16 inch.

3.6 Workmanship. Grade B blotting paper covered by this specification shall be clean, free from dirt spots, oil spots, shives, foreign matter, and shall be uniform in color. The sheets shall be free from holes, tears,cuts, folds, scuff marks, lint, or loose particles. There shall be no splices within a sheet and there shall be no partial sheets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1Sampling for inspection. Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.2 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) shown in table II. Each inspection lot sampled shall consist of one grade and color of blotting paper.

TABLE II. Sampling procedure.

Examination paragraph	Lot size units	Sample unit	Inspection level	AQL percent defective
4.3.1.1	Shipping containers	Shipping container	S-2	1/
4.3.1.2	Packages or bundle	Package or bundle	S-2	NA
4.3.1.3	Packages or bundles	Package or bundle	S-2	NA
4.3.1.4	Sheets	Sheets	S-3	1.5
4.3.1.5	Sheets	Sheets	S-4	4.0

1/ Acceptable quality level shall be as specified in PPP-P-25.

4.3.1.1 Examination of preparation for delivery. An examination shall be made to determine that the packaging, packing, and marking requirements comply with PPP-P-25.

4.3.1.2 Examination of the end item for count. The lot shall be unacceptable if the average number sheets per package or bundle, of all sample units examined, is less than specified or indicated.

4.3.1.3 Examination of the end item for color uniformity. The lot shall be unacceptable if the color of the sheets is not uniform within the package or bundle and throughout the lot.

4.3.1.4 Examination of the end item for dimensional defects. The sample unit for this examination shall be one sheet. The number of sheets comprising the sample size, as specified in table II for this examination shall be made up by taking two consecutive sheets from one ream (to count as two sample units). Examine each sheet for the defects listed below.

Examine	Defect
Sheet size	Less than specified in length or width.
Sheets 8-1/2 by 14 inches or less	Oversize by more than 1/16 inch along any edge, from size specified.
Sheets over 8½ by 14 inches	Oversize by more than 1/8 inch along any edge, from size specified.
Squareness	Diagonal variation exceeds 1/16 inch.
Consecutive sheets	Successive sheets differ from each other by more than 1/32 inch in either dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

4.3.1.5 Examination of the end item for visual defects. The sample unit for this examination shall be one sheet. The number of sheets required in accordance with table II shall be randomly selected from the packages or bundles selected under 4.3.1.2; as applicable, an equal number of sheets shall be taken from each package or bundle sampled. Examine both sides of the sample unit for the defects listed below.

Examine	Defect
Appearance	Color not as specified; not uniform throughout on both sides; does not compare favorably with standard sample. Finish does not compare favorably with standard sample. Presence of holes, dirt, or oil spots larger than 0.5 millimeter (mm) in area, lumps, foreign matter, slivers, or shives.
Workmanship	Sheets not trimmed clean; ragged, torn, uneven, or crushed edge. Any tear, cut, crease, wrinkle, fold, chafed or scuff mark.

4.3.2 Testing of the end item. The end item shall be tested for the applicable characteristics as specified in section 3 for each lot presented for examination for each size or color of material. The tests shall be made in accordance with the indicated TAPPI method or as referenced in table III. The lot size shall be expressed in units of blotting paper of one size. The test sample unit shall consist of 3000 square inches of paper and the sample size shall be selected in accordance with S-1. Test results shall include all values on which the results are based and there shall be no failure to meet the lot average or sample unit requirements. All samples shall be conditioned and tested in accordance with the provisions of TAPPI T402.

TABLE III. Testing of the end item.

Characteristic	Specification reference		Requirements applicable to	Results reported as Pass or fail Nearest
	Requirement	Test method		
Atmospheric conditions	4.3.2	T402	All testing	
Basis weight	Table I	T410	Lot average	1 pound
Burst	Table I	T403	Lot average	1 psi
Absorption	Table I	T431	Sample unit	1 second

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. Packaging, packing, and marking shall be level A, B, or C, as specified (see 6.2) and shall be in accordance with PPP-P-25.

6. NOTES

6.1 Intended use. Blotting paper in accordance with this specification is intended for dark blotters and hand blotters.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification
(b) Color (see 3.3)
(c) Size and trim (see 3.5)
(d) Selection of applicable level of packaging, and packing, and marking required (see 5.1).

6.3 Standard comparison samples may be obtained upon application to the procuring agency issuing the invitation for bids.

6.4 Grade A blotting paper described in UU-P-63F and UU-P-0063G has been deleted from this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:
Army-GL
Navy-SA
Air Force-69

Preparing activity:
GSA-FSS

Coordinating activities:
COMMERCE-NBS
GPO

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.