UU-T-0085A(GSA-FSS)
March 15, 1971
SUPERSEDING
Int. Fed. Spec. UU-T-0085(GSA-FSS)
January 14, 1965

INTERIM FEDERAL SPECIFICATION

TAPE, CORRECTION

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers pressure-sensitive correction tape of one type and grade, with easily removable liner to protect the adhesive prior to application of the tape. (See 6.1.)

1.2 Classification.

1.2.1 Sizes. Correction tape covered by this specification shall be of the following sizes based on the width (see 6.2):

Size 1 - 1/6-inch width.
Size 2 - 2/6-inch width.
Size 3 - 5/6-inch width.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

Federal Specifications:

O-D-825 -- Duplicating Fluid, Direct Process (Spirit-Type).
UU-P-150 -- Paper, Carbon, Duplicating Machine, Spirit-Process.
UU-P-228 -- Paper, Set, Duplicating Master Spirit or Liquid Process.
UU-P-232 -- Paper, Duplicating, Copy, Liquid Process.
UU-P-233 -- Paper, Duplicating, Master, Spirit-Process.
PPP-B-566 -- Boxes, Folding, Paperboard.
PPP-B-636 -- Box, Fiberboard.
PPP-B-665 -- Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 -- Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 -- Marking for Domestic Shipment (Civil Agencies).
Fed. Std. No. 147 -- Tapes, Pressure-Sensitive and Gummed; Methods of Inspection, Sampling, and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of the specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-L-10547 -- Liners, Case, and Sheet, Overwrap Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 -- Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI) Test Methods:

T 402 os-49 - Conditioning Paper and Paperboard for Testing.
T 404 ts-66 - Tensile Breaking Strength of Paper and Paperboard.
T 410 os-68 - Weight per Unit Area (Basis Weight or Substance), Paper and Paperboard.
T 411 os-68 - Thickness (Caliper) of Paper and Paperboard.
T 425 m-60 - Opacity of Paper.
T 452 os-58 - Brightness of Paper and Paperboard.
T 479 sm-48 - Smoothness of Printing Paper.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, N. Y. 10017.)

American Society for Testing and Materials:

ASTM D 2240-68 - Indentation Hardness of Rubber and Plastics by Means of a Durometer.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., Agent, 1616 P Street, N. W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 W. Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Paper. The paper shall be made from 100 percent bleached chemical woodpulp. The paper shall be uniform texture with smoothly finished surface and shall be suitably sized so that inked impressions from typewriter ribbons, ball point pens, and drawing ink will be well defined and will not feather. The paper shall be in conformance with the physical requirements in table I when tested by the applicable test methods specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

Table I. Physical requirements for paper without adhesive

Characteristic	Requirement	TAPPI Test Method No.
Basis weight, 25 x 38-500, minimum pounds	42.5	T 410 os-68
Tensile breaking strength, minimum, average:		T 404 ts-66
Machine direction, pounds/inch width	20	
Cross direction, pounds/inch width	10	
Finish (smoothness), minimum, seconds, average	50	T 479 sm-48, Bekk
Thickness, inch, average	0.0025 ± 0.0005	T 411 os-68
Opacity, percent, minimum, average	83	T 425 m-60
Brightness, percent, minimum, average	80	T 452 os-58

3.1.2 Adhesive. The adhesive shall be pressure-sensitive, i.e., no moisture, heat, or other external agent shall be required to bond the tape to the paper surface. The tape shall adhere immediately to the paper surface without wrinkling, curling, or lifting at any place, and there shall be no evidence of excessive adhesive in the form of edge ooze. When the liner is removed from the tape, the adhesive shall not separate from the paper and appear as a residue on the liner (see table II).

3.1.3 Liner. The liner for protecting the adhesive shall be a material that can be easily removed from the tape without causing breaking or delamination of the tape or liner (see 3.4).

3.2 Construction. The correction tape shall be constructed of paper meeting the requirements in table I. The wire side of the paper shall be evenly coated with adhesive (see 3.1.2). A liner (see 3.1.3) shall be applied to the adhesive side of the tape and shall be of sufficient width to extend not less than 1/32 inch beyond each side of the tape.

3.3 Adhesion of tape.

3.3.1 Initial adhesion. When determined as specified in 4.5.1, the initial adhesion of the pressure sensitive tape shall be not less than 60.0 ounces per inch of width.

3.3.2 Adhesion after aging. When determined after aging for ten days at a temperature of 60° ± 2°C (140° ± 3.6°F) as specified in 4.5.2.1, the adhesion of the pressure sensitive tape shall be not less than 60.0 ounces per inch of width.

3.4 Adhesion of tape to liner (quick release). When determined as specified in 4.5.3, the average force required to separate the liner from the tape shall be not more than 15 grams (0.5 ounces) per inch of width.

3.5 Duplicating quality. When applied to a spirit master, imaged with spirit carbon, and processed with spirit-type duplicating fluid as specified in 4.5.4, correction tape shall reproduce impressions on liquid-process copy paper equivalent in intensity, faithfulness, legibility, and cleanliness to the impressions made from the spirit master. The tape shall remain in place during the test, and the tape and typed images thereon shall show no evidence of damage from the duplicating fluid.

3.6 Dimensions of tape.

3.6.1 Length. The minimum length of the tape shall be 600 inches.

3.6.2 Width. The tape shall be 1/6, 2/6, and 5/6 inch in width as specified (see 1.2.2 and 6.2). A plus tolerance of 1/64 inch will be permitted.

3.7 Rolls. The tape shall be wound on itself to form rolls not exceeding 3 inches in diameter. The liner shall be on the outside of the roll.

3.8 Dispensers. Each roll of tape shall be contained in a dispenser of sufficient strength to adequately retain and dispense the entire roll of tape. The dispensers shall be designed in such a manner that during the dispensing operation the tape and liner will separate by pulling the free end of the liner. Each dispenser shall be equipped with a serrated metal cutting edge sufficiently sharp to cut the tape cleanly without causing the tape to wrinkle or tear unevenly. All other edges of the metal cutting device shall be rounded to prevent physical injury to the user.

3.9 Color. The exposed surface of the tape shall be white and shall show no discoloration after aging for ten days at 60° ± 2°C (140° ± 3.6° F), as specified in 4.5.2.1 and examining as specified in 4.5.2.2.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:19Z
Check the source to verify that this is the current version before use.

3.10 Identification marking. The dispensers for the tape shall be marked with the name or trademark of the manufacturer, the Federal Stock Number, and the date of manufacture of the tape.

3.11 Workmanship. Tape and dispensers shall be free from defects which may affect their serviceability, durability, or appearance. Occurrence of defects shall not exceed the applicable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the examination and testing set forth in the specification where such are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3 Inspection of components and materials. In accordance with 4.1, the supplier is responsible for insuring that components and materials used were manufactured, examined, and tested in accordance with the specified requirements of referenced subsidiary specifications and standards or if none, in accordance with this specification.

4.3.1 Sampling and testing of paper component. For the purpose of testing the paper component of correction tape, each lot shall consist of all finished paper, prior to application of the adhesive, of the same type or grade manufactured by the same source, under essentially the same conditions and identified as used in the production of the quantity of the end item submitted for inspection at one time. Samples shall be drawn from the lot in accordance with level S-1 of MIL-STD-105. The sample unit shall be not less than 13 square feet of paper. The finished paper shall be tested for conformance with the requirements for characteristics in table I in accordance with the applicable TAPPI test method specified in table I. Test results shall include all values upon which the results are based. There shall be no failure to meet the test unit requirements. All test units shall be conditioned and tested in accordance with TAPPI Method T 402 os-49.

4.3.2 Report of analysis. In lieu of using his own facilities, the contractor may submit a report of analysis of the component materials from a laboratory acceptable to the Government as evidence of compliance with the specification requirements. The report of analysis shall include, in addition to the actual test data, the manufacturer's name, name and address of the testing laboratory, date of test, and quantity of material represented by the test report.

4.3.3 Evidence of compliance. Where reports of analysis are submitted, the Government reserves the right to check test such items to determine the validity of the analysis.

4.4 Sampling, examination, and testing of end item.

4.4.1 Lot. For purposes of examination and testing, a lot shall consist of all rolls of tape of the same width, each in a dispenser, offered for delivery at one time.

4.4.2 Visual examination. Correction tape in dispensers shall be examined for visual defects in table II. The inspection level shall be II, and the acceptable quality level (AQL) 2.5 percent defective. The unit for visual examination shall be one roll of tape in a dispenser. If any unit in the sample for examination fails to meet any requirement for which examination is made, it shall be considered defective. If the number of defective units in the sample exceeds the acceptance number in MIL-STD-105, the entire lot shall be considered as having failed to meet the requirements of the specification.

4.4.3 Dimensional examination. Correction tape from dispensers shall be examined for conformance with dimensional requirements in table II. The inspection level shall be S-2 and the acceptable quality level (AQL) 4.0 percent defective. If any unit in the sample fails to meet any dimensional requirement in table II, it shall be considered defective. If the number of defective units in the sample exceeds the acceptance number specified in MIL-STD-105, the entire lot shall be considered as having failed to meet the requirements of the specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:19Z
Check the source to verify that this is the current version before use.

Table II. Visual and dimensional defects.

Examination	Defect
VISUAL DEFECTS	
Paper	Not uniform in texture. Not smooth surface finish. Not suitably sized to accept inks specified in 3.1.1.
Adhesive	Not pressure sensitive. Tape wrinkles, curls, or lifts; does not adhere immediately to paper surface to which applied. Evidence of edge ooze.
Liner	Adhesive separates from tape and deposits on liner. Liner not easily removed from tape. Tape or liner breaks or delaminates.
Construction	No adhesive coating on one side of tape. Edges uneven or broken. Liner not applied to side of tape covered with adhesive.
Color	Not white.
Dispenser	Tape not furnished in dispensers as specified in 3.8. Dispensers not marked as specified in 3.10.
Roll	Tape not wound on itself. Tape spliced.
DIMENSIONAL DEFECTS	
Length of tape	Less than 600 inches.
Width of tape	Less than or more than specified in 3.6.2.
Extension of liner	Liner extends less than 1/32 inch beyond each side of tape.

4.4.4 Examination of preparation for delivery. An examination shall be made to determine compliance with the packaging, packing, and marking requirements of section 5. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 and the acceptable quality level (AQL) 6.5 defects per one hundred units. Defects shall be as specified in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

Table III. Preparation for delivery defects

Examination	Defect
Markings (exterior and interior)	Omitted; incorrect; or improper size, location, sequence, or method of application. Illegible.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate sealing. Bulging or distortion of container.
Packaging and packing	Case liners not sealed. Contents more or less than specified.

4.4.5 Testing of end item. A random sample of rolls and dispensers shall be taken from the lot in accordance with MIL-STD-105, inspection level S-1, and acceptable quality level (AQL) 4.0 percent defective. The sample unit shall be 5 rolls of tape. If the tape fails to meet any requirement for which tests are made, the sample unit shall be considered defective. If the number of defective sample units in the sample for test exceeds the acceptance number in MIL-STD-105, the entire lot of tape shall be considered as having failed to meet the requirements of this specification.

4.5 Test methods for end item. Correction tape shall be subjected to the following tests under atmospheric conditions specified in method 1 of Fed. Std. No. 147.

4.5.1 Adhesion. The adhesion of tape shall be determined as described in method 10 of Fed. Std. No. 147. Five specimens shall be tested, one from each roll of tape in the sample unit, and the average value obtained for the five specimens checked for conformance with 3.3.2.

4.5.2 Resistance to aging.

4.5.2.1 Adhesion after aging. The five rolls of tape in the sample unit shall be aged for the required time at the required temperature (see 3.3.2) as described in method 62 of Fed. Std. No. 147. Five specimens, one from each roll of tape in the sample unit shall be taken from the aged rolls and the adhesion after aging determined as specified in 4.5.1. The average value obtained for the five specimens shall be checked for conformance with 3.3.2.

4.5.2.2 Color after aging. A specimen of unaged tape shall be compared with a specimen of the aged tape for conformance with 3.9.

4.5.3 Adhesion of tape to liner (quick release). The force required to separate the liner from the tape shall be determined by method 12 of Fed. Std. No. 147. Five specimens shall be tested, one from each roll in the sample unit, and the average value obtained for the five specimens shall be checked for conformance with 3.4.

4.5.4 Duplicating quality. The materials listed below shall be used in this test:

Material	Federal Specification and type (as applicable)
Paper, Set, Duplicating Master Spirit or Liquid Process	UU-P-228
Paper, Duplicating, Master, Spirit Process	UU-P-233
Paper, Carbon, Duplication Machine, Spirit Process	UU-P-150
Paper, Duplicating, Copy, Liquid Process	UU-P-232
Duplicating Fluid, Direct Process, Spirit Type	O-D-825

The preparation of the spirit master shall be made on an electric typewriter with pica type, in good condition. The typewriter shall be equipped with a ribbon not more than 0.0050 inch thick and a platen having a durometer hardness of 89 to 93 when determined in accordance with ASTM D 2240-68, or an equivalent platen designed for the preparation of spirit masters on the machine being used. The type faces shall be thoroughly cleaned before each test.

Insert in the typewriter, the spirit master and carbon properly assembled, or an equivalent spirit master paper set. Form two columns on the spirit master, each composed of ten typed lines of the lower case letters shown below, with triple spacing between each line:

"aegkmnprsw" "aegkmnprsw"

Cover the ten typed lines in one column with correction tape and replace the covered letters by typing on the correction tape. Using the master, run 300 copies on a spirit processing machine. Examine the duplicated copies for compliance with 3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:19Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. The tape, in individual dispensers, in quantities shown in table IV, shall be packaged in close-fitting boxes conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be adequately closed to prevent accidental opening.

5.1.2 Level B. The rolls of tape shall be packaged as specified in 5.1.1.

5.1.3 Level C. The tape shall be packaged in accordance with the supplier's standard practice providing that this will insure protection for the tape during shipment and safe delivery to its destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The tape packaged as specified in 5.1 shall be packed in quantities as specified in table IV in close-fitting boxes conforming to PPP-B-636, class weather resistant, grade V3c. Close, waterproof seal, and strap the box in accordance with appendix to PPP-B-636. When specified (see 6.2) each shipping container shall be provided with a case liner conforming to MIL-L-10547. Closure and sealing shall conform to the appendix thereto.

5.2.2 Level B. The tape packaged as specified in 5.1 shall be packed in quantities as specified in table IV in close-fitting boxes conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Tape packaged as specified in 5.1 shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification rules or the National Motor Freight Classification rules.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Table IV.

Width (Inch)	No. of rolls per unit package	No. of unit packages per shipping container	No. of rolls per shipping container
1/6	5	100	500
2/6	3	100	300
5/6	2	100	200

6. NOTES

6.1 Intended use. Correction tape is intended primarily for use in correcting and revising prepared photo-offset masters, spirit duplicating masters, and other manuscripts and documents so that they are satisfactory for duplication (see 3.5).

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Width required (see 1.2.1 and 3.6.2).
(c) Level of packaging and packing, and any special marking required (see 5.1, 5.2, and 5.3).

MILITARY INTEREST:

DOD coordination has been waived.

GSA DC 71.12287

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:19Z
Check the source to verify that this is the current version before use.