FED. SUP CLASS
5940



STYLE 1 STYLE 2

DASH NO.	THICKNESS OF MOUNTING	L ±.005	STYLE	SUPERSEDES
-5	3/32	1/8	1	-1
-6			2	-2
-7	5/32	3/16	1	-3
-8			2	-4
-9	7/32	1/4	1	
-10			2	
-11	9/32	3/8	2	

NOTES:

1. MATERIAL: BRASS, QQ-B-626, COMP. 22, 1/2 HARD.
2. FINISH: (a) TIN PLATED IN ACCORDANCE WITH MIL-T-10727, TYPE I, .0003 MIN. THICKNESS OR TYPE II, .0001 MIN. THICKNESS.
   OR
   (b) TIN-LEAD PLATED IN ACCORDANCE WITH MIL-P-81728, .0003 MIN. THICKNESS (COPPER UNDERPLATE NOT REQUIRED).
3. THREADS SHALL BE IN ACCORDANCE WITH HANDBOOK H28.
4. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, DECIMALS SHALL HAVE A TOLERANCE OF ±.005. INTERPRET IN ACCORDANCE WITH USASI Y14.5-1966 (ANSI).
5. FOR MOUNTING NUT SEE MS35649.
6. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.

FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS.

(B) ENTIRE STANDARD REVISED

APPROVED 21 JUNE 1960 REVISED (A) 6 MARCH 1963 (B) 12 Oct 1972

This military standard is approved by NAVAL AIR SYSTEMS COMMAND, Department of the Navy and shall be used by that activity. All other military activities are required to employ this standard where suitable.

P.A. NAVY - AS Other Cust	TITLE TERMINAL, STUD THREADED DOUBLE TURRET	MILITARY STANDARD MS17172 (AS)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: MS17172(WEP)	SHEET 1 OF 1

DD FORM MAR 72 672-1 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. PLATE NO. 23071

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:04Z
Check the source to verify that this is the current version before use.