FED. SUP CLASS
5305

DIE CAST ZINC AND ALUMINUM

SCREW SIZE	MATERIAL THICKNESS	HOLE DIA	DRILL SIZE NO.
2 (.086)	.060	.073	49
	.083	.073	49
	.109	.076	48
	.125	.076	48
	.140	.076	48
4 (.112)	.109	.098	40
	.125	.100	39
	.140	.100	39
	.188	.100	39
	.250	.102	38
6 (.138)	.125	.120	31
	.140	.120	31
	.188	.120	31
	.250	.125	1/8
	.312	.125	1/8
8 (.164)	.125	.149	25
	.140	.149	25
	.188	.149	25
	.250	.152	24
	.312	.152	24
10 (.190)	.125	.166	19
	.140	.166	19
	.188	.166	19
	.250	.170	18
	.312	.172	11/64
	.375	.172	11/64
1/4 (.250)	.125	.221	2
	.140	.221	2
	.188	.221	2
	.250	.228	1
	.312	.228	1
	.375	.228	1

PLASTICS

SCREW SIZE	PHENOL FORMALDEHYDE				CELLULOSE ACETATE, CELLULOSE NITRATE, ACRYLIC RESIN, STYRENE RESIN			
	HOLE DIA	DRILL SIZE NO.	DEPTH OF PENETRATION		HOLE DIA	DRILL SIZE NO.	DEPTH OF PENETRATION	
			MIN	MAX			MIN	MAX
2 (.086)	.078	5/64	.094	.250	.076	48	.094	.250
4 (.112)	.104	37	.125	.312	.100	39	.125	.312
6 (.138)	.125	1/8	.188	.375	.120	31	.188	.375
8 (.164)	.147	26	.250	.500	.144	27	.250	.500
10 (.190)	.170	18	.312	.625	.166	19	.312	.625
1/4 (.250)	.228	1	.375	.750	.221	2	.375	.750

NOTES:

1. Because conditions vary widely, it may be necessary to change the hole size to suit a particular application.
(B) 2. All dimensions are in inches. Hole diameters are standard drill sizes rounded to nearest .001 inch.
3. For aeronautical purposes, more definitive hole dimensions are contained in AND10325.
4. Referenced documents shall be of the issue in effect on date of invitations for bid.
5. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

(B) THIS IS A DESIGN STANDARD AND SHALL NOT BE USED AS A PART NUMBER.

REVIEWER: AV, IS, MI, MSA, 85,
USER: AS, AT, CL, MC, ME, OS, SN

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 5 OCT 1959 REVISED (A) 7 JUN 1961 (B) 27 AUG 1969

P.A. MC Other Cust 82	TITLE SCREW, TAPPING-THREAD CUTTING, TYPES BF AND BT, APPROXIMATE HOLE SIZES FOR	MILITARY STANDARD MS 24633
PROCUREMENT SPECIFICATION NOTE	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (Reverse)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:58Z
Check the source to verify that this is the current version before use.