MIL-C-14994 (MU)
2 December 1968
SUPERSESSION DATA
(see 6.3)

MILITARY SPECIFICATION

CHARGE PROPELLING, 152MM, XM189 AND XM190, LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers two types of propelling charges used with 152MM Ammunition. These propelling charges are designated as follows:

Charge, Propelling, 152MM, XM189 for Cartridges XM409, XM410 and XM411 and XM625

Charge, Propelling, 152MM, XM190 for Cartridge XM657

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

9207817 - Charge, Propelling, 152MM for Cartridges XM409, XM410, XM411 and XM625
9235780 - Charge, Propelling, 152MM, XM190 for Cartridge XM657

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-90 - Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles

(The Interstate Commerce Commission Regulations are now a part of the Code of Federal Regulations (1949 Edition and Revisions) available from the Superintendent of Documents, Government Printing Office, Washington, D. C. Orders for the above publications should cite "49 CFR 71-90 (latest revisions).")

3. REQUIREMENTS

3.1 Materials.-All materials shall be in accordance with applicable drawings and specifications.

3.2 Propelling charge.-The propelling charge shall comply with all the requirements specified in Drawing (dwg.) 9207817 (or dwg. 9235780, as applicable), and with all other applicable requirements in this specification.

3.3 Propelling charge weight.-The charge weight of M26E1 propellant shall comply with the weight specified in the loading authorization within a tolerance of plus or minus 0.2 ounces.

3.4 Workmanship.-All components and assemblies shall be free of dirt, grease and other foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 Lot formation.-A lot shall consist of charges produced by one manufacturer in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The examinations and tests listed herein shall be performed on inspection lots submitted in accordance with Standard MIL-STD-105 or MIL-STD-1235, as applicable. The criteria and procedures for assignment of lot numbers shall be in accordance with MIL-STD-1168. A propelling charge lot shall contain no more than one lot of propellant.

4.2.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each Major defect and an AQL of 0.65 percent for each Minor defect.

4.2.2.1 Charge, Propelling (see dwg. 9207187 or 9235780 as applicable).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Major:		AQL 0.65 percent	
101.	Closing seam missing	Visual	01001
102.	Any seam broken or incomplete to the extent that propellant can escape	Visual	01002
103.	Assembly damaged to the extent that propellant can escape	Visual	01003
Minor:		AQL 1.0 percent	
201.	Marking incorrect, misleading or unidentifiable	Visual	01004
202.	Poor workmanship (see 3.4)	Visual	01005

4.2.3 Testing

4.2.3.1 Propelling charge weight (see 3.3) - Major defect - Code No. 01006.-The charges shall be weighed and check weighed 100% using any suitably calibrated, Government-approved scale. The check weighing shall be accomplished independently of the original weighing and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and removed from the lot.

4.2.4 Inspection equipment.-The contractor shall have available and utilize correctly all inspection equipment necessary for the performance of the inspections listed herein.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Level C.-Propelling charge assemblies shall be packed in accordance with Code of Federal Regulations 40 CFR 71-90 and to afford protection against damage during shipment from supply source to the first receiving activity for immediate use. Containers shall conform to the carrier rules and regulations applicable to the mode of transportation utilized.

5.2 Marking.-In addition to any marking required by the contract or order, marking shall be in accordance with Standard MIL-STD-129 and Code of Federal Regulations 49 CFR 71-90.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspection herein are to facilitate future data collection and analysis by the Government.

6.3 Supersession data.-This specification supersedes Picatinny Arsenal Purchase Description PA-PD-2748, dated 5 January 1966.

Custodian
Army-MU

Preparing activity:
Army-MU

Project No. 1320-A147

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.