MIL-P-14997A (AR)
19 MAY 1988
SUPERSEDING
MIL-P-14997 (AR)
15 October 1981

MILITARY SPECIFICATION

PROJECTILE, 105MM, ILLUMINATING, M314A3
LOADING ACCESSORIES FOR

This specification is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department for Defense.

1. SCOPE

1.1 Scope. This specification covers Projectile, 105MM: Illuminating, M314A3 Loading Accessories for

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specificaiton For
MIL-W-12332	-	Welding, resistance, spot, seam, projection, for fabricating assemblies of low-carbon steel
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:20Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-151	-	Metal, Test Methods

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9206744	-	Projectile, 105MM, Illuminating, M314A3, Loading Assembly
9206749	-	Illuminating Canister Loading Assembly
9206750	-	Canister Base Assembly

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI-B46.1	-	Surface Texture

(Applications for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N.Y. 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

ASTM Method B117 - Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, and referenced specifications.

3.2 Hardness of canister body. The hardness of the canister body shall fall within the range specified on dwg. 9206756 when tested as specified in 4.5.3.

3.3 Strength of weld. The weld securing the brake and body shall withstand a pull as outlined in Specification MIL-W-12332, para 7.3.3 and 4.5.4 herein.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of the first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. The requirements for workmanship are as detailed on the applicable drawings, in the applicable specifications and the following:

3.5.1 Surface finish. The requirements for surface finish shall be as specified on the applicable drawings.

3.5.2 Protective coating. Protective coating shall be in accordance with the applicable drawing and the specifications listed thereon.

3.5.3 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required by the applicable drawing and shall be in accordance with the provisions of MIL-A-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

3.5.4. Burr and sharp edges. No part shall have a burr or sharp edge which might interfere with the assembly or function of the round or which might be injurious to personnel handling the item.

3.5.5 Foreign matter. No part or assembly shall contain dirt, grease, chips, oil, rust, corrosion or other foreign matter.

3.5.6 Painting. Painting shall comply with the requirements of the applicable drawing. All paint shall be dry to the touch before packing for shipment. Drying time prior to testing shall be in accordance with applicable specification.

3.5.7 Cloth. All cloth shall be free of tears, rips and foreign matter. The stitches in the cloth shall be neat and continuous without breaks, tears or foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection

b. Quality conformance inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities as indicated:

Part Description	Drawings	Quantity
Gasket, Baffle	9206745	5
Nut, swivel pin	9206764	10
Plate, swivel pin	9206766	5
Pin, swivel	9206753	5
Plate, base	9206754	5
Base	9206752	5
Canister base assembly	9206750	10
Body	9206756	5
Disc, assembly	9206761	5
Rotation brake	9206757	5
Canister body assembly	9206755	10
Bag parachute	9227195	5
Parachute assembly	9206766	5
Support, parachute	9206751	5
Plate, shroud	9206771	10
Pin, groove	9278187	5

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I herein. First article samples designated for a salt spray test shall be subjected for 96 hours in accordance with the procedure specified in 4.5.2. After exposure, samples shall be examined and compared with unexposed samples for the effects of corrosion. Any evidence of corrosion on the test samples shall be cause for rejection.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Projectile, 105MM Illuminating, M314A3				See Contents
					NEXT HIGHER ASSEMBLY
					N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Gasket, Baffle (Dwg. 92066745)				
	Examination for Defects	5		3.1	4.4.2.1
	Nut, Swivel Pin (Dwg. 9206764)				
	Examination for Defects	5		3.1	4.4.2.2
	Salt Spray Test	5		3.1	4.3.2/4.5.2
	Plate, Swivel Pin (Dwg. 9206766)				
	Examination for Defects	5		3.1	4.4.2.3
	Pin, Swivel (Dwg. 9206753)				
	Examination for Defects	5		3.1	4.4.2.4
	Plate, Base (Dwg. 9206754)				
	Examination for Defects	5		3.1	4.4.2.5
	Base (Dwg. 9206752)				
	Examination for Defects	5		3.1	4.4.2.6
	Canister Base Assembly (Dwg. 9206750)				
	Examination for Defects	5		3.1	4.4.2.7
	Salt Spray Test	5		3.1	4.3.2, 4.5.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	Projectile, 105MM Illuminating, M314A3				See Contents
					NEXT HIGHER ASSEMBLY
					N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 9206756)				
	Examination for Defects	5		3.1	4.4.2.8
	Disc, Assembly (Dwg. 9206761)				
	Examination for Defects	5		3.1	4.4.2.9
	Rotation Brake (Dwg. 9206757)				
	Examination for Defects	5		3.1	4.4.2.10
	Canister Body Assembly (Dwg. 9206755)				
	Examination for Defects	5		3.1	4.3.2.11
	Salt Spray Test	5		3.1	4.3.2, 4.5.2
	Bag Parachute (Dwg. 9227195)				
	Examination for Defects	5		3.1	4.4.2.12
	Parachute Assembly (Dwg. 9206766)				
	Examination for Defects	5		3.1	4.4.2.13
	Support, Parachute (Dwg. 9206751)				
	Examination Defects	5		3.1	4.4.2.14

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-01-18T05:20Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
	Projectile, 105MM Illuminating, M314A3				See Contents
					NEXT HIGHER ASSEMBLY
					N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Shroud (Dwg. 9206771)				
	Examination for Defects	5		3.1	4.4.2.15
	Salt Spray Test	5		3.1	4.3.2, 4.5.2
	Pin, Groove (Dwg. 9279187)				
	Examination for Defects	5		3.1	4.4.2.16

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-18 05:202
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-1235 or MIL-STD-105 as applicable.

b. Automatic gaging. Facilities equipped with Government furnished automatic gaging capable of performing 100% inspection of any characteristic shall utilize capability in accordance with contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206745
4.4.2.1	Gasket, Baffle				NEXT HIGHER ASSEMBLY 9206744
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Presence of three (3) slots		0.65%	3.1	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

10

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206764
4.4.2.2	Nut, Swivel Pin				NEXT HIGHER ASSEMBLY 9206746
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.1	Gage
102	Minor diameter of thread, max.		0.40%	3.1	Gage
Minor					
201	Distance across flats, max.		0.65%	3.1	Gage
202	Thickness		0.65%	3.1	Gage
203	Surface finish improper		0.65%	3.1	Visual/4.5.1
204	Protective finish inadequate		0.65%	3.1	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2024-04-05 05:26
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206777
4.4.2.3	Plate, Swivel Pin				NEXT HIGHER ASSEMBLY 9206746
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Inside diameter, min.		0.65%	3.1	Gage
202	Thickness, min.		0.65%	3.1	Gage
203	Protective finish inadequate		0.65%	3.1	Visual
204	Surface finish improper		0.65%	3.1	Visual/4.5.1
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2024-07-31 05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Pin, Swivel				9206753
					NEXT HIGHER ASSEMBLY 9206750
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defiend				
Major					
101	Pitch diameter of thread		0.40%	3.1	Gage
102	Major diameter of thread		0.40%	3.1	Gage
Minor					
201	Large diameter		0.65%	3.1	Gage
202	Diameter of ball (fwd and aft)		0.65%	3.1	Gage
203	Total length		0.65%	3.1	Gage
204	Distance from base to aft shoulder		0.65%	3.1	Gage
205	Distance from base to ball race shoulder		0.65%	3.1	Gage
206	Thickness of ball race flange		0.65%	3.1	Gage
207	Full thread length,min.		0.65%	3.1	Gage
208	Surface finish improper		0.65%	3.2	Visual/4.5.1
209	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: [illegible]
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.5	Plate, Base		1 OF 1	9206754
				NEXT HIGHER ASSEMBLY: 9206750

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.1	Gage
202	Thickness		0.65%	3.1	Gage
203	Surface finish improper		0.65%	3.1	Visual/4.5.1
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: Sep 6 08:10:52
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Base	1 OF 1	9206752
			NEXT HIGHER ASSEMBLY 9206750

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter of flange		0.65%	3.1	Gage
202	Outside diameter of base plate cavity		0.65%	3.1	Gage
203	Inside diameter of base plate cavity		0.65%	3.1	Gage
204	Inside diameter of bearing bore		0.65%	3.1	Gage
205	Outside diameter of bearing bore boss		0.65%	3.1	Gage
206	Diameter of hole		0.65%	3.1	Gage
207	Total length		0.65%	3.1	Gage
208	Distance from face to flange		0.65%	3.1	Gage
209	Thickness of flange		0.65%	3.1	Gage
210	Depth of base plate cavity		0.65%	3.1	Gage
211	Depth of bearing bore		0.65%	3.1	Gage
212	Radius missing		0.65%	3.1	Gage
213	Surface finish improper		0.65%	3.1	Visual/4.5.1
214	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 88 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-[illegible]
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206750
4.4.2.7	Canister Base Assembly				NEXT HIGHER ASSEMBLY 9206749
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Swivel does not rotate freely		0.40%	3.1	Manual
102	Any component missing or improperly assembled		0.40%	3.1	Visual
103	Crimp not 360 degrees		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

16

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: Aug 16 2025 07:05:21 EDT
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Body				9206756
					NEXT HIGHER ASSEMBLY 9206755
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardness		Note 1	3.2	4.4.3.1/4.5.3
Minor					
201	Inside diameter, min.		0.65%	3.1	Gage
202	Total length		0.65%	3.1	Gage
203	Thickness, min.		0.65%	3.1	Gage
204	Diameter of hole, max.		0.65%	3.1	Gage
205	Radius missing		0.65%	3.1	Visual
206	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1. Sample in accordance with MIL-STD-105 using Table IIA, code letter "D" and AQL 1.5%.

Source: https://assist.dla.mil -- Downloaded: 2024-10-18T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206761
4.4.2.9	Disc Assembly				NEXT HIGHER ASSEMBLY 9206749
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Diameter, max.		0.65%	3.1	Gage
202	Improperly assembled		0.65%	3.1	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18 09:20:22
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Rotation Brake	1 OF 1	9206757
			NEXT HIGHER ASSEMBLY 9206755

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length, max.		0.65%	3.1	Gage
202	Thickness		0.65%	3.1	Gage
203	Width		0.65%	3.1	Gage
204	Profile of brake		0.65%	3.1	Gage
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2024-04-18T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206755
4.4.2.11	Canister Body Assembly				NEXT HIGHER ASSEMBLY 9206749
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component or operation missing or improper		0.40%	3.1	Visual
102	Spot weld missing or inadequate		Note 1	3.1	Manual 4.4.3.2/4.5.4
Minor					
201	Brake above tolerance		0.65%	3.1	Gage
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1) Sample in accordance with MIL-STD-105 using Table IIA, Code Letter "D" and AQL 1.5%.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: Sep 4 07:05:202
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9227195
4.4.2.12	Bag, Parachute				NEXT HIGHER ASSEMBLY 9206744
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Improper seams or stitching		0.65%	3.1	Visual
202	Length from bottom of bag to start of closure stitching		0.65%	3.1	Scale
203	Location of closure stitching from edge of top flap		0.65%	3.1	Scale
204	Length of overlap at open end		0.65%	3.1	Scale
205	Length of overlap at bottom (closed end)		0.65%	3.1	Scale
206	Width at development		0.65%	3.1	Scale
207	Length at development		0.65%	3.1	Scale
208	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: [illegible]
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Parachute Assembly				9206766
					NEXT HIGHER ASSEMBLY 9206746
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Circumference of reinforcing band at hem, min.		0.65%	3.1	Gage
202	Length of parachute cord from hem to shroud wire		0.65%	3.1	Gage
203	Variation in length of shroud wire		0.65%	3.1	Gage
204	Any component missing or improperly assembled		0.65%	3.1	Visual
205	Stitching improper, missing or broken		0.65%	3.1	Visual
206	Hole or tear in canopy (greater than 1/8 in dia. or length)		0.65%	3.1	Visual
207	Shroud cord not sewn min. distance onto radial tape		0.65%	3.1	Scale
208	Crimp pull test		Note 1	3.1	Tension tester
209	Overlap of tape, min.		0.65%	3.1	Gage
210	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1) Sample in accordance with MIL-STD-105 using Table IIA, Code Letter "D" and AQL 1.5%.

Source: https://assist.dla.mil -- Downloaded: Sep 6 08:05:20 2021
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206751
4.4.2.14	Support, Parachute				NEXT HIGHER ASSEMBLY 9206744
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.1	Gage
202	Thickness		0.65%	3.1	Gage
203	Profile of support (radius and arc length)		0.65%	3.1	Gage/4.5.5
204	Finish improper		0.65%	3.1	Visual/4.5.1
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces ORSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-04-18 05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9206771
4.4.2.15	Plate, Shroud				NEXT HIGHER ASSEMBLY 9206766
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.1	Gage
202	Inside diameter of center hole, min.		0.65%	3.1	Gage
203	Thickness		0.65%	3.1	Gage
204	Diameter of shroud line holes, min.		0.65%	3.1	Gage
205	True portion of shroud line holes		0.65%	3.1	Gage
206	Countersink missing		0.65%	3.1	Visual
207	Surface finish improper		0.65%	3.1	4.5.1
208	Protective finish improper		0.65%	3.1	Visual
209	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2024-10-19T06:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-14997A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9278187
4.4.2.16	Pin Groove				NEXT HIGHER ASSEMBLY 9206744
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.1	Gage
202	Total length		0.65%	3.1	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: [illegible]
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article Table, Quality Conformance Inspection Table and herein.

4.4.3.1 Hardness test of canister body. (see 3.2 and Dwg. 9206756) Samples shall be randomly selected from each eight hours of production in accordance with MIL-STD-105, using Table II A, Code Letter "D" and AQL 1.5 percent. If any of the hardness determinations taken on the sample canister bodies fail to comply with the requirements specified, the production represented by the sample shall be rejected. The test shall be performed in accordance with 4.5.3.

4.4.3.2 Test for adequate weld strength of canister body assembly (see 3.3 and Dwg. 9206755). Three (3) assemblies shall be selected from each welding machine at the beginning of each day of production and every time the electrodes or machine adjustments are changed in order to qualify the machine. Test procedures shall be as specified in 3.6 and 4.5.4. No machine shall be used for production unless all test specimens in the qualification sample comply with the applicable requirement.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.4.4.1 Automatic inspection equipment. All automatic test and inspection equipment when utilized by the contractor shall be subjected to periodic verification or calibration checks during production. The procedures shall include as a minimum: frequency, method of verification, and the method of retrieval of items produced between verification/calibration. These procedures shall be included in the operation/calibration procedures as required by 4.4.4.

4.5 Methods of inspection.

4.5.1 Surface roughness. The roughness comparison specimens prescribed in ANSI-B46.1 shall be used as a basis for surface roughness determination. Four (4) power magnification may be used in performing visual examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.5.2 Salt spray test. Inert component parts or subassemblies selected as specified in Table I shall be subjected to a 5 percent salt spray test in accordance with ASTM Method B117.

4.5.3 Hardness test of canister body (nondestructive test). A proper adapter shall be used so as to permit taking of Rockwell hardness readings on the outside surface of the canister body approximately one inch from the open end. Two hardness determinations, taken 180 degrees apart, shall be made on each sample canister body. Each determination shall consist of the average of two readings taken approximately 1/4 inch apart. Testing procedures shall be in accordance with method 243.1 of Federal Standard 151 using equipment in accordance with 4.4.4. After testing, conforming samples may be returned to production.

4.5.4 Test for adequate weld strength. Test for adequate weld strength shall be conducted as outlined in 3.3. No more than one undersize weld button is permitted on each sample tested. More than one weld button which measures less than 0.13 inches diameter shall be cause for rejection of the lot.

4.5.5 Parachute support profile of support test. Testing shall be performed on four (4) samples simultaneously. Four (4) parts shall fit into a 3.090+ .001 inside diameter ring gage. With the four parts contacting at three (3) edges, the maximum gap between the remaining edges shall not excede 0.108 inches. Failure to meet this requirement will be cause for rejection of all four (4) samples.

5. PACKAGING.

5.1 Packaging and marking requirements. Packaging and marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Intended use. The projectile loading accessories contained in this specification are intended for use with Projectile, 105MM, Illuminating: M314A3.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as requied to Commander, USACCOM (ARDEC), ATTN: AMSMC-QAR-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirement List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

6.4 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Paragraph	Data Requirement Title	Applicable DID
3.2, 3.3	Procedure Report	DI-T-5372*
4.4.4	Inspection Equipment Description Documentation	DI-R-1714

*Delete a, b, c, d of paragraph 1 block 10, DD Form 1664, and substitute contractor designated parameters and limits.

6.5 Submission of data cards. In addition to the normal distribution, one copy of all ammunition cards shall be forwarded to Commander, USAMCCOM (ARDEC), ATTN: AMSMC-QAR-Q, Picatinny Arsenal, NJ 07806-5000.

6.6 Subject term (keyword) listing.

Ammunition
Artillery
Illuminating
Military Specification
Munition
Projectile, 105MM: Illuminating, M314A3, Metal Parts Assembly

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project (1315-A979)

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-P-14997A (AR)	2. DOCUMENT DATE (YYMMDD) 19 May 1988

3. DOCUMENT TITLE
PROJECTILE, 105MM, ILLUMINATING, M314A3 LOADING ACCESSORIES FOR-

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME US Army ARDEC Standardization & Specification Office	b. TELEPHONE (Include Area Code) (1) Commercial: (201) 724-6671 (2) AUTOVON: 880-6671
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S/Bldg 6 Picatinny Arsenal, NJ 07806-500	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:20Z
Check the source to verify that this is the current version before use.