INCH-POUND
MIL-DTL-14997B (AR)
25 October 2007
SUPERSEDING
MIL-P-14997A (AR)
19 May 1998

DETAIL SPECIFICATION

Projectile, 105MM, Illuminating, M314A3 Loading Accessories

This specification is approved for use by the U.S. Army Armament Research Development and Engineering Center (ARDEC), and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers Projectile, 105MM: Illuminating, M314A3 Loading Accessories.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are needed to meet the requirements specified in section 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to assure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in section 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to the Commander, U.S. Army ARDEC, ATTN: AMSRD-AAR-QES-E, Picatinny, NJ 07806-5000 or emailed to ardec-stdzn@pica.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards and handbooks. The following specifications, standards and handbooks below form a part of this document to the extent specified herein.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-W-12332 - Welding, Resistance, Spot, Seam, And Projection, for fabricating Assemblies of Low-Carbon Steel.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1916 - DOD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch or http://assist.daps.dla.mil or from the Standardization Documents Order Desk, 700 Robbins Avenue, Bldg. 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications below form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

9206744 - Projectile, 105MM, Illuminating, M314A3, Loading Assembly
9206749 - Illuminating Canister Loading Assembly
9206750 - Canister Base Assembly

(Copies of these drawings may be requested online at Drawing-Request@pica.army.mil or from the U.S. Army ARDEC, ATTN: AMSRD-AAR-AIS-TD, Picatinny, NJ 07806-5000.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS

ASME B 46.1 - Surface Texture

(Copies of this document are available online at http://www.asme.org or from ASME Codes and Standards, 3 Park Avenue, MS/20N2, New York, NY 10016).

ASTM INTERNATIONAL

ASTM B 117 - Salt Spray (Fog) Testing
ASTM E 18 - Rockwell Hardness Test

(Copies of these documents are available online at http://www.astm.org or from ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428.)

2.4 Order of precedence. In the event of a conflict between the text or this specification and the references cited herein, the text of this specification takes precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article inspection. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Materials, parts and assemblies.

3.2.1 Gasket, baffle. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206745.

3.2.2 Nut, swivel pin. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206764.

3.2.3 Plate, swivel pin. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206777.

3.2.4 Pin, swivel. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206753.

3.2.5 Plate, base. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206754.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

3.2.6 Base. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206752.

3.2.7 Canister base assembly. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206750.

3.2.8 Body. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206756.

3.2.9 Disc assembly. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206761.

3.2.10 Rotation brake. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206757.

3.2.11 Canister body assembly. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206755.

3.2.12 Bag, parachute. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9227195.

3.2.13 Parachute assembly. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206766.

3.2.14 Support, parachute. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206751.

3.2.15 Plate, shroud. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9206771.

3.2.16 Pin groove. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 9278187.

3.2.17 Alternative, Plate, Baffle. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 13009275.

3.2.8 Alternative, fiberboard liner. The materials, components and assemblies shall be in accordance with all requirements specified on drawing 13009274.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

3.3 Hardness of canister body. The hardness of the canister body shall fall within the range specified on drawing 9206756.

3.4 Strength of weld. The weld securing the brake and body shall withstand a pull as outlined on Specification MIL-W-12332, paragraph. 7.3.3, Peel Tests.

3.5 Parachute support profile of support test. The maximum gap between edges shall not exceed 0.108 inches.

3.6 Workmanship. The requirements for workmanship are as follows:

3.6.1 Surface finish. The requirements for surface finish shall be as specified on the applicable drawing. Finish specified shall apply to the indicated surfaces regardless of contour configuration

3.6.2 Protective coating. Protective coating shall be in accordance with the applicable drawing.

3.6.3 Threads. Threads shall be full and undamaged for the entire minimum length or depth.

3.6.4. Burr and sharp edges. No part shall have a burr or sharp edge which might interfere with the assembly or function of the round or which might be injurious to personnel handling the item.

3.6.5 Foreign matter. No part or assembly shall contain dirt, grease, chips, oil, rust, corrosion or other foreign matter.

3.6.6 Painting. All paint shall be dry to the touch before packing for shipment. The paint shall be considered dry when the soft tacky condition no longer exists and the paint feels firm when touched with a finger using moderate pressure.

3.6.7 Cloth. All cloth shall be free of tears, rips and foreign matter. The stitches in the cloth shall be neat and continuous without breaks, tears or foreign matter.

3.7 Salt spray test. Inert component parts or subassemblies shall be subjected to a 5 percent salt spray test in accordance with ASTM B 117.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement / verification cross-reference matrix.

Methods of Verification N/A - Not Applicable 1 - Analysis 2 - Demonstration 3 - Examination 4 - Test							Classes of Verification A- First Article B- Acceptance		
Section 3 Requirements	Description	Verification Method					Verification Class		Section 4 Verification
		N/A	1	2	3	4	A	B	
3.1	First article inspection				X	X	X	X	4.2
3.2	Materials, parts & components	X							
3.2.1	Gasket baffle				X		X	X	4.3.2.1
3.2.2	Nut swivel pin				X	X	X	X	4.3.2.2/4.4.4
3.2.3	Plate swivel pin				X		X	X	4.3.2.3
3.2.4	Pin swivel				X		X	X	4.3.2.4
3.2.5	Plate base				X		X	X	4.3.2.5
3.2.6	Base				X		X	X	4.3.2.6
3.2.7	Canister base assembly				X	X	X	X	4.3.2.7/4.4.4
3.2.8	Body				X		X	X	4.3.2.8
3.2.9	Disc assembly				X		X	X	4.3.2.9
3.2.10	Rotation brake				X		X	X	4.3.2.10
3.2.11	Canister body assembly				X	X	X	X	4.3.2.11/4.4.4
3.2.12	Bag parachute				X		X	X	4.3.2.12
3.2.13	Parachute assembly				X		X	X	4.3.2.13
3.2.14	Support parachute				X		X	X	4.3.2.14, 4.4.5
3.2.15	Plate shroud				X	X	X	X	4.3.2.15, 4.4.4
3.2.16	Pin groove				X		X	X	4.3.2.16
3.2.17	Alt.plate baffle				X		X	X	4.3.2.17
3.2.18	Alt. fiberboard liner				X	X	X	X	4.3.2.18
3.3	Hardness of canister body				X	X	X	X	4.4.1
3.4	Strength of weld				X	X	X	X	4.4.2
3.5	Parachute support profile test				X	X	X	X	4.4.5
3.6	Workmanship				X		X	X	4.3.2.1 - 4.3.2.18
3.7	Salt spray test					X	X	X	4.4.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.1 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First article inspection. When specified, a sample shall be subjected to first article verification in accordance with Table II.

4.2.1 First article quantity. First article verification shall be performed on the quantity of items as indicated in table II.

4.2.2 First article inspections to be performed. The first article verification shall be performed in accordance with Table II.

4.2.3 First article rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Table II. First article inspection - continued

CLASSIFICATION	EXAMINATION OR TEST	Number of FAT samples	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Gasket, Baffle (Dwg. 92066745)			
	Examination for defects	5	3.2.1	4.3.2.1
	Nut, Swivel Pin (Dwg. 9206764)			
	Examination for defects	5	3.2.2	4.3.2.2
	Salt spray test	5	3.2.2	4.4.4
	Plate Swivel Pin (Dwg. 9206777)			
	Examination for defects	5	3.2.3	4.3.2.3
	Pin. Swivel (Dwg. 9206753)			
	Examination for defects	5	3.2.4	4.3.2.4
	Plate, base (Dwg. 9206754)			
	Examination for defects	5	3.2.5	4.3.2.5
	Base (Dwg. 9206752)			
	Examination for defects	5	3.2.6	4.3.2.6
	Canister Base Assembly (Dwg. 9206750)			
	Examination for defects	5	3.2.7	4.3.2.7
	Salt spray test	5	3.2.7	4.4.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Table II. First article inspection - continued

CLASSIFICATION	EXAMINATION OR TEST	Number of FAT samples	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body (Dwg. 9206756)			
	Examination for defects	5	3.2.8	4.3.2.8
	Disc Assembly (Dwg. 9206761)			
	Examination for defects	5	3.2.9	4.3.2.9
	Rotation Brake (Dwg. 9206757)			
	Examination for defects	5	3.2.10	4.3.2.10
	Canister Body Assembly (Dwg. 9206755)			
	Examination for defects	5	3.2.11	4.3.2.11
	Salt spray test	5	3.2.11	4.4.4
	Test for adequate weld strength	5	3.4	4.4.2
	Bag, Parachute (Dwg. 9227195)			
	Examination for defects	5	3.2.12	4.3.2.12
	Parachute Assembly (Dwg. 9206766)			
	Examination for defects	5	3.2.13	4.3.2.13
	Support, Parachute (Dwg. 9206751)			
	Examination for defects	5	3.2.14	4.3.2.14
	Profile of support test	5	3.2.14	4.4.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Table II. First article inspection - continued

CLASSIFICATION	EXAMINATION OR TEST	Number of FAT samples	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Plate, Shroud (Dwg. 9206771)			
	Examination for defects	5	3.2.15	4.3.2.15
	Salt spray test	5	3.2.15	4.4.4
	Pin. Groove (Dwg. 9279187)			
	Examination for defects	5	3.2.16	4.3.2.16
	Alternative, Plate Baffle (Dwg. 13009275)			
	Examination for defects	10	3.2.17	4.3.2.17
	Alternative Fiberboard Liner (Dwg. 13009274)			
	Examination for defects	10	3.2.18	4.3.2.18

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection.

4.3.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-STD-1916 paragraph 4.2, Acceptance by Tables.

4.3.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for critical, major and minor characteristics are defined in MIL-STD-1916. Unless otherwise specified, inspection level IV shall be used for all characteristics defined as majors and inspection level II for all minor characteristics. Critical characteristics shall be addresses in accordance with MIL-STD-1916.

b. Automatic gaging. Facilities equipped with furnished automatic gaging capable of performing 100 percent inspection of any characteristic shall utilize capability in accordance with contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.1	TITLE Gasket, Baffle		SHEET 1 OF 1	DRAWING NUMBER 9206745
				NEXT HIGHER ASSEMBLY 9206744
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major	None defined			
Minor				
201	Presence of three (3) slots	Level II	3.2.1	Visual
202	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.2	TITLE Nut, Swivel Pin		SHEET 1 OF 1	DRAWING NUMBER 9206764
				NEXT HIGHER ASSEMBLY 9206746
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Pitch diameter of thread	Level IV	3.2.2	AIE
102	Minor diameter of thread	Level IV	3.2.2	AIE
103	Salt spray test	4.4.4	3.7	4.4.4
Minor				
201	Distance across flats, max	Level II	3.2.2	AIE
202	Thickness	Level II	3.2.2	AIE
203	Surface finish improper	Level II	3.2.2/3.6.1	Visual/4.4.3
204	Protective finish inadequate	Level II	3.2.2/3.6.2	Visual
205	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.3	TITLE Plate, Swivel Pin		SHEET 1 OF 1	DRAWING NUMBER 9206777
				NEXT HIGHER ASSEMBLY 9206746
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major	None defined			
Minor				
201	Inside diameter, min	Level II	3.2.3	AIE
202	Thickness, min	Level II	3.2.3	AIE
203	Protective finish inadequate	Level II	3.2.3	Visual
204	Surface finish improper	Level II	3.2.3/3.6.1	Visual/4.4.3
205	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.4	TITLE Pin, Swivel	SHEET 1 OF 1	DRAWING NUMBER 9206753
			NEXT HIGHER ASSEMBLY 9206750

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Pitch diameter of thread	Level IV	3.2.4	AIE
102	Major diameter of thread	Level IV	3.2.4	AIE
Minor				
201	Large diameter	Level II	3.2.4	AIE
202	Diameter if ball (fwd and aft)	Level II	3.2.4	AIE
203	Total length	Level II	3.2.4	AIE
204	Distance from base to aft shoulder	Level II	3.2.4	AIE
205	Distance from base to ball race shoulder	Level II	3.2.4	AIE
206	Thickness of ball race flange	Level II	3.2.4	AIE
207	Full thread length, min	Level II	3.2.4	AIE
208	Surface finish improper	Level II	3.2.4/3.6.1	Visual/4.4.3
209	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.5	TITLE Plate, base	SHEET 1 OF 1	DRAWING NUMBER 9206754
			NEXT HIGHER ASSEMBLY 9206750

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outside diameter	Level II	3.2.5	AIE
202	Thickness	Level II	3.2.5	AIE
203	Surface finish improper	Level II	3.2.5/3.6.1	Visual/4.4.3
204	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.6	TITLE Base	SHEET 1 OF 1	DRAWING NUMBER 9206752
			NEXT HIGHER ASSEMBLY 9206750

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outside diameter of flange	Level II	3.2.6	AIE
202	Outside diameter of base plate cavity	Level II	3.2.6	AIE
203	Inside diameter of base plate cavity	Level II	3.2.6	AIE
204	Inside diameter of bearing bore	Level II	3.2.6	AIE
205	Outside diameter of bearing bore boss	Level II	3.2.6	AIE
206	Diameter of hole	Level II	3.2.6	AIE
207	Total length	Level II	3.2.6	AIE
208	Distance from face to flange	Level II	3.2.6	AIE
209	Thickness of flange	Level Ii	3.2.6	AIE
210	Depth of base plate cavity	Level II	3.2.6	AIE
211	Depth of bearing bore	Level II	3.2.6	AIE
212	Radius missing	Level II	3.2.6	AIE
213	Surface finish improper	Level II	3.2.6/3.6.1	Visual/4.4.3
214	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.7	TITLE Canister Base Assembly	SHEET 1 OF 1	DRAWING NUMBER 9206750 NEXT HIGHER ASSEMBLY 9206749

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Swivel does not rotate freely	Level IV	3.2.7	Manual
102	Any component missing or improperly assembled	Level IV	3.2.7	Visual
103	Crimp not 360 degrees	Level IV	3.2.7	Visual
104	Salt spray test	4.4.4	3.7	4.4.4
Minor				
201	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.8	TITLE Body	SHEET 1 OF 1	DRAWING NUMBER 9206756 / NEXT HIGHER ASSEMBLY 9206755	
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Hardness	4.4.1	3.2.8	4.4.1
Minor				
201	Inside diameter, min	Level II	3.2.8	AIE
202	Total length	Level II	3.2.8	AIE
203	Thickness, min	Level II	3.2.8	AIE
204	Diameter of hole, max.	Level II	3.2.8	AIE
205	Radius missing	Level II	3.2.8	Visual
206	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.9	TITLE Disc Assembly		SHEET 1 OF 1	DRAWING NUMBER 9206761 NEXT HIGHER ASSEMBLY 9206749
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major	None defined			
Minor				
201	Diameter, max.	Level II	3.2.9	AIE
202	Improperly assembled	Level II	3.2.9	Visual
203	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.10	TITLE Rotation Brake	SHEET 1 OF 1	DRAWING NUMBER 92067457
			NEXT HIGHER ASSEMBLY 9206755

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Total length	Level II	3.2.10	AIE
202	Thickness	Level II	3.2.10	AIE
203	Width	Level II	3.2.10	AIE
204	Profile of brake	Level II	3.2.10	AIE
205	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.11	TITLE Canister Body Assembly	SHEET 1 OF 1	DRAWING NUMBER 9206755 NEXT HIGHER ASSEMBLY 9206749

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Any component or operation missing or improper	Level IV	3.2.11	Visual/manual
102	Test for adequate weld strength	4.4.2	3.4	4.4.2
103	Salt spray test	4.4.4	3.7	4.4.4
Minor				
201	Brake above tolerance	Level II	3.2.11	AIE
202	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.12	TITLE Bag, Parachute		SHEET 1 OF 1	DRAWING NUMBER 9227195
				NEXT HIGHER ASSEMBLY 9206744
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major	None defined			
Minor				
201	Improper seams or stitching	Level II	3.2.12	Visual
202	Length from bottom of bag to start of closure stitching	Level II	3.2.12	AIE/Scale
203	Location of closure stitching from edge of top flap	Level II	3.2.12	AIE/Scale
204	Length of overlap at open end	Level II	3.2.12	AIE/Scale
205	Length of overlap at bottom (closed end)	Level II	3.2.12	AIE/Scale
206	Width at development	Level II	3.2.12	AIE/Scale
207	Length at development	Level II	3.2.12	AIE/Scale
208	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.13	TITLE Parachute Assembly	SHEET 1 OF 1	DRAWING NUMBER 9206766
			NEXT HIGHER ASSEMBLY 9206746

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Circumference of reinforcing band at hem, min	Level II	3.2.13	AIE
202	Length of parachute cord from hem to shroud wire	Level II	3.2.13	AIE
203	Variation in length of shroud wire	Level II	3.2.13	AIE
204	Any component missing or improperly assembled	Level II	3.2.13	Visual
205	Stitching improper, missing or broken	Level II	3.2.13	Visual
206	Hole or tear in canopy (greater than 1/8 in dia. Or length)	Level II	3.2.13	Visual
207	Shroud not sewn min, distance onto radial tape	Level II	3.2.13	Scale
208	Crimp pull test	Level II	3.2.13	Tension Tester
209	Overlap of tape, min	Level II	3.2.13	AIE
210	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.14	TITLE Support, Parachute		SHEET 1 OF 1	DRAWING NUMBER 9206751
				NEXT HIGHER ASSEMBLY 9206744
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major	None defined			
Minor				
201	Total length	Level II	3.2.14	AIE
202	Thickness	Level II	3.2.14	AIE
203	Profile of support test (radius and arc length)	4.4.5/3.5	3.2.14	AIE/4.4.5
204	Finish improper	Level II	3.2.14/3.6.1	Visual/4.4.3
205	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.15	TITLE Plate, shroud	SHEET 1 OF 1	DRAWING NUMBER 9206771
			NEXT HIGHER ASSEMBLY 9206766

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Salt spray test	4.4.4	3.7	4.4.4
Minor				
201	Outside diameter	Level II	3.2.15	AIE
202	Inside diameter if center hole, min	Level II	3.2.15	AIE
203	Thickness	Level II	3.2.15	AIE
204	Diameter of shroud line holes, min	Level II	3.2.15	AIE
205	True portion of shroud line holes	Level II	3.2.15	AIE
206	Countersink missing	Level II	3.2.15	Visual
207	Surface finish improper	Level II	3.2.15/3.6.1	Visual/4.4.3
208	Protective finish improper	Level II	3.2.15/3.6.2	Visual
208	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.16	TITLE Pin, Groove	SHEET 1 OF 1	DRAWING NUMBER 9278187
			NEXT HIGHER ASSEMBLY 9206744

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outside diameter	Level II	3.2.16	AIE
202	Total length	Level II	3.2.16	AIE
203	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.17	TITLE Alternative, Plate Baffle		SHEET 1 OF 1	DRAWING NUMBER 13009275
				NEXT HIGHER ASSEMBLY 9206744
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Diameter, max	Level IV	3.2.17	AIE
102	Holes number	Level IV	3.2.17	Visual
103	Holes size	Level IV	3.2.17	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.18	TITLE Alternative, Fiberboard Liner		SHEET 1 OF 1	DRAWING NUMBER 13009274
				NEXT HIGHER ASSEMBLY 13009272
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Outside diameter	Level IV	3.2.18	AIE
102	Overall length	Level IV	3.2.18	AIE
103	Thickness	Level IV	3.2.18	AIE
104	Moisture content	Level IV	3.2.18	AIE/Test
Minor				
201	Evidence of poor workmanship	Level II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

4.4 Methods of inspection.

4.4.1 Hardness test of canister body (nondestructive test). A proper adapter shall be used so as to permit taking of Rockwell hardness readings on the outside surface of the canister body approximately one inch from the open end. Two hardness determinations, taken 180 degrees apart, shall be made on each sample canister body. Each determination shall consist of the average of two readings taken approximately 1/4 inch apart. Testing procedures shall be in accordance with ASTM E 18. Eight samples shall be randomly selected from each eight hours of production. If any of the hardness determinations taken on the sample canister bodies fail to comply with the requirements specified on the drawing and herein, the production represented by the sample shall be rejected.

4.4.2 Test for adequate weld strength. Test for adequate weld strength shall be conducted as outlined in 3.4. No more than one undersize weld button is permitted on each sample tested. More than one weld button which measures less than 0.13 inches diameter shall be cause for rejection of the lot. Three (3) assemblies shall be selected from each welding machine at the beginning of each day of production and every time the electrodes or machine adjustments are changed in order to qualify the machine. No machine shall be used for production unless all test specimens in the qualification sample comply with the requirement specified in 3.4.

4.4.3 Surface roughness. The roughness comparison specimens prescribed in ASME B 46.1 shall be used as a basis for surface roughness determination. Four (4) power magnifications may be used in performing visual examination.

4.4.4 Salt spray test. Inert component parts or subassemblies selected for this test shall be subjected to a 5 percent salt spray test for 96 hours in accordance with ASTM B 117. After exposure, samples shall be examined for the effects of corrosion. Any evidence of corrosion on the test samples shall be a cause for rejection of the production represented by the sample. Two (2) samples shall be taken each week, one during the first 30 minutes of production and a second at any other time.

4.4.5 Parachute support profile of support test. Testing shall be performed on four (4) samples simultaneously. Four (4) parts shall fit into a 3.090 +.001 inside diameter ring gage. With the four parts contacting at three (3) edges, the maximum gap between the remaining edges shall not exceed 0.108 inches. Failure to meet this requirement will be cause for rejection of all four (4) samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department of Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The projectile loading accessories contained in this specification are intended for use with Projectile, 105MM, Illuminating, M314A3.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Requirements for submission of First Article sample (see 4.4).
c. Requirements for submittal of Acceptance Inspection Equipment (see 6.3).
d. Requirements for ammunition lot numbering.

6.3 Submission of contractor acceptance inspection equipment (AIE) designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: AMSRD-AAR-QEM-A, Picatinny, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Submission of ammunition data cards. In addition to the normal distribution of records for items procured by the Department of the Army, ammunition data cards should be forwarded to Commanding Officer, U.S Army ARDEC, ATTN: AMSRD-AAR-AEM-C and AMSRD-AAR-QEM-A, Picatinny Arsenal, NJ 07806-5000.

6.5 Automatic inspection equipment. All automatic test and inspection equipment when utilized by the contractor should be subjected to periodic verification or calibration checks during production. The procedures should include as a minimum: frequency, method of verification, and the method

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.

of retrieval of items produced between verification/calibration.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.6 Subject term (keyword) listing.

Ammunition
Artillery
Military Specification
Munition

Custodian:	Preparing Activity:
Army- AR	Army-AR
	Project (1315-2008-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:20Z
Check the source to verify that this is the current version before use.