[INCH–POUND]
A–A–59950/1
1 JULY 2014


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 7 PIECE, FOR COLD PLATE APPLICATIONS, .225 X .225 INCH (5.72 x 5.72 mm) BODY SIZE, SCREW ACTUATED SHAFT

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring shaft mounted 7 wedge card holders described herein shall consist of this document and the latest issue in effect of A–A–59950.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes herein).



Example: AA59950/01CB48R is the PIN for a black anodized, 4.8 inch (122 mm) long card holder. The card holder uses two counterbore and countersink holes for rivet mounting.

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card assembly it is attached to firmly in its installed position and prevent loosening or movement as a result of shock and vibration. The card holder shall also provide a thermal transfer path from the circuit card assembly to the cold plate or heat sink surfaces.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and meet the general requirements specified in CID A–A–59950.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A–A–59950.

Actuating screw hex drive socket. The across flats dimension for hex drive socket shall be .098 inch (2.38 mm) for mounting options "R" and "S" and .098 inch (2.5 mm) for mounting option "M".

Cold plate slot width. The recommended cold plate slot width to accommodate the circuit card assembly with attached card holder is .250 inch (6.35 mm) plus the thickness of the printed board of the circuit card assembly (see A–A–59950).


Installation torque. The recommended nominal installation torque is as follows: 6 inch-pounds (0.68 N-m) for assemblies of configuration "C" and "E" and 7 to 8 inch-pounds (0.79 to 0.90 N-m) for assemblies of configurations "L" and "D".

Configuration. The configuration of card holders shall be as specified in table I. The details of a particular configuration consist of those on figure 1 and may include those on figures 2 or 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

TABLE I. Configuration.

Configuration	Applicable figures	Hardware options
C	1	No added hardware
L	1, and 2	Screw self-locking element
E	1, and 3	Additional mounting hole
D	1, 2, and 3	Screw self-locking element and additional mounting hole



Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.20	5.1	.225	5.72	.230	5.84	.290	7.37	.68	17.3

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Unless otherwise specified, tolerances are ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. Tolerance for the mounting hole spacing is ±.005 inch (0.13 mm).
4. The across flats dimension for actuating screw hex drive socket shall be .094 inch (2.38 mm) or .098 inch (2.5 mm) for the corresponding mounting option (see hex drive socket details).

FIGURE 1. Relaxed and expanded dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

Finish. The wedge body finish designator shall be as specified in A–A–59950. The finishes available for this CID specification sheet are as follows: "B" (black anodize), "C" (gold chemical film), "E" (electroless nickel), "H" (hard black anodize), or "R" (clear chemical film).

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A–A–59950. The lengths available for this CID specification sheet are listed in table II. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE II. Additional assembly dimensions (see figure 1). 1/

PIN length designator	Dimension "LENGTH" ±.02 (0.5 mm)	Dimension "M" ±.005 (0.13 mm)	Dimension "M/2" ±.005 (0.13 mm)
48	4.8 (122 mm)	2.900 (73.66 mm)	1.450 (36.83 mm)
53	5.3 (135 mm)	3.400 (86.36 mm)	1.700 (43.18 mm)
58	5.8 (147 mm)	3.900 (99.06 mm)	1.950 (49.53 mm)
63	6.3 (160 mm)	4.400 (111.76 mm)	2.200 (55.88 mm)
68	6.8 (173 mm)	4.900 (124.46 mm)	2.450 (62.23 mm)
73	7.3 (185 mm)	5.400 (137.16 mm)	2.700 (68.58 mm)
78	7.8 (198 mm)	5.900 (149.86 mm)	2.950 (74.93 mm)

1/ Dimensions are in inches. Millimeters, in parenthesis, are given for general information only.

Mounting. The mounting designators shall be as specified in A–A–59950. The mounting options available for this CID specification sheet are as follows: "R" (rivet mount holes with counterbore and countersink), "S" (tapped 2–56 threads), or "M" (tapped metric M2.5 X 0.45 tolerance class 6H threads). See figure 1 and table I for mounting hole spacing requirements.

Rivet mount holes. The holes used for rivet mounting shall be .068 to .073 inch (1.68 to 1.85 mm) diameter through holes, countersunk 100 degrees by .060 inch (1.52 mm) deep.

Rivets. This card holder uses rivet style A as specified in A–A–59950 when rivet mounting is used.

Configuration hardware options. Card holders can have the following hardware options: no added hardware, screw self-locking element, an additional mounting hole, or a combination of both screw self-locking element and third mounting. See table I for the correct PIN configuration identifier. Card holders requiring no added hardware options shall include configuration identifier "C" in the PIN (see classification and notes section herein).

Screw self-locking element (see figure 2). The use of a screw self-locking element on the screw will provide a prevailing-torque for increased resistance to loosening of the card holder assembly from shock and vibration. The screw self-locking element shall be as specified in A–A–59950. Card holders requiring a screw self-locking element shall include configuration identifier "L" in the PIN (see table I, classification and notes section herein).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.




FIGURE 2. Screw self-locking element details.

Additional mounting holes (see figure 3). Card holders requiring an additional mounting hole shall include configuration identifier "E" in the PIN (see table I).




FIGURE 3. Additional mounting hole details.

Screw self-locking element and additional mounting hole. Card holders requiring a screw self-locking element and additional mounting hole options shall include configuration identifier "D" in the PIN (see table I, classification and notes section herein).

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents.

Commercial Item Description

A–A–59950 – Holder, Electrical Card, Wedge Retainers, 7 Piece, For Cold Plate Applications, General Requirements For.

(Copies of these documents are available online at http://quicksearch.dla.mil.)

Ordering data. Ordering data shall be as specified in A–A–59950.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
3E7U8	Wakefield Solutions 200 Towerview Court Cary, NC 27513	Telephone: (919) 469–2004 Facsimile: (919) 469–2827 E-mail: wedgelocks@wakefield.com URL: www.wakefield-vette.com

Part number supersession data. These CID specification sheet PINs supersede the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "48". See table IV for CID PIN construction using other available lengths for this CID specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE III. Commercial part number supersession data.

PIN designator AA59950/01	Vendor similar designator or type part number 1/ 2/		
	CAGE 3E7U8	CAGE	CAGE
CB48M	422C7–480MMB		
CB48R	422C7–480RSB		
CB48S	422C7–480SSB		
LB48M	422C7–480MMB–P		
LB48R	422C7–480RSB–P		
LB48S	422C7–480SSB–P		
EB48M	422C7–480MMB–C		
EB48R	422C7–480RSB–C		
EB48S	422C7–480SSB–C		
DB48M	422C7–480MMB–CP		
DB48R	422C7–480RSB–CP		
DB48S	422C7–480SSB–CP		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data – Continued.

PIN designator AA59950/01	Vendor similar designator or type part number 1/ 2/		
	CAGE 3E7U8	CAGE	CAGE
CC48M	422C7–480MMG		
CC48R	422C7–480RSG		
CC48S	422C7–480SSG		
LC48M	422C7–480MMG–P		
LC48R	422C7–480RSG–P		
LC48S	422C7–480SSG–P		
EC48M	422C7–480MMG–C		
EC48R	422C7–480RSG–C		
EC48S	422C7–480SSG–C		
DC48M	422C7–480MMG–CP		
DC48R	422C7–480RSG–CP		
DC48S	422C7–480SSG–CP		
CE48M	422C7–480MME		
CE48R	422C7–480RSE		
CE48S	422C7–480SSE		
LE48M	422C7–480MME–P		
LE48R	422C7–480RSE–P		
LE48S	422C7–480SSE–P		
EE48M	422C7–480MME–C		
EE48R	422C7–480RSE–C		
EE48S	422C7–480SSE–C		
DE48M	422C7–480MME–CP		
DE48R	422C7–480RSE–CP		
DE48S	422C7–480SSE–CP		
CH48M	422C7–480MMH		
CH48R	422C7–480RSH		
CH48S	422C7–480SSH		
LH48M	422C7–480MMH–P		
LH48R	422C7–480RSH–P		
LH48S	422C7–480SSH–P		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data – Continued.

PIN designator AA59950/01	Vendor similar designator or type part number 1/ 2/		
	CAGE 3E7U8	CAGE	CAGE
EH48M	422C7–480MMH–C		
EH48R	422C7–480RSH–C		
EH48S	422C7–480SSH–C		
DH48M	422C7–480MMH–CP		
DH48R	422C7–480RSH–CP		
DH48S	422C7–480SSH–CP		
CR48M	422C7–480MMT		
CR48R	422C7–480RST		
CR48S	422C7–480SST		
LR48M	422C7–480MMT–P		
LR48R	422C7–480RST–P		
LR48S	422C7–480SST–P		
ER48M	422C7–480MMT–C		
ER48R	422C7–480RST–C		
ER48S	422C7–480SST–C		
DR48M	422C7–480MMT–CP		
DR48R	422C7–480RST–CP		
DR48S	422C7–480SST–CP		

1/ The CID PINs listed are only for length designator "48".
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59950.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

TABLE IV. Example of PIN with available length designators.

PIN designator AA59950/01	Vendor similar designator or type part number 1/ 2/		
	CAGE 3E7U8	CAGE	CAGE
CB48R	422C7–480RSB		
CB53R	422C7–530RSB		
CB58R	422C7–580RSB		
CB63R	422C7–630RSB		
CB68R	422C7–680RSB		
CB73R	422C7–730RSB		
CB78R	422C7–780RSB		

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59950.

2/ Other lengths are available on request.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Review activity:
Air Force – 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FAS

Preparing activity:
DLA – CC

Project 5998–2014–001

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.