A-A-142A
April 30, 1986
SUPERSEDING
A-A-142
September 26, 1979

COMMERCIAL ITEM DESCRIPTION

CORRECTABLE TYPEWRITER RIBBONS (HIGH YIELD)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers high yield correctable typewriter ribbons for general typing application.

Salient characteristics:

Ribbons shall consist of a continuous length of plastic film coated on one side with black imaging material with an uncoated orange film strip attached to the leading end.

The ribbons shall be firmly wound in cartridges or on spools or cores designed for operation with the machines specified (see note).

Composition and application of the imaging material shall be such that it does not offset from one layer to the next and does not flake from the film.

The ribbon shall not tear nor be cut through during the typing and take-up operation and take-up smoothly, evenly and completely.

The ribbon shall produce black impressions which are of uniform density, clean, legible and sharp, without smears and smudges and which are completely removable from the paper surface by a compatible lift-off tape or tab.

Workmanship. The plastic file shall be free from holes, tears, or blisters; the imaging material smoothly and evenly applied and of a uniform thickness; and the ribbons free of defects such as pinholes, foreign matter, streaks, or other imperfections which could adversely affect performance and serviceability. In addition, ribbons shall be free from ragged or nicked edges, and the cartridges free of any defects which may affect serviceability.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

Performance test. Select one sample ribbon and place in the machine in the normal manner until the ribbon has run its full course and is wound from one side to the other. If the machine is designed for ribbon reverse, the "full course" shall include reversal and continuous operation for at least one quarter of the return length of the ribbon. During the course of the test operation, the ribbon shall be observed to ensure that it is not binding or twisting so as to interfere with proper printing. Upon completion of the test, the printed matter (the product of the ribbon printing test), shall be examined to ensure that quality of print is uniformly dark and with no blank spots, light spots, or discontinuities. Failure to comply with any of these requirements shall be cause for rejection.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified, in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Sampling. Sampling for inspection and tests shall be performed in accordance with MIL-STD-105, except where otherwise indicated. For purposes of sampling, a lot shall consist of all ribbons of the same description manufactured under the same conditions at essentially the same time.

Sampling of end item for visual examination. A random sample shall be taken from each lot in accordance with Inspection Level S-3. The AQL shall not exceed 2.5 percent defective. The sample shall be one ribbon.

Sampling of end items for tests. A random sample shall be taken from each lot in accordance with Inspection Level S-1. The AQL shall not exceed 2.5 percent defective.

Examination of end item for visual defects. Sample shall be examined for defects listed below. Any ribbon containing one or more defects shall be rejected. The Government reserves the right to classify as a defect any not listed.

Examine	Defects
Cartridge and ribbon	Not compatible with machine specified.
Width	Not as specified.
Length	Not as specified.
Leader signal	Missing
Workmanship	See Workmanship paragraph.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the current version before use.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is too acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note. Purchaser shall specify the ribbon dimensions and the machine on which the ribbons are intended to be used.

When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

MILITARY INTERESTS:

NONE

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.