[METRIC]
A-A-1457A
April 24, 1992
SUPERSEDING
A-A-1457
April 28, 1980

COMMERCIAL ITEM DESCRIPTION

TIMER, INTERVAL, MECHANICAL
(120 Minute maximum interval)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GG-T-416.

Salient characteristics.

General. The timer shall have all of the following components: case, base, dial (face), regulator, bell alarm, suspension device, clock mechanism, starting device, crystal (face cover) and hands.

Materials. The materials used shall be of sufficient strength and durability to ensure that the timers are securely and sturdily constructed and will remain usable over the normal life of the timer. Any metals used shall be corrosion resistant or treated to resist corrosion of any type, consistent with their normal functioning. The crystal material shall be clear, nonyellowing, nonbreakable and not easily scratched.

Dimensions. The overall dimensions shall not exceed 18 centimeters in height, 15.25 centimeters in width and 13 centimeters in depth.

Mounting. The base shall be stable with no rocking or wobbling when placed on a flat level surface. The base shall have at least two mounting holes.

Marking. The timer shall have two scales: The outer scale shall be marked for every 15 seconds and numbered for every minute. The inner scale shall be marked and numbered for every ten minute interval.

Timers shall have nonluminous markings and hands that shall be readable from a distance of 92 centimeters in normal office light.

Hands. There shall be two hands, one the approximate length for each scale. They shall be easily set for any desired interval to a maximum of at least 119 minutes, and shall indicate the time remaining in an interval.

Starting device. The starting device shall be conveniently located on the outside of the timer case. It shall activate the timer when placed in the "start" position and automatically return to its original position by the end of an interval.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:14Z
Check the source to verify that this is the current version before use.

Workmanship. The timers shall be free from any defects which may impair their appearance, durability or serviceability.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection and tests. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Sampling. Sampling for visual inspection and testing shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified, Inspection Level II with AQL 2.5 percent defective for visual inspection and level S-2, AQL 1.5 percent defective for testing shall apply.

Inspection. Samples selected in accordance with the requirements herein shall be visually inspected to verify conformance to dimensional and workmanship requirements of the CID. Any departure from specified requirements may be grounds for rejection.

Testing.

Alarm. The alarm shall sound only at the end of the desired interval and shall be audible from a distance of 7.5 meters.

Clock mechanism. The clock mechanism shall be spring driven and capable of running 8 hours without rewinding. It shall be accurate to ± 3 seconds per minute and shall have a regulator capable of adjusting to, and maintaining an accuracy of 120 seconds per hour.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations (FAR), the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistant with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing,labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Copies of MIL-STD-105 can be obtained from the Standardization Document Order Desk, 700 Robbins Ave., Bldg 4D, Philadelphia, PA 19111-5094.

NOTE. Purchaser shall specify NSN 6645-00-732-7789.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:14Z
Check the source to verify that this is the current version before use.