A-A-205A
November 6, 1986
SUPERSEDING
A-A-205
JANUARY 24, 1980

COMMERCIAL ITEM DESCRIPTION

DUPLICATING FLUID, DIRECT PROCESS (SPIRIT TYPE)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification O-D-285.

This commercial item description covers fluid for use in direct-process (spirit type) duplicating machines.

Salient characteristics.

The duplicating fluid shall be furnished in two types in the formulation table in the proportions shown.

Type I - Denatured alcohol and ether.
Type II - Denatured alcohol, methyl or isopropyl alcohol, and ether.

The denatured alcohol content shall conform to Formula 3-A or 3-C of the Internal Revenue Service formulas for Denatured Alcohol and Rum (see Note 1).

Formulation, (per 100 gallons)

Ingredients	Type I	Type II
	Gallons	Gallons
Denatured alcohol, 190 proof (see Note 1)----	95	35 to 55
Methyl or isopropyl alcohol----------	(See Note 1)	40 to 60
Propylene glygol-monomethyl ether	5 (max.)	(5 max.)

Note 1. Specially denatured alcohol formula 3-A: Five gallons of commercially pure methyl alcohol is added to every 100 gallons of ethyl alcohol. Specially denatured alcohol Formula 3-C: Five gallons of commercially pure isopropyl alcohol is added to every 100 gallons of ethyl alcohol.
Note 2. The volumes shown above shall be based on the U. S. gallon at 15.5 degrees C. (60 degrees F.).

The duplicating fluid shall be free from suspended material and sediment. The pH value shall be not less than 5.5 nor more than 8.0 at 25 degrees C. when tested with an electric pH meter having a glass electrode, the sample being diluted with an equal volume of freshly boiled and cooled distilled water. The duplicating fluid shall not have nor give off an objectionable odor or leave a residual odor in the copy paper.
The flash point shall be not less than 50 degrees F. (tag open or closed cup) when tested in accordance with ASTM D 1310.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

The issue of the ASTM test method in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Performance requirement. The duplicating fluid, when used in the duplicating machine with copy paper conforming to UU-P-00232E and a prepared master set conforming to A-A-1501, shall be capable of producing the number of copies specified in A-A-1501. The copies shall be legible with sharply defined characters of good intensity and without spotty appearance.

Workmanship. The duplicating fluid shall be furnished free from evidence of dirt and any other foreign matter which might impair their usefulness.

Examination of the end item for defects in workmanship. The sample unit for this examination shall be one filled container. The inspection level shall be S-1 with an acceptable quality level (AQL) of 2.5 expressed in terms of percent defective in accordance with MIL-STD-105.

Inspection for test requirements. A two gallon sample shall be taken from each lot. The sample shall be a composite taken from not less than five containers. The sample shall be analyzed for conformance to the formulation requirements, and tested for pH, flash point, and performance (Type II only). Any failure to meet the requirements stated herein shall result in rejection of the lot.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order. (The duplicating fluid shall be furnished in 1-gallon rectangular metal cans with nondrip pour spouts or in 1-gallon plastic containers. The containers shall conform to the applicable DOT regulations.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

Precautionary marking. Each container shall be prominently and permanently marked with the applicable Department of Transportaion (DOT) Regulations as show below:

CAUTION: FLAMMABLE MIXTURE
DO NOT USE NEAR FIRE OR FLAME

FOR FORMULA 3-A:
POISON - DO NOT USE INTERNALLY (SKULL AND CROSSBONES SYMBOL)

FOR FORMULA 3C:
A PERSON BECOME VIOLENTLY ILL
IF INGESTED

USE ONLY IN WELL-VENTILATED WORK AREA
(TO AVOID TOXIC AND CUMULATIVE EFFECTS)

CAUTION, AVOID INHALATION OF FUMES

ANTIDOTE: Induce vomiting immediately or use a stomach pump, followed by repeated doses of bicarbonate of soda (2 full teaspoons in a glass of water or white of an egg).

Notes.

Purchaser should specify type and formula.

WHEN THIS COMMERCIAL ITEM DESCRIPTION IS USED FOR PROCUREMENT, THE COMMERCIAL ITEM CERTIFICATION CLAUSE MUST APPEAR IN THE SOLICITATION.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MILITARY INTERESTS:

NONE: DoD has determined that no military activity has an official interest in this commercial item description.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.