A-A-2279
November 7, 1984

COMMERCIAL ITEM DESCRIPTION

NOZZLE, FIRE HOSE, WATER (FIXED GALLONAGE)

The General Services Administration has authorized the use of this commercial item description.

This description covers a fog and straight stream nozzle with a single, fixed constant-gallonage setting but with the capability of field conversion to a minimum of one other flow rate and shall be furnished in the following types, classes, and styles.

Type I - Brass, chrome plated
Type II - Aluminum, hard coated

Class A - Nozzles

Style	Size (inches)	Threads (inches)	Flow (GPM) (as shipped)	Flow (GPM) (Convertible to)	Description
1*	1	1	23	12;30	Pistol Grip
2	1	1	60	-	Pistol Grip
3	1-1/2	1-1/2	95	60;125	Pistol Grip
4	1-1/2	1-1/2	95	60;125	Leader Line
5*	2-1/2	2-1/2	250	150;170;200	Direct Connect
6*	2-1/2	2-1/2	250	150;170;200	With Playpipe

Class B - Breakapart Nozzles

Style	Size (inches)	Threads (inches)	Flow (GPM) (as shipped)	Flow (GPM) (Convertible to)	Description
1	1-1/2	1-1/2x1-1/2	95	60;125	Leader Line
2*	2-1/2	2-1/2x1-1/2	250	150;170;200	Direct Connection
3*	2-1/2	1-1/2x1-1/2	250	150;170;200	For Playpipe
4*	2-1/2	2-1/2x1-1/2	250	150;170;200	With Playpipe

Class C - Breakapart Tips

Style	Size (inches)	Threads (inches)	Flow (GPM) (as shipped)	Flow (GPM) (Convertible to)	Description
1	1-1/2	1-1/2x1-1/2	95	60;125	Leader Line
2*	2-1/2	2-1/2x1-1/2	250	150;170;200	For Playpipe

* Shall be capable of converting to a minimum of one of the flow rates listed under "(Convertible to)".

Salient characteristics.

Shall be capable of being flushed without shutting down.
Shall be approved for use with non-protein/synthetic and aqueous film-forming foam (AFFF).
Shall deliver same gallonage for straight stream, narrow or wide fog.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Both nozzles and breakapart nozzles shall be provided with ball-type shut-offs. All Class A nozzles, except Styles 1 and 2, shall be provided with rocker lugs and a free swiveling base, unless otherwise specified. For Styles 1 and 2 the base rocker lugs are optional with the manufacturer.
All Class B and C nozzles shall have rocker lugs. Rigid or swivel base shall be the manufacturer's option.
All thread to be of the NH series unless otherwise specified.
Nozzles shall be designed and rated for an inlet pressure of 100 psi.

Workmanship. Nozzles shall be free of defects which may affect the durability, appearance, or serviceability.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note. When this commercial item description is used for procurement the commercial item certification clause must appear in the solicitation.

Purchaser shall specify type, class, and style of nozzle desired.

MILITARY INTERESTS:

Review Activity

Army - ME

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.