A-A-2280
November 7, 1984

COMMERCIAL ITEM DESCRIPTION

NOZZLE, FIRE HOSE, WATER (SELF-ADJUSTING)

The General Services Administration has authorized the use of this commercial item description.

This description covers a fog nozzle with an automatic mechanism that reacts to the volume of water supplied, selects the proper orifice, and adjusts to fluctuating flow. Nozzles shall be furnished in the following classes and styles, as specified.

Class A - Nozzles

Style	Size (inches)	Thread Size (inches)	Flow Range (GPM) Min	Flow Range (GPM) Max	Description
1	1	1	10	40	Booster Line
2	1	1	10	40	Pistol Grip
3	1-1/2	1-1/2	60	125	Leader Line
4	1-1/2	1-1/2	60	125	Pistol Grip
5	2-1/2	1-1/2	60	400	For Playpipe
6	2-1/2	2-1/2	60	400	Direct Connect
7	2-1/2	1-1/2	60	400	With Playpipe

Class B - Breakapart Nozzles

Style	Size (inches)	Thread Size (inches) Base	Thread Size (inches) Tip	Flow Range (GPM) Min	Flow Range (GPM) Max	Description
1	1-1/2	1-1/2		60	125	Leader Line
2	2-1/2	1-1/2	1-1/2	60	400	For Playpipe
3	2-1/2	2-1/2	1-1/2	60	400	Direct Connect
4	2-1/2	2-1/2	1-1/2	60	400	With Playpipe

Class C - Breakapart Tips

Style	Size (inches)	Thread Size (inches)	Flow Range (GPM) Min	Flow Range (GPM) Max	Description
1	1-1/2	1-1/2	60	125	Leader Line
2	2-1/2	1-1/2	60	400	For Playpipe

Salient characteristics.

Shall be made of aluminum, hard coat finish.
Shall be able to change flow without shutting down.
Shall be approved for use with non-protein/synthetic and aqueous film-forming foam (AFFF).
Playpipe handles shall swivel.
Both nozzles and breakapart nozzles shall be provided with ball-type shut-offs.
Nozzles shall be designed and rated for an inlet pressure of 100 psi.
All Class A nozzles, except Styles 1 and 2 shall be provided with rocker lugs and a free swiveling base, unless otherwise specified. For Styles 1 and 2 the base in optional with the manufacturer.
All Class B and C nozzles shall have rocker lugs and either a rigid or swivel base (manufacturer's option).
All threads to be of NH series, unless otherwise specified.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Workmanship. Nozzles shall be free of defects which may affect the durability, appearance or serviceability.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging packing, labeling, and marking shall be as specified in the contract or order.

Note. When this commercial item description is used for procurement the commercial item certification clause must appear in the solicitation.

Purchaser shall specify class and style as desired.

MILITARY INTERESTS:

Review Activity

Army - ME

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.