A-A-2293
May 15, 1984

COMMERCIAL ITEM DESCRIPTION

GAGE, WHEEL ALIGNMENT

The General Services Administration has authorized the use of this commercial item description.

Salient Characteristics:

The wheel alignment gage shall be capable of measuring caster, camber, and steering axis inclination and shall be combined in a single unit.

A gage or gages capable of accommodating wheel rim diameters of 10 inches to 24 inches shall be supplied. The gage shall be capable of being quickly mounted in a firm, secure, and fully operable fashion on all types of wheels within the 10 to 24 inch range. If necessary, the gage shall be supplied with adapters as appropriate to ensure compliance with this requirement. A means to check gage levelness with respect to the vehicle shall also be provided.

Scale requirements

Scales shall be permanently and legibly identified and marked in the graduations specified. Scales shall be easily read and interpreted. At minimum, caster and camber scales shall be independent.

All requirements specified for scale ranges are minimums.

Caster

Range: minus 3 degrees to plus 7 degrees
Graduation: 1/2 degree, numerically marked every 1 degree.
Readings shall be on a maximum of 20 degrees left turn and 20 degrees right turn of the front wheels from a straight ahead position.

Camber

Range: minus 2 degrees to plus 2 degrees
Graduation: 1/2 degree numerically marked every 1 degree.

Steering axes inclination

Range: minus 5 degrees to plus 9 degrees.
Graduation: 1/2 degree, numerically marked every 1 degree.
Readings shall be on a maximum of 20 degrees left turn and 20 degrees right turn of the front wheels from a straight ahead position.
Note: When steering axis inclination is not an independent scale, the scale used to make this measurement shall contain the range minus 5 degrees to plus 9 degrees.

FSC 5210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Gages shall be supplied with a complete set of operating instructions and a sturdy case suitable for carrying and storage and with sufficient space for the gage and all accessory components.

Workmanship. Gages supplied in accordance with this description shall be free from rust, burrs, fins, and defects that affect serviceability, durability, and appearance.

Testing. All gages shall be checked on testers or templates acceptable to the contracting officer. All measurements shall be accurate to within 5 percent of actual.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note: Assigned National Stock Number (NSN) 5210-00-529-0883.

MILITARY INTERESTS:

Military coordinating activity

Navy - YD

Custodians

Army - GL
Navy - YD

User activities

Army - AT
Navy - MC

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.