COMMERCIAL ITEM DESCRIPTION
COPYING MACHINE, INDIRECT ELECTROSTATIC PROCESS
(PLAIN PAPER)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers indirect electrostatic process copying machines having specific characteristics as hereinafter defined.

Classification:

Class A - manual feeding of original documents.
- Style 1- no reduction, enlargement, or sorting capabilities required.
- Style 2- minimum of two reduction modes plus one enlargement mode, sorter not required.
- Style 3- minimum of two reduction modes plus one enlargement mode, with sorter.
- Style 4- with sorter, no reduction or enlargement modes required.

Class B - semi-automatic document feed.
- Style 1 - no reduction, enlargement, or sorting capabilities required.
- Style 2- minimum of two reduction modes plus one enargement mode, sorter not required.
- Style 3- minimum of two reduction modes plus one enlargement mode, with sorter.
- Style 4- with sorter, no reduction or enlargement modes required.

Salient characteristics:

Copy machines shall be newly manufactured (not rebuilt or remanufactured).
Copy speed - 12 letter-size (3 1/2" X 11") copies per minute, minimum.
Maximum delivery time for first copy (after warmup) - S seconds.
To operate on 120 volts AC 60 HZ electrical current.
Flat-bed platen. Minimum size for classes 1 and 4 shall be 8 1/2" X 14", and minimum size for classes 2 and 3 shall be 11" X 17".
Self-diagnostic system consisting of a minirmum of three (3) lighted indicators which identify (a) needing toner, (b) needing papers and (c) paper misfeed or jam.
Paper trays (minimum of two to be furnished) having combined abilities to handle paper sizes described below.
Capability to copy on the following mediums, as a minimum:
(a) Plain cut sheet paper conforming to the requirements of Commercial Item Description A-A-1912, two sizes; 3 1/2" X 11" and 8 1/2" X 14".
(b) Self-adhesive labels.
(c) Transparencies.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Capability to copy pages of bound documents.
Shall be in accordance with U. L. Standard No. 114.
Multiple copy switch (minimum 1-99 copies).
Capability to copy carbonless blues (see Test Procedure II).
Operator acivated control which provides for darKening or lightening of copies.
Shall copy to within 7 min of the edge of the paper.
In style 2 machines one reduction mode shall produce copies that are 64 ± 3 percent the size of the original, the second mode shall produce copies that are 74 + 4 percent the size of the original, and the enlargement mode shall produce copies that are 120 ± 10 percent the size of the original.
in style 3 machines the reduction and enlargement modes shall correspond to the requirements for style 2 copiers.
in styles 3 and 4 machines sorters shall have a minimum of ten(10) receiving bins.

Performance requirements. The machine shall provide copies which have the following minimum qualities when tested as specified in Test Procedure L Paper used for testing shall conform to the requirements of Commercial item Description A-A-1912, issue in effect on the date of the Request for Proposal (RFP). Copies of the test targets presented as Figures I and II are for illustrative purposes only. Actual targets should be obtained from the sources referenced.

Resolution. Resolution shall equal or exceed 4.0 line pairs per millimeter.

Half-tones. The finished copy shall show at least three(3) distinct gray shades(excluding background).

Blackness, density. The solid darkest area on the finished copy shall show a reflectance of 10 percent or less. Adjacent background areas shall show a reflectance of SO percent or greater.

Carbonless blue. The average reflectance shall be 50.0 percent or less.

Test procedure L The copiers shall be installed in accordance with the manufacturer's normal commercial practice. Copies shall be made in accordance with the following procedure:

1. Turn on and warm up machine.
2. Place the resolution test target (Figure I) in position for reproduction.
3. Set the darkness/lightness control per the manufacturer’s operating instructions. If no instructions are provided, the control shall be set at the middle of its range.
4. Make twelve (12) runs of ten (10) copies each, so that a total of 120 copies are produced. Runs shall be made at ten(10) minute intervals so that the total copies arc produced within a 2 1/2 hour period.
5. The 11th, 55th, and 120th copies shall be removed for evaluation.
6. Repeat steps 2. through 5., using the IEEE test target (Figure II).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Evaluation: Evaluation of resolution shall be performed on copies produced from Figure I test target. Evaluation of half-tones and blackness shall be performed on copies produced from Figure II test target.

Resolution: Using a magnifier between 5X and 10X, determine the smallest line pair target in each target set which can be resolved. The line pair target is considered resolved when the lines(and spaces) are visibly separate. The resolution of the copiers shall be the lowest resolution value obtained from the 15 target sets on the three copies removed for evaluation.

Half-tones. Each of the three copies removed for evaluation shall be visually examined to determine that at least three distinct shades of gray are visible in both patterns 7 and 8 of the Test Chart. The white background shall not be considered a shade; the darkest step shall be considered a shade.

Blackness. The copies used for the half-tone evaluation also shall be visually examined to determine blackness of solid areas and whiteness of the back ground. Using a standard gray scale such as a "Munsell Neutral Value Scale", the observer shall visually compare patterns 7 and 8 on each copy to the gray scale, the observer shall determine the reflectance of the background by determining the reflectance of the first step of pattern 7 and the 15th step of pattern 8.

All six(6) dark area reflectance determinations shall comply with the reflectance requirement for the solid darkest area on the copy.

All six(6) background reflectance determinations shall comply with the reflectance requirement for the background tires of the copy.

Test procedure II (Copying Carbonless Blue):

1. Turn on and warm up the machine.
2. Make five(5) copies each of the color standard charts-Hue symbol 5PB, 7.5PB, and 10PB from the "Munsell Book of Color, Matte Finish Collection" with the dark[~css/lightness control set to make the darkest copies.
3. From each group of 5 copies, choose the 5th copy and perform the evaluation.

Evaluation:

Take the 5th copy of the 5PB Hue Color Chart and, using visual evaluation, match the lightest symbol in the 7 Value(V) line with one of the neutral grays of the "Munsell Neutral Value Scale" and record the reflectance value.

Repeat the above using the 7.5PB and 10PB Hue symbols.

Take the average of the three reflectance values and use it to determine compliance with the performance requirement under Carbonless Blue.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:21Z
Check the source to verify that this is the current version before use.

Identification. Each copier shall have the manufacturer's serial number permanently and legibly stamped or affixed on a major component in a readily accessible location. In addition, each copier shall be permanently and legibly marked in a conspicuous location with the manufacturer's name or trademark.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and mat-king. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Document Availability.

U.L. Standard No. 114 is avail able from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, ' L 60062.

Commercial Item Description A-A-1912 is available from General Services Administration, 7th and D Streets, S. W., Room 6039, Specification Section, Washington, DC 20407.

IEEE Standard 167A-1930, Facsimile Test Chart is available from the institute of Electrical and Electronic Engineers, 50 East Huron Street, Chicago, IL 60017.

Microcopy Resolution Test Chart, Standard Reference Material-1010a is available from the Office of Standard Reference Materials, National Bureau of Standards, Washington, DC 20234.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:21Z
Check the source to verify that this is the current version before use.