[METRIC]
A-A-891C
October 30, 1992
SUPERSEDING
A-A-891B
June 23, 1981

COMMERCIAL ITEM DESCRIPTION

TYPEWRITER
(ELECTRIC, SINGLE-ELEMENT)

The General Services Administration has authorized the use of this commercial item description.

This description covers heavy duty, office, non-portable, electric, typebar typewriters drawn from currently produced lots. Heavy duty refers to service classification capability of 10 years at 4 hours per day of business typing application prior to overhaul, i.e, 30 million impressions.

Salient characteristics:

Vertical line space selection with a minimum of three positions:
- Position 1 - 6 line spaces per 25 mm (1 inch).
- Position 2 - 3 line spaces per 12.5 mm (1/2 inch).
- Position 3 - Manufacturer's option.

Variable vertical spacer.
Paper bail with minimum of two bail rolls.
Adjustable paper guide.
Line finder device that permits ratchet-free movement of platen and return to original line of type.
Margin warning device.
Interchangeable type (easily removed and replaced)
Tabulator key (bar).
Tabulator set.
Tabulator clear (single and total).
Shift key (right and left).
Shift lock.
Shift lock release (right and left).
Margin release.
Carrier/carriage return with automatic line feed.
Backspace.
Spacebar (forward spacing)
Margin set (right and left).
Repeat keys (forward spacer, back space, underscore and hyphen).
Dust keys.
Pitch, designated in characters per 25 mm (1 inch)(as specified).
Type style (as specified).
Maximum paper width and related maximum horizontal writing line capability (as specified).
Ribbon/cartridge system (as specified), i.e., two ribbon positions (ribbon and stencil) and automatic ribbon reverse reqired for cloth ribbon, but not for cartridge systems.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7430

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

Color choice (as specified from colors available in contracted manufacturer's commercial selection).

Electro-mechanical requirements.

Typewriters shall be equipped with resilient feet or base to minimize movement and prevent marring of furniture. Minimum carriage clearance, without riser, shall be 85 mm (3-1/4 inch) from the desktop.
All keys and operating controls shall be easily accessible and in no case shall any controls be located on the back of the typewriter.
Unless otherwise specified, typewriter keyboards shall be in accordance with ANSI Standard X-4.23.
Typewriters shall operate on a 60 Hz, 115 V a.c. power source, unless otherwise specified. When specified, the typewriters shall conform to electro-magnetic interference requirements of MIL-STD-461, -462, -463, (on/off switch excepted from the requirements of these three standards).

Identification. Each typewriter shall have the manufacturer's serial number and name or trademark permanently and legibly stamped or affixed on a major component in a readily accessible location.

Optional features, as specified.
1) Error correcting capability.
2) Proportional spacing.
3) Last line indicator.
4) Dual pitch capability.

Workmanship. Typewriters shall be be clean, free from faulty construction or any defects which may effect either appearance, serviceability or durability or constitute a hazard to the user.

Compliance. Typewriters shall conform to UL Standard No. 114. The issue of UL Standard No. 114 in effect on the date of the solicitation shall be used to determine compliance with this requirement.

Regulatory requirements. In accordance with Section 23.403 of theFederal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:11Z
Check the source to verify that this is the current version before use.

UL Standard No. 114 is available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

ANSI Standard X4.23 is available from the American National Standard Institute, 1430 Broadway, New York, NY 10018.

Military Standards 461, 462, 463 are available DODSSP, Standardization Document Order Desk, 700 Robbins Avenue, Bldg 4D, Philadelphia, PA 19111-2978.

PREPARING ACTIVITY

GSA - FSS

Source: https://assist.dla.mil Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

UL Standard No. 114 is available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

ANSI Standard X4.23 is available from the American National Standard Institute, 1430 Broadway, New York, NY 10018.

Military Standards 461, 462, 463 are available from DODSSP, Standardization Document Order Desk, 700 Robbins Avenue, Bldg 4D, Philadelphia, PA 19111-2978.

PREPARING ACTIVITY

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.