MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED SCHOTTKY TTL, PARITY CHECKER, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/349A, dated 1 October 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, I_{IL}, min limits column: Delete "-.03" and substitute "+.02".

PAGE 4

4.2a.(1): Add test condition F.

Table II, Group A test requirements, class B devices: Add subgroups "10, 11".

PAGE 12

TABLE II, V_{CC} pin, test no. 23: Add "5/".

PAGE 15

TABLE III, note 2, circuit C, Add: "-.02/+.02".

TABLE III: Add note 5 "5/ At the option of the manufacturer, V_{CC} = 0.0 V."

PAGE 16

4.4.3b.(1): Add test condition F.

PAGE 17

6.2g: Delete "carriers,".

6.6, TABLE IV, under circuit C: Add "X".

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1005)

AMSC N/A

FSC 5962

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:25Z
Check the source to verify that this is the current version before use.