METRIC

A-A-267C
6 December 2010
SUPERSEDING
A-A-267B
28 January 1998

COMMERICIAL ITEM DESCRIPTION

DEODERANT, GENERAL PURPOSE (AEROSOL AIR FRESHENER)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description covers an aerosol air freshener to counteract malodors in occupied indoor areas such as public buildings and aircraft.

2. SALIENT CHARACTERISTICS.

2.1 The product shall not contain formaldehyde.

2.2 The product shall leave a mild and pleasant odor immediately after spraying

2.3 When used as directed on the container, the product shall counteract the odors from stale cigar and cigarette smoke, urine and fecal matter, vomit, food spillage, garbage, cooked foods, perspiration, and pets.

2.4 The product shall be contained in an aerosol dispenser. The dispenser shall produce a spray in the form of a fine mist when moderate finger pressure is applied on the actuator. The dispenser shall stop the release of the spray immediately upon release of the pressure on the actuator. The dispenser shall deliver at least 98 percent by weight of its contents.

2.5 Delivery rate. When tested as specified in ASTM D3069 – Delivery Rate of Aerosol Products, the dispenser shall not have a delivery rate not less than 0.3 grams per second and not greater than 2.0 grams per second.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or Defense Logistics Agency Aviation VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.daps.dla.mil/.

AMSC N/A FSC 6840

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

2.6 Net weight. The net weight of the contents of the aerosol dispenser shall be a minimum of 396 grams (14 ounces avoirdupois).

2.7 Flammability. When tested as specified in ASTM D1310 – Flash Point and Fire Point of Liquids by Tag Open-Cup Apparatus and ASTM D3065 – Flammability of Aerosol Products, the product shall meet the following requirements:

Flame Projection	-	2.54 cm (1 inch), maximum
Tag O/C Flash Point	-	47°C (116°F), minimum
Closed Drum Test	-	45 seconds, minimum

2.8 Seepage. When tested as specified in ASTM D3094 – Seepage Rate of Aerosol Products, the dispensers shall have a seepage rate no greater than 3.0 mL, using wide mouth eudiometer tubes similar to that in Figure 2 of ASTM D3094.

2.9 Container stability. The filled container shall not leak or be damaged by internal pressure when heated to 54°C (130°F).

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE.

4.1 Product Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING. Preservation, packaging, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 The contractor may use his normal quality assurance procedure for manufacture of this product; however, should a disagreement arise between the Government and its customer or between the Government and the manufacturer concerning compliance to the salient characteristics of this commercial item description, the test methods and tests stated in this commercial item description will be used to determine compliance of the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

6.2 Source of Documents.

6.2.1 ASTM standards. Copies of ASTM standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959. Electronic copies of ASTM standards may be obtained from http://www.astm.org/.

6.2.2 FAR. The FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies may be obtained from https://www.acquisition.gov/far/.

Civil Agency Coordinating Activity:

GSA – FAS

Preparing Activity:

DLA – GS3

(Project 6840-2011-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.