A - A - 7 4 1
August 20, 1980

COMMERCIAL ITEM DESCRIPTION

MOWER, LAWN, ROTARY, WALK BEHIND (HAND PROPELLED)

The General Services Administration has authorized the use of this commercial item description.

This commcercial item description covers rotary type, hand-propelled, walk behind, 4 cycle, recoil starter, gasoline powered lawn mower intended for heavy duty, industrial use,

Salient characteristics:

Power requirements:

Class A -- 3-1/2 rated horsepower
Class B - 4 rated horsepower
Class C - 5 rated horsepower

Cutting swath in inches (Nominal):

Size I - 18 inches
Size 2 - 20 inches
Size 3 - 21 inches
Size 4 - 22 inches

Minimum acceptable blade tip speed at full throttle - 250 feet per second (170.5 mph).

The engine rated horsepower specified shall be maximum engine power rated at 3600 rpm per SAE J-607 procedure. The maximum operation speed may be lower than 3600 rpm.

The sound level shall not exceed 86dB(A) at the operator's ear when measured in accordance with SAE 3-1174 procedure.

Each wheel shall have a bolt and nut type height it adjuster with a minimum range of 2 inches adjustable to a minimum of 3 cutting heights.

The handle shall be adjustable to a minimum of 3 positions. All operator's controls shall be conveniently located for ease of operation from the operator's position. All controls shall be positive in action and remain fixed in set position.

The mower shall withstand dropping 10 times from a height of 36 inches onto a concrete floor and landing essentially on all wheels. Wheel alignment shall be measured before and after to assure no permanent deformation has occured. The blade height inside the housing to the lower edge of the housing shall be measured before and after. No more than 1/8 inch deformation shall have occurred to the deck as measured at any point around the blades circumference. Acceptance shall require that none of the component parts shall fracture, break, loosen or deform in a manner that would adversely affect performance or would constitute a hazard to the operator.

The wheels shall be steel with roller or ball bearings. If bearings are not sealed, grease fittings are required. The wheels shall have a minimum diameter of 8 inches.

The mower shall have either an Outdoor Power Equipment Institute (OPEI) label or meet all applicable requrements of ANSI-B71.4, Safety Specifications for Commercial Tuft Care Equipment, latest revision, when tested by an independent testing laboratory acceptable to the Government.

Where referenced requirments are in conflict with this commercial item, description, the requirements herein specified shall govern.

Workmanship. The mower shall be free from defects such as fractures, splits, punctures, dents, rust deterioration or malformations, sharp edges, burrs and slivers, Finish shall consist of a durable rust-proof, weather proof coating of lacquer, enamel or equal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

The issues of ANSI and SAE standards in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description, and that the product conforms to the producer's own drawings, specifications, standards, and quali- assurance practices and is the same product offered for sale in the commercial marketplace, The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under- the provisions of the contract.

Recovered materials, The manufacturer shall utilize recovered materials to the maximum extent practicable,

Packaging, packing, and marking, The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage, The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification, Marking shall be as specified in the contract order,

ANSI Standards are available from the American National Standards Institute, Inc., 1430 Broadway, New York, N 10018.

SAE Standards are available from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, P 15096.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.