The documentation and process conversion measures necessary to comply with this amendment shall be completed by 26 July 1995

INCH-POUND

MIL-S-19500/291E
AMENDMENT 1
26 April 1995

MILITARY SPECIFICATION
SEMICONDUCTOR DEVICE, TRANSISTOR, PNP,
SILICON, SWITCHING,
TYPES 2N2906A, 2N2907A, 2N2906AUA
2N2907AUA, 2N2906AUB, AND 2N2907AUB
JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This amendment forms a part of MIL-S-19500/291E, dated 28 July 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, add the following new note:

"11. In accordance with ANSI Y14.5M, diameters are equivalent to ϕx symbology."

PAGE 9

4.3, screen table, screen 7, JANS column, after "hermetic seal" add "(optional)"; JANTX and JANTXV column, delete "hermetic seal" and add "1/"; screen 10, delete "48 hours minimum" and substitute "24 hours minimum" (both columns); below table, add the following note:

"1/ Hermetic seal test shall be performed in either screen 7 or screen 14."

PAGE 10

4.4, end of paragraph, add the following:

"If alternate screening is being performed per 4.6.3.1d and figure 2 of MIL-S-19500, a sample of screened devices shall be submitted to and pass the requirements of group A1 and A2 inspection only (table IVb, group B, subgroup 1 is not required to be performed again if group B has already been satisfied per 4.4.2)."

4.4.2.1, delete "B3" and substitute "B4".

PAGE 11

4.4.2.3b., end of paragraph, add the following:

"When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test (subgroups B3 and B5 for JANS, and subgroups B1 and B2 for JAN, JANTX, and JANTXV) may be pulled prior to the application of final lead finish."

PAGE 15

TABLE I, subgroup 3, collector to base cutoff current, conditions column, delete "V_{CB} = 60 V dc" and substitute "V_{CB} = 50 V dc"; subgroup 4, magnitude of small-signal short-circuit forward current transfer ratio, conditions column, delete "I_C = 20 mA" and substitute "I_C = 50 mA".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:08Z
Check the source to verify that this is the current version before use.

PAGE 16

TABLE II, step 7, collector to base cutoff current, conditions column, delete "V_{CB} = 60 V dc" and substitute "V_{CB} = 50 V dc".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, SH
Air Force - 13, 15, 19, 85, 99
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5961-1710)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:08Z
Check the source to verify that this is the current version before use.