METRIC
FF-B-171/27
30 NOVEMBER 1993

FEDERAL SPECIFICATION SHEET

BEARING, BALL, ANNULAR, SINGLE ROW, ANGULAR CONTACT, COUNTERBORED OUTER RING, CONTACT ANGLE ABOVE 22° UP TO AND INCLUDING 32°, NON-SEPARABLE, ANSI/AFBMA DIMENSION SERIES 04.

The complete requirements for acquiring the bearings described herein shall consist of this document and the latest issue of FF-B-171/GEN.




FIGURE 1.
OPEN (NO SHIELDS OR SEALS)
(CODE A)

BEARING CONFIGURATIONS

AMSC/NA FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Boundary dimensions. The boundary dimensions shall be specified in the part number by the size code in table I.

2. Cages. Cages shall be manufactured from any material unless otherwise specified. Cages shall be specified in the part number by the codes in table II.

3. Shields and Seals. All angular contact bearings with counterbored outer rings shall be open (no shields or seals, see figure 1) and designated by the code "A" in the part number.


4. Radial Internal clearance. The tolerance limits for radial internal clearance shall be in accordance with ANSI/AFBMA Standard 20 and shall be specified in the part number by the codes in table III.

5. Tolerance Class. The tolerance limits for tolerance class ABEC-1 and ABEC-5 shall be in accordance with ANSI/AFBMA Standard 20 and shall be specified in the part number by the codes in table III.

6. Preservative Compound. All bearings shall be supplied with preservative compound in accordance with MIL-P-197 and designated by the code "C" in the part number.

7. Part number. The part number consists of the letters FFB, the basic Federal specification number, the specification sheet number, and alpha or numeric codes for cage, size, shields and seals, radial internal clearance and tolerance class, and preservative compound.

EXAMPLE : FFB171/27 Y 10 A 6 C



FFB171/27Y10A6C indicates - Bearing, cage-pressed brass: bore 50mm: outside diameter 130mm; width 31mm; open (no shields or seals); radial internal clearance-symbol O (normal); tolerance class ABEC-5; preservative compound in accordance with MIL-P-197.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:45Z
Check the source to verify that this is the current version before use.

TABLE I. Boundary dimensions.

Size Code 1/	OB Bore	OD Outside Diameter	W Width	Chamfer $r_s$min 2/	Shaft Shoulder Diameter Min 3/	C Dynamic Load Rating (Pounds)
00	25	80	21	5.1	34	6430
06	30	90	23	1.5	39	8305
07	35	100	25	1.5	44	10535
08	40	110	27	2.0	50	11385
09	45	120	29	2.0	55	14835
10	50	130	31	2.1	62	16780
11	55	140	33	2.1	67	19305
12	60	150	35	2.1	72	20960
13	65	160	37	2.1	77	22650
14	70	180	42	3.0	84	26070
15	75	190	45	3.0	89	27860
16	80	200	48	3.0	94	31355
17	85	210	52	4.0	103	33245
18	90	225	54	4.0	108	37535

1/ Size codes in Table I are industry bore codes.

2/ The minimum bearing chamfer ($r_s$min) must clear the maximum shaft or housing fillet radius. This dimension does not control the shape of the bearing chamfer contour.

3/ For reference purposes only. Maximum shoulder heights shall be such as to permit bearing removal pressure to be applied to the bearing inner ring. In cases where this requirement cannot be met, provisions shall be made for the removal of the bearing from the shaft without damage to the bearing or other parts.

TABLE II. Codes for Cages.

Code	Cage
J	Pressed steel or molded plastic
M	Machined bronze or brass
T	Machined non-metallic (phenolic)
Y	Pressed brass

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:45Z
Check the source to verify that this is the current version before use.

TABLE III. Codes for Radial Internal Clearance and ABEC tolerance.

Code	Radial Internal Clearance	Tolerance Class
1 2 3 4	Symbol 2 (Less than normal) Symbol 0 (Normal) Symbol 3 (Greater than normal) Symbol 4 (Greater than symbol 3)	ABEC-1
5 6 7 8	Symbol 2 (Less than normal) Symbol 0 (Normal) Symbol 3 (Greater than normal) Symbol 4 (Greater than symbol 3)	ABEC-5

MILITARY INTERESTS:

Military Coordinating Activity:
DLA - IS

Custodians:
Army - AT
Air Force - 11

Review Activities:
Army - AR, EA, MI
Navy - OS

User Activity:
Army - GL, ME

CIVIL AGENCY COORDINATING ACTIVITIES:
GSA-FSS

PREPARING ACTIVITY:
DLA-IS

(Project 3110-0848-27)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:45Z
Check the source to verify that this is the current version before use.