The documentation and process conversion measures necessary to comply with this revision shall be completed by 30 October 1999.

INCH-POUND

MIL-PRF-19500/538A(USAF)
30 July 1999
SUPERSEDING
MIL-S-19500/538(USAF)
22 October 1980

PERFORMANCE SPECIFICATION SHEET
SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER
TYPE 2N6676, 2N6678, 2N6691 AND 2N6693 JAN, JANTX AND JANTXV

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon, power transistors. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (TO-3) - 2N6676, 2N6678; and figure 2 (TO-61) - 2N6691, 2N6693.

1.3 Maximum ratings.

Types	P_T T_A = +25°C 1/	P_T T_C = +25°C 1/	V_{CBO} and V_{CEX}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}
	W	W	V dc	V dc	V dc	A dc	A dc	°C
2N6676	6	175	450	300	8.0	5	15	-65 to +200
2N6678	6	175	650	400	8.0	5	15	-65 to +200
2N6691	3	175	450	300	8.0	5	15	-65 to +200
2N6693	3	175	650	400	8.0	5	15	-65 to +200

1/ Derate linearly 1.0 W/°C for T_C > +25°C.
Derate linearly 34.2 mW/°C for T_A > +25°C - 2N6676 and 2N6678.
Derate linearly 17.1 mW/°C for T_A > +25°C - 2N6691 and 2N6693.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad St., Columbus, OH 43216-5000, by using the addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. at T_C = +25°C.

	h_{FE1} V_{CE} = 3 V dc I_C = 1 A dc 1/	h_{FE2} V_{CE} = 3 V dc I_C = 15 A dc 1/	$V_{BE(sat)}$ I_C = 15 A dc I_B = 3 A dc	$V_{CE(sat)}$ I_C = 15 A dc I_B = 3 A dc	$R_{\theta JC}$
			V dc	V dc	°C/W
Min	15	8			
Max	40	20	1.5	1.0	1.0

	$\lvert h_{fe} \rvert$	C_{obo}	Switching				
	V_{CE} = 10 V dc I_C = 1 A dc f = 5 MHz	V_{CB} = 10 V dc I_E = 0 100 KHz < f < 1 MHz	t_c	t_d	t_r	t_s	t_f
		pF	µs	µs	µs	µs	µs
Min	3	150					
Max	10	500	0.5	0.1	0.6	2.5	0.5

1/ Pulsed (see 4.5.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Defense Automated Printing Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.


3. REQUIREMENTS

3.1 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified manufacturer's list before contract award (see 4.2 and 6.3).

3.2 Associated specification. The individual item requirements shall be in accordance with MIL-PRF-19500 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.


Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		0.875		22.22	3
CH	0.270	0.380	6.86	9.65	
HR	0.495	0.525	12.57	13.34	
HR1	0.131	0.188	3.33	4.78	
HT	0.060	0.135	1.52	3.43	
L1		0.050		1.27	5, 9
LD	0.038	0.043	0.97	1.09	5, 9
LL	0.312	0.500	7.92	12.70	5
MHD	0.151	0.161	3.84	4.09	7
MHS	1.177	1.197	29.90	30.40	
PS	0.420	0.440	10.67	11.18	4
PS1	0.205	0.225	5.21	5.72	4, 5
S	0.655	0.675	16.64	17.14	4



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Body contour is optional within zone defined by CD
4. These dimensions shall be measured at points 0.050 (1.27 mm) to 0.055 (1.40 mm) below seating plane. Measurement shall be made at seating plane.
5. Both terminals.
6. At both ends.
7. Two holes.
8. Terminal 1 is the emitter, terminal 2 is base. The collector shall be electrically connected to the case.
9. LD applies between L1 and LL. Diameter is uncontrolled in L1.
10. In accordance with ANSI Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (T0-3) for 2N6676 and 2N6678.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.



Ltr	Dimension				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A_1	- - -	0.270	- - -	6.86	
CD	0.570	0.610	14.48	15.49	
CD_1	0.610	0.687	15.49	17.45	
CH	0.325	0.460	8.26	11.68	
HF	0.667	0.687	16.94	17.45	
HT	0.090	0.150	2.29	3.81	
OAH	0.640	0.875	16.26	22.22	4
PS	0.340	0.415	8.64	10.54	3, 6
PS_1	0.170	0.213	4.32	5.41	3, 6
SL	0.422	0.455	10.72	11.56	
SU	- - -	0.090	- - -	2.29	7
T	0.047	0.072	1.19	1.83	
T_1	0.046	0.077	1.17	1.96	
UD	0.220	0.249	5.59	6.32	

NOTES:
1. Metric equivalents are given for general information only.
2. See NSB Handbook H28, “Screw-Thread Standards for Federal Services”.
3. The orientation of the terminals in relation to the hex flats is not controlled.
4. All three terminals.
5. The case temperature may be measured anywhere on the seating plane within 0.125 inch (3.18 mm) of the stud.
6. Terminal spacing measured at the base seat only.
7. This dimension applies to the location of the center line of the terminals.
8. Terminal - 1, emitter; terminal - 2, base; terminal - 3, collector. all leads are isolated from the case.

FIGURE 2. Physical dimensions (TO-61) for 2N6691 and 2N6693.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and figure 1 (TO-3) - 2N6676, 2N6678; and figure 2 (TO-61) - 2N6691, 2N66931 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

4.VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.3 Screening. Screening shall be in accordance with table IVb of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurements
	JANTX, JANTXV levels
9	I_{CEX1}
11	I_{CEX1} and h_{FE2}; ΔI_{CEX1} = 100 percent of initial value or 50 µA dc, whichever is greater.
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_{CEX1} = 100 percent of initial value or 50 µA dc, whichever is greater. h_{FE2} = ± 25 percent of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

T_J = + 187.5 °C, ± 12.5 °C; $V_{CB} \geq$ 100 V dc; $T_A \leq$ 35°C.

4.3.2 Isolation resistance test. Isolation resistance test conditions are as follows: MIL-STD-750, method 1016, test condition B, short collector, emitter and base terminals together. Limit is 10^9 Ω minimum.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIb (JAN, JANTX, and JANTXV) and in 4.4.2.1 herein. Electrical measurements (end-points) shall be in accordance with group A, subgroup 2 herein. Delta requirements shall be in accordance with table II herein.

4.4.2.1 Group B inspection, table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	For eutectic die attach: $V_{CB} \geq 100$ V dc; adjust P_T to achieve T_J = 187.5° C, ± 12.5°C; $T_A \leq 35$°C.
B3	1037	For solder die attach: 2,000 cycles, $V_{CB} \geq 100$ V dc.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500 and herein. Electrical measurements (end-points) shall be in accordance with group A, subgroup 2 herein. Delta requirements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Test condition A; weight = 10 pounds; time = 15 s.
C2	2036	Test condition D1; torque = 6 inch-ounce; time =15 s.
C2	2036	Stud torque (2N6691, 2N6693 only) Test condition D2; torque = 15 inch-pound; time = 15 s.
C6	1027	For eutectic die attach: $V_{CB} \geq 100$ V dc; adjust P_T to achieve T_J = 187.5° C, ± 12.5°C; $T_A \leq 35$°C.
C6	1037	For solder die attach: 2,000 cycles, $V_{CB} \geq 100$ V dc.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Thermal resistance. Thermal resistance measurements shall be conducted in accordance with method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power application shall be 2.5 A dc.

b. Collector to emitter voltage magnitude shall be 20 V dc.

c. Reference temperature measuring point shall be the case.

d. Reference point temperature shall be 25°C to 75°C.

e. Mounting arrangement shall be with heat sink to case.

f. Maximum limit of $R_{\theta JC}$ shall be 1.0 °C/W.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1 Visual and mechanical examination	2071					
Subgroup 2						
Collector to base breakdown voltage 2N6676, 2N6691 2N6678, 2N6693	3011	Bias condition D, I_C = 200 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	 300 400		V dc
Collector to emitter cutoff current 2N6676, 2N6691 2N6678, 2N6693	3041	Bias condition A; V_{BE} = -1.5 V dc V_{CE} = 450 V dc V_{CE} = 650 V dc	I_{CEX1}		0.1	mA dc
Collector to base cutoff current 2N6676, 2N6691 2N6678, 2N6693	3036	Bias condition D; V_{CB} = 450 V dc V_{CB} = 650 V dc	I_{CBO}		1.0	mA dc
Emitter-base cutoff current	3061	Bias condition D, V_{EB} = 8 V dc	I_{EBO}		2.0	mA dc
Base emitter voltage	3066	Test condition A; I_C = 15 A dc; pulsed (see 4.5.1); I_B = 3 A dc	$V_{BE(sat)}$		1.5	V dc
Collector to emitter saturated voltage	3071	I_C = 15 A dc; pulsed (see 4.5.1) I_B = 3 A dc	$V_{CE(sat)1}$		1.0	V dc
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 1 A dc; pulsed (see 4.5.1)	h_{FE1}	15	40	
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 15 A dc; pulsed (see 4.5.1)	h_{FE2}	8	20	
Isolation resistance (2N6691 and 2N6693 only)	1016	See 4.3.2	R_{ISO}	$1x10^9$		Ω
Subgroup 3						
High-temperature operation:		T_A = +125°C				
Collector to emitter cutoff current 2N6676, 2N6691 2N6678, 2N6693	3041	Bias condition A; V_{BE} = -1.5 V dc V_{CE} = 450 V dc V_{CE} = 650 V dc	I_{CEX2}		1.0	mA dc

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - Continued						
Collector to emitter saturated voltage	3071	I_C = 15 A dc; I_B = 3 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		2.0	V dc
Low-temperature operation :		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 3 V dc I_C = 15 A dc; pulsed (see 4.5.1)	h_{FE3}	4		
Subgroup 4						
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 1 A dc; f = 1 MHz	$\|h_{fe}\|$	3	10	
Open capacitance (open circuit)	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1.0 MHz	C_{obo}	150	500	pF
Switching parameters:		T_A =+125°C				
Pulse delay time		See figure 3	t_d		0.1	µs
Pulse rise time		See figure 3	t_r		0.6	µs
Pulse storage time		See figure 3	t_s		2.5	µs
Pulse fall time		See figure 3	t_f		0.5	µs
Cross over time		See figure 3	t_c		0.5	µs
Subgroup 5						
Safe operating area (dc operation)	3051	**T_C = +25°C** t = 1 s; 1 cycle; (See figure 4)				
Test 1 (All device types)		V_{CE} = 11.7 V dc; I_C = 15 A dc				

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 5 - Continued						
Test 2 (2N6676, 2N6678)		V_{CE} = 30 V dc; I_C = 5.9 A dc				
Test 3 (All device types)		V_{CE} = 100 V dc; I_C = 0.25 A dc				
Test 4 (2N6691, 2N6693)		V_{CE} = 25 V dc; I_C = 7 A dc				
Test (2N6676, 2N6678) (2N6691, 2N6693)		V_{CE} = 300 V dc; I_C = 20 mA dc V_{CE} = 400 V dc; I_C = 10 mA dc				
Safe operating area (clamped switching)	3053	T_A = 25°C, V_{CC} =15 V dc (see figure 6); Load condition B, V_{BB2} = 5.0 V, R_{BB1} = 5 Ω; R_{BB2} = 1.5 Ω; L = 50 µH; R of inductor = 0.05 Ω, R_{load} =R of inductor				
2N6676, 2N6691		Clamp voltage = 350 V dc; I_C = 15 A dc				
2N6678, 2N6693		Clamp voltage = 450 V dc; I_C = 15 A dc				
Electrical measurements		Table I, subgroup 2 herein.				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan see MIL-PRF 19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

TABLE II. Groups A, B, and C delta electrical measurements. 3/ 4/

Steps	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector to emitter cutoff current 2N6676, 2N6691 2N6678, 2N6693	3041	Bias condition A; V_{BE} = -1.5 V dc V_{CE} = 450 V dc V_{CE} = 650 V dc	ΔI_{CEX1} 2/	100 percent of initial value or 50 µA whichever is greater.		
2.	Forward - current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 15 A dc; pulsed (see 4.5.1)	Δh_{FE2}	± 25 percent change from initial reading.		
3.	Collector to emitter voltage (saturated)	3071	I_C = 15 A dc; I_B = 3 A dc, pulsed (see 4.5.1)	$\Delta V_{CE(sat)1}$	± 100 mV change from previously measured value.		

1/ See MIL-PRF-19500 for sampling plan.

2/ Devices which exceed the group A limits for this test shall not be acceptable.

3/ The delta electrical measurements for table VIb (JAN, JANTX and JANTXV) of MIL-PRF-19500 are as follows:

a. Subgroup 3, see table II herein, steps 1 and 2.

b. Subgroup 6, see table II herein, step 2.


4/ The delta electrical measurements for table VII of MIL-PRF-19500 are as follows:

a. Subgroup 2, see table II herein, step 1.


b. Subgroup 3, see table II herein, step 1.

c. Subgroup 6, see table II herein, steps 1, 2 and 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.




t_d AND t_r TIME TEST CIRCUIT




t_s AND t_f TIME TEST CIRCUIT

FIGURE 3. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.



t_c TIME TEST CIRCUIT



SAME INPUT WAVEFORM AS t_s AND t_f TIME TEST CIRCUIT

NOTES:

1. The rise time (t_r) of the applied pulse shall be ≤ 20 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 ohms.
2. Output sampling oscilloscope: $Z_{in} \geq 100$ k ohms; $C_{in} \leq 12$ pF; rise time ≤ 20 ns.

FIGURE 3. Pulse response test circuits - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.




FIGURE 4. Maximum safe operating graph (DC).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.




FIGURE 5. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.




FIGURE 6. Safe operating area for switching between saturation and cutoff (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Issue of DODISS to be cited in the solicitation (see 2.2.1).

b. The lead finish as specified (see 3.4.1).

c. Type designation and quality assurance level.

d. Packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturer's List QML-19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, DSCC-VQE, Columbus, OH 43216.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA – CC

(Project 5961-F154)

Review activities:
Air Force - 13, 19
Army - MI

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/538A(USAF)	2. DOCUMENT DATE (YYMMDD) 990730

3. DOCUMENT TITLE
SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER TYPES 2N6676, 2N6678, 2N6691 AND 2N6693 JAN, JANTX AND JANTXV

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) Commercial DSN FAX EMAIL	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. Point of contact: Alan Barone,	b. TELEPHONE Commercial 614-692-0510 DSN 850-0510 FAX 614-692-6939 EMAIL alan_barone@dscc.dla.mil
c. ADDRESS : Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad Street, Columbus, OH 43216-5000	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533, Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-68880

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:57Z
Check the source to verify that this is the current version before use.