The documentation and process conversion measures necessary to comply with this amendment shall be completed by 12 May 1996

INCH-POUND

MIL-S-19500/552A(USAF)
AMENDMENT 2
12 February 1996
SUPERSEDING
AMENDMENT 1
25 January 1995

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, TRANSIENT VOLTAGE SUPPRESSOR
TYPES 1N6469 THROUGH 1N6476
JAN, JANTX, AND JANTXV

This amendment forms a part of MIL-S-19500/552A(USAF), dated 27 December 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

Preamble, delete and substitute as printed above.

PAGE 3

Figure 1, dimension table and notes; delete and substitute as follows:

"

| Ltr | Dimensions | | | | Notes |
|---|---|---|---|---|---|
| | Inches | | Millimeters | | |
| | Min | Max | Min | Max | |
| ϕB | .150 | .185 | 3.81 | 4.70 | 3 |
| ϕD | .037 | .042 | 0.94 | 1.07 | |
| G | .150 | .375 | 3.81 | 9.53 | 3 |
| L | .900 | 1.300 | 22.86 | 33.02 | |
| $L_1$ | | .050 | | 1.27 | 4 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Package contour optional within ϕB and length G. Heat slugs, if any, shall be included within this cylinder but shall not be subject to minimum limit of ϕB.
4. Within this zone lead, diameter may vary to allow for lead finishes and irregularities other than heat slugs."

PAGE 4

4.3, screen 11, measurement column; delete "Iadvance down .035R" and substitute "$I_D$". Screen 13, measurement column; delete "$\Delta I_R$" and substitute "$\Delta I_D$".


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:12Z
Check the source to verify that this is the current version before use.

PAGE 5

* 4.4.2.1, B5; delete "$R_{\Theta JL} \leq 50°C/W$, $+25°C \leq T_L \leq +35°C$" and substitute "$R_{\Theta JA} \leq 50°C/W$, $+25°C \leq T_A \leq +35°C$".

PAGE 6

TABLE I, subgroup 2, reverse current, maximum limits column; delete "column 2 of table III" and substitute "column 5 of table III".

TABLE I, subgroup 4, forward voltage, $V_F$, minimum limits column; delete "1.5" and in maximum limits column, add "1.5".

TABLE I, subgroup 4, forward voltage, $V_{FM}$, minimum limits column; delete "4.8" and in maximum limits column, add "4.8".

PAGE 7

TABLE II, step 1, inspection column, reverse current; delete "standby". Step 3, inspection column, reverse current; delete "standby"; in the symbol column, delete "1/". Step 4, in the symbol column, delete "1/".

PAGE 8

TABLE III, delete and substitute as follows:

"

TABLE III. Electrical characteristics.

| Col 1 | Col 2 | Col 3 | Col 4 | Col 5 | Col 6 | Col 7 | | Col 8 | Col 9 | Col 10 |
|---|---|---|---|---|---|---|---|---|---|---|
| | $V_{(BR)}$ at $I_{(BR)}$ min | $I_{(BR)}$ $t_p$ =300ms duty cycle ≤ 2 % | $V_{RWM}$ | $I_D$ at $V_{RWM}$ | $V_C$ at $I_{pp}$ for $t_p$ =1 ms | $I_p$ $t_p$ = 20 µs $t_r$ =8 µs | $I_p$ $t_p$ = 1 ms $t_r$ =10 µs | $\alpha_{V(BR)}$ at $I_{(BR)}$ | $V_{(BR)}$ min at $I_{(BR)}$ $T_A$ = -55°C | $V_{CF}$ at $t_p$ = 1 ms mA(PK) = per col 7 inverse polarity |
| | V dc | mA dc | V(PK) | µA dc | V (PK) | A (PK) | A (PK) | % /°C | V dc | V (PK) |
| 1N6469 | 5.6 | 50 | 5 | 5,000 | 9.0 | 945 | 167 | -.03,+.045 | 5.4 | -3.5 |
| 1N6470 | 6.5 | 50 | 6 | 5,000 | 11.0 | 775 | 137 | +.060 | 6.2 | -3.2 |
| 1N6471 | 13.6 | 10 | 12 | 1,000 | 22.6 | 374 | 66 | +.085 | 12.7 | -3.8 |
| 1N6472 | 16.4 | 10 | 15 | 1,000 | 26.5 | 322 | 57 | +.085 | 15.3 | -3.8 |
| 1N6473 | 27.0 | 5 | 24 | 100 | 41.4 | 206 | 36.5 | +.096 | 24.9 | -3.6 |
| 1N6474 | 33.0 | 1 | 30.5 | 5 | 47.5 | 190 | 32 | +.098 | 30.2 | -3.6 |
| 1N6475 | 43.7 | 1 | 40.3 | 5 | 63.5 | 136 | 24 | +.101 | 40.0 | -3.5 |
| 1N6476 | 54.0 | 1 | 51.6 | 5 | 78.5 | 106 | 19 | +.103 | 48.5 | -3.4 |

"



Source: https://assist.dla.mil -- Downloaded: 20261019T03:12Z
Check the source to verify that this is the current version before use.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodian:
Air Force - 17

Review activities:
Air Force - 13, 19, 85, 99

Preparing activity:
DLA - ES

(Project 5961-F133)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:12Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:12Z
Check the source to verify that this is the current version before use.