

FED. SUP CLASS
2610





IND STR SD
REGULAR
(TYPICAL) (1)



IND STR SD
RIBBED
(TYPICAL)



TR REAR
DIRECTIONAL TRACTION
(DIR TRTN)
(TYPICAL)



TR FRONT
RIBBED
(TYPICAL)

NOTES:

1. THE "TYPICAL" TREAD PATTERNS DEPICTED ARE SELECTED FROM THOSE PATTERNS COMMERCIALLY AVAILABLE. THEY ARE FOR ILLUSTRATIVE PURPOSES ONLY AND ARE NOT TO BE CONSTRUED AS REPRESENTING A SPECIFIC CONFIGURATION OR ANY PARTICULAR MANUFACTURER.
2. "TYPE CLASSIFICATIONS", AS FOLLOWS, ARE DEFINITIVE ONLY AND SHOULD NOT BE INTERPRETED AS LIMITING APPLICATION OF THE TIRE.

IND STR SD	INDUSTRIAL STRAIGHT SIDE OR INDUSTRIAL PNEUMATIC
TR REAR	AGRICULTURAL OR INDUSTRIAL TRACTOR REAR
TR FRONT	AGRICULTURAL OR INDUSTRIAL TRACTOR FRONT

3. NYLON CORD OR POLYESTER CORD MAY BE SUBSTITUTED FOR RAYON CORD.
4. RATED LOADS ARE BASED ON SPEEDS OF 10 MILES PER HOUR MAXIMUM FOR IND STR SD TIRES AND 20 MILES PER HOUR MAXIMUM FOR TR REAR AND TR FRONT TIRES.
5. THE "TUBE USED, MS DASH NO." REFERS TO MILITARY STANDARD MS 35392 INNER TUBE, PNEUMATIC TIRE.
6. THE "MEASURING RIM" IS THE "STANDARD RIM" OR "PREFERRED RIM" DESIGNATED IN THE TIRE AND RIM ASSOCIATION, INC. YEARBOOK.
7. "TIRE SECTION" IS THE WIDTH OF A NEW TIRE, INCLUDING NORMAL GROWTH DUE TO INFLATION AND INCLUDING NORMAL SIDE WALLS, BUT NOT INCLUDING PROTECTIVE SIDE RIBS, BARS, AND DECORATIONS.
8. DIMENSIONS SHOWN ARE IN INCHES AND ARE APPROXIMATE ONLY. THEY ARE NOT TO BE USED FOR INSPECTION PURPOSES.
9. ITEMS WHICH ARE DENOTED BY (9), ARE CLASSIFIED AS "AGRICULTURAL IMPLEMENT" IN THE TIRE AND RIM ASSOCIATION INC. YEARBOOK.
10. EXCEPT AS SPECIFIED HEREIN, ALL TIRES MUST CONFORM TO THE INDICATED PROCUREMENT SPECIFICATION EVEN THOUGH THE PARTICULAR TIRE MAY NOT BE SHOWN THEREIN.
11. THE TIRE PART NUMBER CONSISTS OF THE MILITARY STANDARD NUMBER AND THE MS DASH NUMBER. EXAMPLE: MS 35389-1.
12. FOR LIMITED STANDARD ITEMS REQUIRED TO SUPPORT IN-SERVICE MATERIEL, REFER TO PAGES 6 AND 7.
13. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.
14. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER THE PROCUREMENT DOCUMENTS REFERENCED HEREIN.

(E) CANCELLED AFTER 5 JANUARY 1973
USE LATEST PROCUREMENT SPECIFICATION

REVIEW ACTIVITIES: ARMY-ME

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 28 DECEMBER 1955 REVISED (E) 5 JANUARY 1973

P.A. ARMY-AT Other Cust Navy – YD AF – 84	TITLE TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT	MILITARY STANDARD MS 35389
PROCUREMENT SPECIFICATION ZZ-T-1083, ZZ-T-410	SUPERSEDES:	SHEET 1 OF 7

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	4.80/4.00-7	4.80/4.00-7	4.80/4.00-8	4.80/4.00-8	4.80/4.00-8
PLY RATING	4	4	2	4	6
TYPE CLASSIFICATION (2)	IND. STD. SD.	IND. STD. SD.	IND. STD. SD.	IND. STD. SD.	IND. STD. SD.
TREAD TYPE	REGULAR	RIBBED	REGULAR	RIBBED	REGULAR
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS. MAX. (4)	740	740	515	810	1040
INFLATION PRESSURE, PSI	65	65	30	65	100
TUBE USED, MS DASH NO. (5)	-49	-49	-50	-50	-50
MEASURING RIM (6)	2.75	2.75	2.50C	2.50C	2.50C
TIRE SECTION, INCHES (7)	4.30	4.30	4.20	4.20	4.20
DIAMETER, INCHES, MAX.	15.0	15.0	16.9	16.9	16.9
APPROX. LOADED RADIUS	6.7	6.7	7.4	7.6	7.6
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-2	-80	-3	-82	-4
FIIN	050-9630	278-0880	262-8754	528-7593	050-9730

SIZE DESIGNATION	3.40/3.00-7	3.40/300-7	4.10/3.50-6	4.80/4.00-4	4.80/4.00-4
PLY RATING	4	4	4	4	4
TYPE CLASSIFICATION (2)	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.
TREAD TYPE	REGULAR	RIBBED	REGULAR	REGULAR	RIBBED
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD LBS, MAX, (4)	515	515	535	545	545
INFLATION PRESSURE, PSI	90	90	75	65	65
TUBE USED, MS DASH NO. (5)	-112	-112	-48	-109	-109
MEASURING RIM (6)	2.10	2.10	2.45	2.50 C	2.50 C
TIRE SECTION, INCHES (7)	3.15	3.15	3.65	4.20	4.20
DIAMETER, INCHES, MAX.	12.8	12.8	12.7	12.0	12.0
APPROX. LOADED RADIUS	5.9	5.9	5.9	5.6	5.6
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-28	-79	-1	-25	-78
FIIN	204-2263	264-6913	050-9560	050-9430	555-6184

SIZE DESIGNATION	4.80/4.00-9	4.80/400-12	5.30/4.50-7	5.30/4.50-7	5.30/4.50-12
PLY RATING	4	4	4	4	4
TYPE CLASSIFICATION (2)	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST SD.	IND. ST. SD.
TREAD TYPE	RIBBED	REGULAR	REGULAR	RIBBED	RIBBED
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS. MAX. (4)	875	1070	815	815	1160
INFLATION PRESSURE, PSI	65	65	55	55	55
TUBE USED, MS NO. (5)	-116	-51	-115	-115	-119
MEASURING RIM (6)	2.50 C	3.00D	2.75	2.75	3.00D
TIRE SECTION, INCHES (7)	4.20	4.40	4.65	4.65	4.75
DIAMETER INCHES, MAX.	17.9	20.9	16.0	16.0	21.9
APPROX. LOADED RADIUS	8.3	9.6	7.2	7.2	9.9
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-83	-5	-31	-81	-87
FIIN	989-1769	051-0120	050-9650	278-0882	278-0883

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

REVIEW ACTIVITIES: ARMY-ME

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AF-84	TITLE TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE TRACTOR REAR AND TRACTOR FRONT	MILITARY STANDARD MS 35389
PROCUREMENT SPECIFICATION ZZ-T-1083, ZZ-T-410	SUPERSEDES:	SHEET 2

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-03-23T17:22Z
Check the source to verify that this is the current version before use.

SIZE DESIGNATION	6.90/6.00-9	6.90/6.00-9	6.90/6.00-9	6.90/6.00-9	6.50-10
PLY RATING	4	6	8	10	6
TYPE CLASSIFICATION (2)	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS. MAX. (4)	1290	1600	1865	2050	1785
INFLATION PRESSURE, PSI	45	65	85	100	60
TUBE USED, MS DASH NO (5)	-52	-52	-52	-52	-117
MEASURING RIM (6)	4.00 E	4.00 E	4.00 E	4.00 E	5.00 F
TIRE SECTION, INCHES (7)	6.25	6.25	6.25	6.25	7.00
DIAMETER, INCHES, MAX.	21.8	21.8	21.8	21.8	23.8
APPROX. LOADED RADIUS	9.8	9.8	10.1	10.0	10.7
PROCUREMENT SPEC (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-72	-6	-84	-7	-33
FIIN	262-8760	050-9840	050-9870	050-9880	350-9965

SIZE DESIGNATION	6.50-10	6.50-10	7.50-10	7.50-10	7.50-10
PLY RATING	6	10	6	10	10
TYPE CLASSIFICATION (2)	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.	IND. ST. SD.
TREAD TYPE	RIBBED	REGULAR	RIBBED	REGULAR	RIBBED
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS. MAX. (4)	1785	2410	2100	2860	2860
INFLATION PRESSURE, PSI	60	100	50	85	85
TUBE USED, MS DASH NO. (5)	-117	-117	-53	-53	-53
MEASURING RIM (6)	5.00 F	5.00 F	5.50 F	5.50F	5.50F
TIRE SECTION, INCHES (7)	7.00	7.00	8.00	8.00	8.00
DIAMETER, INCHES, MAX.	23.8	23.8	25.9	25.9	25.9
APPROX. LOADED RADIUS	10.7	10.7	14.4	11.4	11.4
PROCUREMENT SPEC (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-85	-34	-36	-86	-8
FIIN	555-6198	051-0210	051-0020	269-7524	051-0050

SIZE DESIGNATION	9.00-10	7.00-12	7.00-15	7.50-16	8.3/8-24
PLY RATING	10	12	12	6	4
TYPE CLASSIFICATION (2)	IND ST SD	IND ST SD	IND ST SD	TR REAR (9)	TR REAR
TREAD TYPE	REGULAR	REGULAR	REGULAR	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	NYLON	RAYON	RAYON
RATED LOAD, LBS. MAX. (4)	3580	3280	3780	1970	1370
INFLATION PRESSURE, PSI	75	100	100	32	22
TUBE USED, MS NO. (5)	-54	-159	-157	-164	-61
MEASURING RIM (6)	6.00F	5.00S	5.50	5.50F	W-7
TIRE SECTION, INCHES (7)	9.20	7.57	7.7	8.00	8.30
DIAMETER, INCHES, MAX.	27.3	27.3	28.6	32.0	39.7
APPROX. LOADED RADIUS	11.6	12.4	13.1	14.3	18.2
PROCUREMENT SPEC (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-9	-88	-110	-89	-10
FIIN	051-0060	528-9640	555-5748	204-2075	275-8009

REVIEW ACTIVITIES: ARMY - ME

APPROVED 26 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT
Other Cust
NAVY-YD
AF-84

PROCUREMENT SPECIFICATION
ZZ-T-1083, ZZ-T-410

TITLE
TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT

SUPERSEDES:

MILITARY STANDARD
MS 35389

SHEET 3

DD FORM 1 SEP 57 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	9.5/9-24	9.5/9-24	9.5/9-38	11.2/10-24	12.4/11-24
PLY RATING	4	8	4	6	4
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR REAR	TR REAR
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS MAX (4)	1535	2445	1900	2320	1935
INFLATION PRESSURE PSI	18	40	18	26	14
TUBE USED MS DASH NO. (5)	-62	-62	-70	-63	-64
MEASURING RIM (6)	W-8	W-8	W-8	W-10	W-11
TIRE SECTION INCHES (7)	9.50	9.50	9.50	11.20	12.40
DIAMETER, INCHES, MAX.	41.8	41.8	55.9	44.0	46.2
APPROX. LOADED RADIUS	19.0	19.2	26.0	19.9	20.8
PROCUREMENT SPEC (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-11	-12	-21	-13	-14
FIIN	141-8708	269-9521	269-9581	262-8663	269-7750

SIZE DESIGNATION	12.4/11-24	12.4/11-28	12.4/11-38	13.6/12-38	16.9/14-30
PLY RATING	8	4	6	6	6
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR REAR	TR REAR
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD LBS MAX (4)	3020	2070	3110	3470	3920
INFLATION PRESSURE, PSI	30	14	22	20	16
TUBE USED, MS DASH NO. (5)	-64	-68	-72	-73	-69
MEASURING RIM (6)	W-11	W-11	W-11, DW-11	W-12	W-15L
TIRE SECTION, INCHES (7)	12.40	12.40	12.40	13.60	16.90
DIAMETER, INCHES, MAX.	46.2	50.3	60.4	62.5	59.3
APPROX. LOAD RADIUS	20.8	22.7	27.7	28.6	26.0
PROCUREMENT SPEC. (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-15	-19	-23	-24	-20
FIIN	262-8802	269-9514	269-9566	593-4340	262-8661

SIZE DESIGNATION	9.00-10	4.00-15	5.00-15	5.90-15	6.00-16
PLY RATING	8	4	4	4	6
TYPE CLASSIFICATION (2)	TR FRONT	TR FRONT(9)	TR FRONT(9)	TR FRONT(9)	TR FRONT(9)
TREAD TYPE	RIBBED	RIBBED	RIBBED	RIBBED	RIBBED
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS MAX (4)	1715	620	755	1040	1260
INFLATION PRESSURE, PSI	44	44	36	24	48
TUBE USED, MS DASH NO. (5)	-54	-160	-56	-163	-161
MEASURING RIM (6)	6.00F	3.00D	3.000	4-J	4.00E
TIRE SECTION, INCHES (7)	9.20	4.40	5.10	5.90	6.25
DIAMETER, INCHES, MAX.	28.2	24.00	25.7	26.7	29.1
APPROX. LOADED RADIUS	12.3	11.3	11.9	12.4	13.5
PROCUREMENT SPEC (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-90	-91	-73	-92	-93
FIIN	294-9338	051-0400	294-9293	555-0309	051-1270

REVIEW ACTIVITIES: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.: ARMY-AT Other Cust NAVY-YD AF-84	TITLE TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT	MILITARY STANDARD MS 35389
PROCUREMENT SPECIFICATION ZZ-T-1083, ZZ-T-410	SUPERSEDES:	SHEET 4

DD FORM SEP 67 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	6.50-16	9.00-16	7.50-18	7.50-20	9.00-24
PLY RATING	8	10	6	6	6
TYPE CLASSIFICATION (2)	TR FRONT(9)	TR FRONT(9)	TR FRONT(9)	TR FRONT(9)	TR FRONT(9)
TREAD TYPE	RIBBED	RIBBED	RIBBED	RIBBED	RIBBED
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
RATED LOAD, LBS MAX. (4)	1930	2940	1700	1840	2750
INFLATION PRESSURE, PSI	48	44	36	36	24
TUBE USED, MS DASH NO. (5)	-162	-10	-59	-60	-64
MEASURING RIM (6)	4.50E	6.00F	5.50F	5.50F	W-8
TIRE SECTION, INCHES (7)	6.80	9.3	8.00	8.00	10.70
DIAMETER, INCHES, MAX.	29.5	32.6	34.1	36.60	42.7
APPROX. LOADED RADIUS	13.5	14.6	15.7	17.2	19.1
PROCUREMENT SPEC (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO.	-94	-111	-75	-76	-95
FIIN	141-8313	051-1730	051-3090	051-4200	541-9738

REVIEW ACTIVITIES: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED Ⓔ FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AF-84	TITLE TIRE; PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT	MILITARY STANDARD MS 35389
PROCUREMENT SPECIFICATION ZZ-T-1083, ZZ-T-410	SUPERSEDES:	SHEET 5

DD FORM 1 SEP 57 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	6x2.00	10x2.50	10x2.75	10x3.00	12x3.00
PLY RATING	4	2	2	4	4
TYPE CLASSIFICATION (2)	IND STR SD	IND STR SD	IND STR SD	IND STR SD	IND STR SD
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	TUBELESS	TUBELESS	TUBELESS	TUBELESS	TUBELESS
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-96	-97	-98	-99	-100
FIIN	269-9587	050-7840	262-8820	262-8821	050-7890

SIZE DESIGNATION	16x4.00	8x3.00-4	10x3.50-4	5.70/5.00-4	3.40/3.00-5
PLY RATING	4	4	4	6	4
TYPE CLASSIFICATION (2)	IND STR SD	IND STR SD	IND STR SD	IND STR SD	IND STR SD
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	TUBELESS	-193	-121	-110	-111
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-101	-102	-40	-26	-27
FIIN	262-8801	269-7749	528-9697	269-9560	050-9510

SIZE DESIGNATION	12x4.00-6	14x4.50-6	16x5.00-8	16x5.00-8	4.80/4.00-9
PLY RATING	4	4	4	6	4
TYPE CLASSIFICATION (2)	IND STR SD	IND STR SD	IND STR SD	IND STR SD	IND STR SD
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED MS DASH NO. (5)	-194	-122	-123	-123	-116
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-410
MS DASH NO. (11)	-103	-41	-104	-42	-32
FIIN	141-8341	528-9699	528-9701	528-9702	050-9800

SIZE DESIGNATION	7.50-10	7.50-10	5.30/4.50-12	4.00-18	9.5/9-18
PLY RATING	6	16	4	4	4
TYPE CLASSIFICATION (2)	IND STR SD	IND STR SD	IND STR SD	TR REAR (9)	TR REAR
TREAD TYPE	REGULAR	RIBBED	REGULAR	REGULAR	DIR TRTN
CORD MATERIAL (3)	RAYON	NYLON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	-53	-53	-119	-197	-59
PROCUREMENT SPEC. (10)	ZZ-T-410	ZZ-T-410	ZZ-T-410	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-105	-106	-38	-107	-47
FIIN	278-0874	528-9620	051-0150	294-5440	262-8678

SIZE DESIGNATION	9.5/9-20	9.5/9-24	14.9/13-24	16.9/14-24	18.4/15-24
PLY RATING	8	6	6	8	6
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR REAR	TR REAR
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	-205	-62	-134	-135	-136
PROCUREMENT SPEC. (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-48	-108	-50	-51	-52
FIIN	262-8655	262-8791	269-9561	269-9512	269-9558

ALL ITEMS ON THIS SHEET ARE INACTIVE FOR NEW DESIGN

AUTHORIZED FOR PROCUREMENT ONLY FOR SUPPORT OF IN-SERVICE MATERIEL

REVIEW ACTIVITIES: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT
Other Cust
NAVY-YD
AF-84

TITLE
TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT

MILITARY STANDARD
MS 35389

PROCUREMENT SPECIFICATION
ZZ-T-1083, ZZ-T-410

SUPERSEDES:

SHEET 6

DD FORM SEP 61 672-1 (Coordinating)

Source: https://assist.dla.mil - Downloaded: 2026-04-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	11.1 /10-26	12.4 /11-26	14.9 / 13-28	16.9/14-28	18.4 / 15-28
PLY RATING	4	4	6	6	6
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR REAR	TR REAR
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	-137	-138	-139	-140	-141
PROCUREMENT SPEC. (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-53	-54	-56	-57	-58
FIIN	269-9511	269-9553	269-9515	269-9563	269-9516

SIZE DESIGNATION	9.5/9-32	16.9/14-32	11.2 / 10-34	12.4 /11-36	13.6 / 12-36
PLY RATING	4	8	4	6	6
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR REAR	TR REAR
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	RAYON
TUBE USED, MS DASH NO. (5)	-142	-195	-196	-144	-145
PROCUREMENT SPEC. (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (11)	-59	-70	-109	-61	-62
FIIN	269-9519	269-9576	294-9364	269-9578	269-9579

SIZE DESIGNATION	14.9 /13-26	14.9/13-36	14.9/13-38	6.00-12	
PLY RATING	6	6	6	6	
TYPE CLASSIFICATION (2)	TR REAR	TR REAR	TR REAR	TR FRONT	
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	RIBBED	
CORD MATERIAL (3)	RAYON	RAYON	RAYON	RAYON	
TUBE USED, MS DASH NO. (5)	-235	-146	-236	-130	
PROCUREMENT SPEC. (10)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-410	
MS DASH NO. (11)	-112	-63	-113	-44	
FIIN	294-9422	269-9580	294-9428	051-0180	

REVIEW ACTIVITIES: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

ALL ITEMS ON THIS SHEET ARE INACTIVE FOR NEW DESIGN

AUTHORIZED FOR PROCUREMENT ONLY FOR SUPPORT OF IN-SERVICE MATERIEL

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY AT Other Cust NAVY-YD AF-84	TITLE TIRE, PNEUMATIC: INDUSTRIAL STRAIGHT SIDE, TRACTOR REAR AND TRACTOR FRONT	MILITARY STANDARD MS 35389
PROCUREMENT SPECIFICATION ZZ-T-1083, ZZ-T-410	SUPERSEDES:	SHEET 7

DD FORM 1 SEP 67 672-1 (Copy/Proof)

Source: https://assist.dla.mil — Downloaded: 2026-04-03T17:22Z
Check the source to verify that this is the current version before use.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973 -714-541/3469