

INACTIVE FOR NEW DESIGN
AFTER 15 MAY 1973

USE
MS35764





FED. SUP CLASS
5306

TABLE I

	NOMINAL SIZE	.250			.3125			.375			.4375		
	THREADS PER INCH	20	28		18	24		16	24		14	20	
D	BODY DIAMETER MAX	.250			.3125			.375			.4375		
	BODY DIAMETER MIN	.245			.3065			.369			.4305		
F	ACROSS FLATS MAX	.438			.500			.562			.625		
	ACROSS FLATS MIN	.428			.489			.551			.612		
G	ACROSS CORNERS MAX	.505			.577			.650			.722		
	ACROSS CORNERS MIN	.488			.557			.628			.698		
H	HEAD HEIGHT MAX	.135			.198			.260			.291		
	HEAD HEIGHT MIN	.125			.188			.250			.281		
M	THREAD LENGTH REF	.750			.875			1.000			1.125		
N	UNTHREADED* LENGTH - MAX	.125	.089		.139	.104		.156	.104		.179	.125	

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
.750	CAD PHOS	803 203	1003 603			817 217	1017 617			831 231	1031 631			846 246	1046 646		
.875	CAD PHOS	804 204	1004 604		.125	818 218	1018 618			832 232	1032 632			847 247	1047 647		
1.000	CAD PHOS	805 205	1005 605		.250	819 219	1019 619			833 233	1033 633			848 248	1048 648		
1.250	CAD PHOS	807 207	1007 607	.100	.500	821 221	1021 621		.375	835 235	1035 635		.250	850 250	1050 650		
1.500	CAD PHOS	808 208	1008 608	.350	.750	822 222	1022 622	.208	.625	836 236	1036 636	.062	.500	851 251	1051 651		.375
1.750	CAD PHOS	809 209	1009 609	.600	1.000	823 223	1023 623	.458	.875	837 237	1037 637	.312	.750	852 252	1052 652	.161	.625
2.000	CAD PHOS	810 210	1010 610	.850	1.250	824 224	1024 624	.708	1.125	838 238	1038 638	.562	1.000	853 253	1053 653	.411	.875
2.250	CAD PHOS	811 211	1011 611	1.100	1.500	825 225	1025 625	.958	1.375	839 239	1039 639	.812	1.250	854 254	1054 654	.661	1.125
2.500	CAD PHOS	812 212	1012 612	1.350	1.750	826 226	1026 626	1.208	1.625	840 240	1040 640	1.062	1.500	855 255	1055 655	.911	1.375
2.750	CAD PHOS	813 213	1013 613	1.600	2.000	827 227	1027 627	1.458	1.875	841 241	1041 641	1.312	1.750	856 256	1056 656	1.161	1.625
3.000	CAD PHOS	814 214	1014 614	1.850	2.250	828 228	1028 628	1.708	2.125	842 242	1042 642	1.562	2.000	857 257	1057 657	1.411	1.875
3.250	CAD PHOS													858 258	1058 658	1.661	2.125
3.500	CAD PHOS										1044 644	2.062	2.500	859 259	1059 659	1.911	2.375
3.750	CAD PHOS													860 260	1060 660	2.161	2.625
4.000	CAD PHOS													861 261	1061 661	2.411	2.875

*See note 6.

INACTIVE

(E) ENTIRE STANDARD REVISED

REVIEWER: AT, AV, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) 29 DEC 1975

...his military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC
Other Cust 82

TITLE
BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 5, UNC-2A AND UNF-2A

MILITARY STANDARD
MS35763

PROCUREMENT SPECIFICATION
MIL-B-45912

SUPERSEDES BAQX1 thru BAQX1.5 and BARX1 thru BARX2

SHEET 1 OF 5

DD FORM SEP 67 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:27Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5306

TABLE I - Continued

NOMINAL SIZE		.500			.5625			.625			.750		
THREADS PER INCH		13	20		12	18		11	18		10	16	
D BODY DIAMETER	MAX	.500			.5625			.625			.750		
	MIN	.493			.5545			.617			.741		
F ACROSS FLATS	MAX	.750			.812			.875			1.000		
	MIN	.736			.798			.860			.983		
G ACROSS CORNERS	MAX	.866			.938			1.010			1.155		
	MIN	.840			.910			.980			1.121		
H HEAD HEIGHT	MAX	.327			.390			.390			.458		
	MIN	.312			.375			.375			.438		
M THREAD LENGTH	REF	1.250			1.375			1.500			1.750		
N UNTHREADED* LENGTH	MAX	.192	.125		.208	.139		.227	.139		.250	.156	

L LENGTH	FINISH	DASH NO		BODY LGT MIN	GRIP LGT MAX	DASH NO		BODY LGT MIN	GRIP LGT MAX	DASH NO		BODY LGT MIN	GRIP LGT MAX	DASH NO		BODY LGT MIN	GRIP LGT MAX
.750	CAD	864	1064			882	1082										
	PHOS	264	664			282	682										
.875	CAD	865	1065			883	1083										
	PHOS	265	665			283	683										
1.000	CAD	866	1066			884	1084			900	1100				1116		
	PHOS	266	666			284	684			300	700				716		
1.250	CAD	868	1068			886	1086			902	1102			918	1118		
	PHOS	268	668			286	686			302	702			318	718		
1.500	CAD	869	1069		.250	887	1087			903	1103			919	1119		
	PHOS	269	669			287	687			303	703			319	719		
1.750	CAD	870	1070	.019	.500	888	1088		.375	904	1104		.250	920	1120		
	PHOS	270	670			288	688			304	704			320	720		
2.000	CAD	871	1071	.269	.750	889	1089		.625	905	1105		.500	921	1121		.250
	PHOS	271	671			289	689			305	705			321	721		
2.250	CAD	872	1072	.519	1.000	890	1090	.125	.875	906	1106		.750	922	1122		.500
	PHOS	272	672			290	690			306	706			322	722		
2.500	CAD	873	1073	.769	1.250	891	1091	.375	1.125	907	1107	.227	1.000	923	1123		.750
	PHOS	273	673			291	691			307	707			323	723		
2.750	CAD	874	1074	1.019	1.500	892	1092	.625	1.375	908	1108	.477	1.250	924	1124	.200	1.000
	PHOS	274	674			292	692			308	708			324	724		
3.000	CAD	875	1075	1.269	1.750	893	1093	.875	1.625	909	1109	.727	1.500	925	1125	.450	1.250
	PHOS	275	675			293	693			309	709			325	725		
3.250	CAD	876	1076	1.519	2.000	894	1094	1.125	1.875	910	1110	.977	1.750	926	1126	.700	1.500
	PHOS	276	676			294	694			310	710			326	726		
3.500	CAD	877	1077	1.769	2.250	895	1095	1.375	2.125	911	1111	1.227	2.000	927	1127	.950	1.750
	PHOS	277	677			295	695			311	711			327	727		
3.750	CAD	878	1078	2.019	2.500	896	1096	1.625	2.375	912	1112	1.447	2.250	928	1128	1.200	2.000
	PHOS	278	678			296	696			312	712			328	728		
4.000	CAD	879	1079	2.269	2.750	897	1097	1.875	2.625	913	1113	1.727	2.500	929	1129	1.450	2.250
	PHOS	279	679			297	697			313	713			329	729		
4.500	CAD									914	1114	2.227	3.000	930	1130	1.950	2.750
	PHOS									314	714			330	730		

* See note 6

INACTIVE (SEE SHEET 1)

REVIEWER: AT, AV, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC	TITLE	MILITARY STANDARD
Other Cust 82	BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 5, UNC-2A AND UNF-2A	MS35763
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES: BAQX1 thru BAQX1.5 and BARX1 thru BARX2	SHEET 2 OF 5

DD FORM 1 SEP 67 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:27Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5306

TABLE I - Continued

NOMINAL SIZE		.875			1.000			1.250		
THREADS PER INCH		9	14		8	12		7	12	
D BODY DIAMETER	MAX	.875			1.000			1.250		
	MIN	.866			.990			1.239		
F ACROSS FLATS	MAX	1.125			1.312			1.688		
	MIN	1.106			1.292			1.663		
G ACROSS CORNERS	MAX	1.299			1.516			1.949		
	MIN	1.261			1.473			1.896		
H HEAD HEIGHT	MAX	.520			.582			.697		
	MIN	.500			.562			.677		
M THREAD LENGTH REF		2.000			2.250			2.750		
N UNTHREADED LENGTH	MAX	.278	.179		.312	.208		.357	.208	

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
1.250	CAD PHOS		1133 733				1148 748						
1.500	CAD PHOS	934 334	1134 734								1177 777		
1.750	CAD PHOS	935 335	1135 735			950 350	1150 750						
2.000	CAD PHOS	936 336	1136 736			951 351	1151 751			979 379	1179 779		
2.250	CAD PHOS	937 337	1137 737			952 352	1152 752			980 380	1180 780		
2.500	CAD PHOS	938 338	1138 738		.500	953 353	1153 753			981 381	1181 781		
2.750	CAD PHOS	939 339	1139 739		.750	954 354	1154 754		.500	982 382	1182 782		
3.000	CAD PHOS	940 340	1140 740	.167	1.000	955 355	1155 755		.750	983 383	1183 783		
3.250	CAD PHOS	941 341	1141 741	.417	1.250	956 356	1156 756	.125	1.000	984 384	1184 784		.500
3.500	CAD PHOS	942 342	1142 742	.667	1.500	957 357	1157 757	.375	1.250	985 385	1185 785		.750
3.750	CAD PHOS	943 343	1143 743	.917	1.750	958 358	1158 758	.625	1.500	986 386	1186 386	.071	1.000
4.000	CAD PHOS	944 344	1144 744	1.167	2.000	959 359	1159 759	.875	1.750	987 387	1187 787	.321	1.250
4.500	CAD PHOS	945 345	1145 745	1.667	2.500	960 360	1160 760	1.375	2.250	988 388	1188 788	.821	1.750
5.000	CAD PHOS	946 346	1146 746	2.167	3.000	961 361	1161 761	1.875	2.750	989 389	1189 789	1.321	2.250

* See note 6.

TABLE II

Length Tolerance

NOMINAL SIZE	.250 .3125 .375	.4375 .500	.5625 .625 .750	.875 1.000	1.250
LENGTH	TOLERANCE (+.000)				
Thru 1.000	-.030	-.030	-.030	-.100	-.120
Over 1.000 thru 2.500	-.040	-.060	-.080	-.140	-.160
Over 2.500 thru 4.000	-.060	-.080	-.100	-.160	-.180
Over 4.000					

INACTIVE (SEE SHEET 1)

REVIEWER: AT, AV, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1

Military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC Other Cust 82	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 5, UNC-2A AND UNF-2A	MILITARY STANDARD MS35763
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES BAQX1 thru BAQX1.5 and BARX1 thru BARX2	SHEET 3 OF 5

DD FORM SEP 67 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:27Z
Check the source to verify that this is the current version before use.

NOTES:
1. MATERIAL: Steel, SAE Grade 5 in accordance with procurement specification.
2. PROTECTIVE COATING: Cadmium plated in accordance with QQ-P-416, Type II, Class 2. Phosphate coated in accordance with MIL-P-16232, Type 2, Class 2.
3. THREADS: Threads shall be in accordance with Screw Thread Standards for Federal Services, Handbook H28.
4. DIMENSIONS: All dimensions are in inches.
5. HEAD DIMENSIONS: For head dimensions see procurement specification.
*6. UNTHREADED LENGTH: Bolts too short for full thread length shall have threads extending over the full length. The distance from the underside of the head to the first complete (full form) thread, as measured with a ring thread gage, shall not exceed the maximum unthreaded length "N".
7. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS35763-203.
8. Referenced documents shall be of the issue in effect on date of invitations for bid.
9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
10. This bolt is covered by U.S. Patent Number 3342236 which expires 19 September 1984. The Government does not have a -royalty free license under this patent. This bolt is known as a "Place Bolt" under this patent.

TABLE III

GRADE 5-REFERENCE INFORMATION ONLY				
NOMINAL SIZE	THREADS PER INCH	PROOF LOAD LBS (MIN)	RECOMMENDED AXIAL LOAD (LBS)	*RECOMMENDED TIGHTENING TORQUE (FT-LBS)
.250	20 28	2700 3100	2025 2325	6.8 9
.3125	18 24	4450 4950	3338 3713	15.8 19.5
.375	16 24	6600 7450	4950 5588	27 37.5
.4375	14 20	9050 10100	6788 7575	50 59.5
.500	13 20	12050 13600	9038 10163	73 87.5
.5625	12 18	15450 17250	11588 12938	97 121
.625	11 18	19200 21750	14400 16313	150 187.5
.750	10 16	28400 31700	21300 23775	265 325.5
.875	9 14	36050 39700	27038 29775	383 449
1.000	8 12	47250 51700	35438 38775	589 690
1.250	7 12	71700 79400	53775 59475	1125 1369

INACTIVE (SEE SHEET 1)

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1.

REVIEWER: AT, AV, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC Other Cust 82	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 5, UNC-2A AND UNF-2A	MILITARY STANDARD MS35763
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES: BAQX1 thru BAQX1.5 and BARX1 thru BARX2	SHEET 4 OF 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:27Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5306

TABLE IV - INTERCHANGEABILITY TABLE

Cadmium or zinc plated bolts covered by the dash numbers given in the original issue of this standard are canceled after 13 Sep 1966. The canceled bolts should be used for maintenance purposes until existing stock is depleted. Use only the superseding bolts for new design and replacement. Replacement shall be in accordance with this table.

DASH NUMBERS

CANCELLED MS35763	NEW MS35763	CANCELLED MS35763	NEW MS35763	CANCELLED MS35763	NEW MS35763	CANCELLED MS35763	NEW MS35763	CANCELLED MS35763	NEW MS35763
3	803	77	877	152	952	452	1052	523	1123
4	804	78	878	153	953	453	1053	524	1124
5	805	79	879	154	954	454	1054	525	1125
7	807	82	882	155	955	455	1055	526	1126
8	808	83	883	156	956	456	1056	527	1127
9	809	84	884	157	957	457	1057	528	1128
10	810	86	886	158	958	458	1058	529	1129
11	811	87	887	159	959	459	1059	530	1130
12	812	88	888	160	960	460	1060	533	1133
13	813	89	889	161	961	461	1061	534	1134
14	814	90	890	179	979	464	1064	535	1135
17	817	91	891	180	980	465	1065	536	1136
18	818	92	892	181	981	466	1066	537	1137
19	819	93	893	182	982	468	1068	538	1138
21	821	94	894	183	983	469	1069	539	1139
22	822	95	895	184	984	470	1070	540	1140
23	823	96	896	185	985	471	1071	541	1141
24	824	97	897	186	986	472	1072	542	1142
25	825	100	900	187	987	473	1073	543	1143
26	826	102	902	188	988	474	1074	544	1144
27	827	103	903	189	989	475	1075	545	1145
28	828	104	904	403	1003	476	1076	546	1146
31	831	105	905	404	1004	477	1077	548	1148
32	832	106	906	405	1005	478	1078	550	1150
33	833	107	907	407	1007	479	1079	551	1151
35	835	108	908	408	1008	482	1082	552	1152
36	836	109	909	409	1009	483	1083	553	1153
37	837	110	910	410	1010	484	1084	554	1154
38	838	111	911	411	1011	486	1086	555	1155
39	839	112	912	412	1012	487	1087	556	1156
40	840	113	913	413	1013	488	1088	557	1157
41	841	114	914	414	1014	489	1089	558	1158
42	842	118	918	417	1017	490	1090	559	1159
46	846	119	919	418	1018	491	1091	560	1160
47	847	120	920	419	1019	492	1092	561	1161
48	848	121	921	421	1021	493	1093	577	1177
50	850	122	922	422	1022	494	1094	579	1179
51	851	123	923	423	1023	495	1095	580	1180
52	852	124	924	424	1024	496	1096	581	1181
53	853	125	925	425	1025	497	1097	582	1182
54	854	126	926	426	1026	500	1100	583	1183
55	855	127	927	427	1027	502	1102	584	1184
56	856	128	928	428	1028	503	1103	585	1185
57	857	129	929	431	1031	504	1104	586	1186
58	858	130	930	432	1032	505	1105	587	1187
59	859	134	934	433	1033	506	1106	588	1188
60	860	135	935	435	1035	507	1107	589	1189
61	861	136	936	436	1036	508	1108		
64	864	137	937	437	1037	509	1109		
65	865	138	938	438	1038	510	1110		
66	866	139	939	439	1039	511	1111		
68	868	140	940	440	1040	512	1112		
69	869	141	941	441	1041	513	1113		
70	870	142	942	442	1042	514	1114		
71	871	143	943	444	1044	516	1116		
72	872	144	944	446	1046	518	1118		
73	873	145	945	447	1047	519	1119		
74	874	146	946	448	1048	520	1120		
75	875	150	950	450	1050	521	1121		
76	876	151	951	451	1051	522	1122		

INACTIVE (SEE SHEET 1)

REVIEWER: AT, AV, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	NC
Other Cust	82

TITLE: BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 5, UNC-2A AND UNF-2A

MILITARY STANDARD
MS35763

PROCUREMENT SPECIFICATION: MIL-B-45912

SUPERSEDES: BAQX1 thru BAQX1.5 and BARX1 thru BARX2

SHEET 5 OF 5

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:27Z
Check the source to verify that this is the current version before use.