FED. SUP CLASS 5305




TABLE I. DASH NUMBERS AND DIMENSIONS.

NOMINAL SIZE		1/4 .2500	5/16 .3125	3/8 .3750	7/16 .4375	1/2 .5000	9/16 .5625	5/8 .6250	3/4 .7500	7/8 .8750
A THREADS PER INCH		20UNC-2A	18UNC-2A	16UNC-2A	14UNC-2A	13UNC-2A	12UNC-2A	11UNC-2A	10UNC-2A	9UNC-2A
ØD BODY DIAMETER	MAX	.2500	.3125	.3750	.4375	.5000	.5625	.6250	.7500	.8750
	MIN	.2450	.3065	.3690	.4305	.4930	.5545	.6170	.7410	.8650
F WIDTH ACROSS FLATS	MAX	.4375	.5000	.5625	.6250	.7500	.8125	.9375	1.1250	1.3125
	MIN	.4260	.4890	.5510	.6120	.7360	.7980	.9220	1.1000	1.2850
G WIDTH ACROSS CORNERS	MAX	.505	.577	.650	.722	.866	.938	1.083	1.299	1.516
	MIN	.488	.557	.628	.698	.840	.910	1.051	1.254	1.465
H HEAD HEIGHT	MAX	.163	.211	.243	.291	.323	.371	.403	.483	.563
	MIN	.150	.195	.226	.272	.302	.348	.378	.455	.531
R RADIUS	MAX	.025	.025	.025	.025	.025	.045	.045	.045	.065
	MIN	.015	.015	.015	.015	.015	.020	.020	.020	.040
1/ MIN TENSILE STRENGTH - LBS		4,750	7,850	11,600	15,900	21,300	27,300	33,900	50,100	69,300

L LENGTH	TOLERANCE: SIZE .750 AND UNDER	TOLERANCE: SIZE .875	DASH NO	DASH NO	DASH NO	DASH NO 2/	DASH NO	DASH NO 2/	DASH NO	DASH NO	DASH NO 2/
.375			1	27	53						
.438			2	28	54	79					
.500			3	29	55	80	104				
.562	+0	+0	4	30	56	81	105	130			
.625	-.031	-.062	5	31	57	82	106	131	155		
.750			6	32	58	83	107	132	156	179	
.875			7	33	59	84	108	133	157	180	202
1.000			8	34	60	85	109	134	158	181	203
1.125			9	35	61	86	110	135	159	182	204
1.250			10	36	62	87	111	136	160	183	205
1.375	+0	+0	11	37	63	88	112	137	161	184	206
1.500	-.062	-.125	12	38	64	89	113	138	162	185	207
1.750			13	39	65	90	114	139	163	186	208
2.000			14	40	66	91	115	140	164	187	209
2.250			15	41	67	92	116	141	165	188	210
2.500			16	42	68	93	117	142	166	189	211
2.750			17	43	69	94	118	143	167	190	212
3.000			18	44	70	95	119	144	168	191	213
3.250		+0	19	45	71	96	120	145	169	192	214
3.500	+0	-.188	20	46	72	97	121	146	170	193	215
3.750	-.094		21	47	73	98	122	147	171	194	216
4.000			22	48	74	99	123	148	172	195	217
4.250			23	49	75	100	124	149	173	196	218
4.500			24	50	76	101	125	150	174	197	219
4.750			25	51	77	102	126	151	175	198	220
5.000			26	52	78	103	127	152	176	199	221
5.500							128	153	177	200	222
6.000							129	154	178	201	223

1/ SEE NOTE 2
2/ INACTIVE FOR NEW DESIGN AFTER 21 JUN 76

(F) DENOTES CHANGES

P.A. AR	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cost 99		SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), ALLOY STEEL, GRADE 8, CADMIUM PLATED, PLAIN AND SELF LOCKING, UNC-2A	MS90728
PROCUREMENT SPECIFICATION ANSI B18.2.1-1981	SUPERSEDES MS35301, MS35303, MS35305, BCVX7 IN PART, BUBX14, 14.1, 15, 15.1, 16 AND 16.1		PAGE 1 OF 3

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5305-1588

USER ACTIVITIES: ARMY-ME NAVY-MC,OS,YD

REVIEWER ACTIVITIES: ARMY-AT,AV,MI AIR FORCE-82 NSA-NS DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

APPROVED 7 MAY 63 REVISED (A) 14 OCT 68 (B) 1 MAY 69 (C) 22 OCT 70 (D) 21 JUNE 76 (E) 20 DEC 83 (F) 30 OCT 84

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:41Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5305

TABLE I. DASH NUMBERS AND DIMENSIONS.

NOMINAL SIZE		1 1.000	1-1/8 1.125	1-1/4 1.250	1-3/8 1.375	1-1/2 1.500	1-3/4 1.750	2 2.000	2-1/4 2.250	2-1/2 2.500
B THREADS PER INCH		8UNC-2A	7UNC-2A	7UNC-2A	6UNC-2A	6UNC-2A	5UNC-2A	4-1/2UNC-2A	4-1/2UNC-2A	4UNC-2A
ØD BODY DIAMETER	MAX	1.0000	1.1250	1.2500	1.3750	1.5000	1.7500	2.0000	2.2500	2.5000
	MIN	.9900	1.1140	1.2390	1.3630	1.4880	1.7380	1.9880	2.2390	2.4880
F WIDTH ACROSS FLATS	MAX	1.5000	1.6875	1.8750	2.0625	2.2500	2.6250	3.0000	3.3750	3.7500
	MIN	1.4690	1.6310	1.8120	1.9940	2.1750	2.5590	2.9000	3.2620	3.6250
G WIDTH ACROSS CORNERS	MAX	1.732	1.949	2.165	2.382	2.598	3.031	3.464	3.897	4.330
	MIN	1.675	1.859	2.066	2.273	2.480	2.893	3.306	3.719	4.133
H HEAD HEIGHT	MAX	.627	.718	.813	.878	.974	1.134	1.263	1.423	1.583
	MIN	.591	.658	.749	.810	.902	1.054	1.175	1.327	1.479
R RADIUS	MAX	.095	.095	.095	.095	.095	.095	.095	.095	.095
	MIN	.060	.060	.060	.060	.060	.060	.060	.060	.060
1/ MIN TENSILE STRENGTH - LBS		90,900	114,600	145,470	173,200	210,900	277,900	299,750	399,700	479,850

L LENGTH	TOLERANCE	DASH NO	DASH NO	DASH NO	DASH NO	DASH NO	DASH NO	DASH NO	DASH NO	DASH NO
1.000	+0 -.062	224								
1.125	+0 -.125	225	245							
1.250		226	246	265						
1.375		227	247	266	284					
1.500		228	248	267	285	302				
1.750		229	249	268	286	303	319			
2.000		230	250	269	287	304	320			
2.250	+0 -.188	231	251	270	288	305	321	335		
2.500		232	252	271	289	306	322	336		
2.750		233	253	272	290	307	323	337	349	361
3.000		234	254	273	291	308	324	338	350	362
3.250		235	255	274	292	309	325	339	351	363
3.500		236	256	275	293	310	326	340	352	364
3.750		237	257	276	294	311	327	341	353	365
4.000		238	258	277	295	312	328	342	354	366
4.250		239	259	278	296	313	329	343	355	367
4.500		240	260	279	297	314	330	344	356	368
4.750		241	261	280	298	315	331	345	357	369
5.000		242	262	281	299	316	332	346	358	370
5.500		243	263	282	300	317	333	347	359	371
6.000		244	264	283	301	318	334	348	360	372

1/ SEE NOTE 2

REQUIREMENTS:

1. MATERIAL: ALLOY STEEL, SAE GRADE 8 IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
2. PROTECTIVE COATING: CADMIUM PLATED IN ACCORDANCE WITH QQ-P-416, TYPE II, CLASS 3.
3. THREADS: THREADS SHALL BE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
4. IDENTIFICATION MARKING: HEADS SHALL BE MARKED IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
5. SELF-LOCKING ELEMENT.
   (a) THE SELF-LOCKING ELEMENT SHALL BE A PATCH TYPE OR LONGITUDINAL STRIP IN ACCORDANCE WITH MIL-F-18240.
   (b) FOR "X" AND "Y" DIMENSIONS AND DESIGN AND USAGE LIMITATIONS, SEE MS15981.
   (c) MAXIMUM RING GAGE DIAMETER THAT LOCKING REGION OF SCREW MUST PASS THRU FREELY OR WITH FINGER PRESSURE SHALL BE OF THE NOMINAL SIZE PLUS 0.010.
6. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS SHEET NUMBER PLUS THE DASH NUMBER TAKEN FROM TABLE I OR II AS APPLICABLE. FOR SCREWS WITH SELF-LOCKING ELEMENT ADD THE LETTER "L" AFTER THE DASH NUMBER.

EXAMPLE: MS90728-236
- 236 — DASH NUMBER
- MS90728 — BASIC MS SHEET NUMBER

MS90728-236 INDICATES- SCREW, CAP, HEXAGON HEAD, ALLOY STEEL, SAE GRADE 8, CADMIUM PLATED, NOMINAL SIZE 1.000-8UNC-2A, LENGTH 3.500, NO SELF-LOCKING ELEMENT.

APPROVED 7 MAY 63 REVISED (F) FOR CHANGE SEE PAL

USER ACTIVITIES: ARMY-ME, NAVY-MC,OS,YD

REVIEWER ACTIVITIES: ARMY-AT,AV,MI AIR FORCE-62 NSA-NS DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. AR; Other Coord 99	INTERNATIONAL INTEREST	TITLE: SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), ALLOY STEEL, GRADE 8, CADMIUM PLATED, PLAIN AND SELF LOCKING, UNC-2A	MILITARY STANDARD MS90728
PROCUREMENT SPECIFICATION: ANSI B18.2.1-1981	SUPERSEDES: MS35301, MS35303, MS35305, 8CVX7 IN PART, 8UBX14, 14.1, 15, 15.1, 16 AND 18.1		PAGE 2 OF 3

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5305-1588

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:41Z
Check the source to verify that this is the current version before use.

7. QUALITY ASSURANCE PROVISIONS: QUALITY ASSURANCE PROVISIONS SHALL BE IN ACCORDANCE WITH ANSI B18.18.1M-1982. THREAD INSPECTION METHOD ACCEPTABILITY SHALL BE IN ACCORDANCE WITH FED-STD-H28/20, SYSTEM 21 AND ANSI B18.18.1M-1982, INSPECTION LEVEL B.

8. PACKAGING: PACKAGING SHALL BE IN ACCORDANCE WITH ASTM D3951-82.

(F)9. THREAD LENGTH: MINIMUM THREAD LENGTH SHALL BE TWICE THE DIAMETER PLUS .250 INCH. THE TOLERANCE SHALL BE PLUS .187 INCH OR 2-1/2 THREADS WHICHEVER IS GREATER. ON SCREWS THAT ARE TOO SHORT FOR MINIMUM THREAD LENGTHS, THE DISTANCE FROM THE BEARING SURFACE OF THE HEAD TO THE FIRST COMPLETE THREAD SHALL NOT EXCEED THE LENGTH OF 2-1/2 THREADS FOR SIZES UP TO AND INCLUDING 1 INCH AND 3-1/2 THREADS FOR SIZES LARGER THAN 1 INCH.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.

2. BASED ON MINIMUM ULTIMATE TENSILE STRENGTH OF 150,000 PSI FOR DIAMETERS THRU 1-1/2 INCHES AND 120,000 PSI FOR DIAMETERS OVER 1-1/2 INCHES. TENSILE STRENGTHS ARE CALCULATED BY THE STRESS AREAS INDICATED IN FED-STD-H28, APPENDIX A5, 3. STRENGTH FACTORS.

3. CROSS REFERENCE OF PART NUMBERS: THE SCREWS COVERED BY DASH NUMBERS GIVEN IN MS35301, MS35303 AND MS35305, ARE CANCELLED AFTER THE DATES INDICATED ON THE CANCELLED DOCUMENTS. USE DASH NUMBERS USED IN THIS STANDARD. THE CANCELLED SCREWS CANNOT ALWAYS REPLACE THE NEW SCREWS AND SHOULD BE USED UNTIL EXISTING STOCKS ARE DEPLETED. USE ONLY THE NEW SCREWS FOR DESIGN AND REPLACEMENT. DASH NUMBERS REPRESENTING OLD AND NEW SCREWS ARE IDENTICAL, MAKING IT UNNECESSARY TO PREPARE AN INTERCHANGEABILITY TABLE.

4. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THAT REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

5. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

USER ACTIVITIES:
ARMY-ME
NAVY-MC,OS,YD

REVIEWER ACTIVITIES:
ARMY-AT,AV,MI
AIR FORCE-82
NSA-NS
DLA-IS

APPROVED 7 MAY 63 REVISED (F) FOR CHANGE SEE PAGE 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P. A. AR / Other Govt 99	INTERNATIONAL INTEREST	TITLE: SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), ALLOY STEEL, GRADE 8, CADMIUM PLATED, PLAIN AND SELF LOCKING, UNC-2A	MILITARY STANDARD MS90728
PROCUREMENT SPECIFICATION ANSI B18.2.1-1981	SUPERSEDES: MS35301, MS35303, MS35305, BCVX7 IN PART, BUBX14, 14.1, 15, 15.1, 16 AND 16.1		PAGE 3 OF 3

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5305-1588

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:41Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:41Z
Check the source to verify that this is the current version before use.