INCH-POUND

MIL-DTL-85/3D
27 April 2012
SUPERSEDING
MIL-DTL-85/3C
17 October 2005

DETAIL SPECIFICATION SHEET

WAVEGUIDES, RIGID, RECTANGULAR (MILLIMETER WAVELENGTH)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the waveguide described herein shall consist of this specification sheet and MIL-DTL-85.




FIGURE 1. Waveguide, Rigid, Rectangular (Millimeter Wavelength).

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1 and table I.
Material: See table I and table IV.
Part number: See table I.

NOTES:

1. Engineering information: See table II.
2. Supersession data and cross index: See table III.
3. Typical resistivity and conductivity of materials: See table IV.
4. There shall be no “dog ears” from fabrication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:44Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions.

		Dimensions (inches) 2/									
		Inside			Outside				(max.)	(max.)	
Part 1/ number M85/3-	EIA WR - ##	Width (A)	Height (B)	Toler-ance	Width (C)	Height (D)	Toler-ance	Wall Thickness (nominal)	Outer corner radius	Inner corner radius	(see Table IV) ASTM type material
006-XXX 007-XXX 008-XXX 009-XXX	28	.2800 (7.11)	.1400 (3.56)	± .0015 (.04)	.360 (9.14)	.220 (5.59)	± .002 (.05)	.040 (1.02)	.012 (.30)	.008 (.20)	Coin silver Copper (OFHC) 3/ Bronze (90/10) 6061
010-XXX 011-XXX 012-XXX 013-XXX	22	.2240 (5.69)	.1120 (2.84)	± .0010 (.03)	.304 (7.72)	.192 (4.88)	± .002 (.05)	.040 (1.02)	.010 (.25)	.007 (.18)	Coin silver Copper (OFHC) Bronze (90/10) 6061
014-XXX 015-XXX 016-XXX	19	.1880 (4.78)	.0940 (2.39)	± .0010 (.03)	.268 (6.81)	.174 (4.42)	± .002 (.05)	.040 (1.02)	.009 (.23)	.006 (.15)	Coin silver Copper (OFHC) Bronze (90/10)
017-XXX 018-XXX	15	.1480 (3.76)	.0740 (1.88)	± .0010 (.03)	.228 (5.79)	.154 (3.91)	± .002 (.05)	.040 (1.02)	.008 (.20)	.004 (.11)	Coin silver Copper (OFHC)
020-XXX 021-XXX	12	.1220 (3.10)	.0610 (1.55)	± .0010 (.03)	.202 (5.13)	.141 (3.58)	± .002 (.05)	.040 (1.02)	.007 (.18)	.004 (.11)	Coin silver Copper (OFHC)
023-XXX 024-XXX	10	.1000 (2.54)	.0500 (1.27)	± .0010 (.03)	.180 (4.57)	.130 (3.30)	± .002 (.05)	.040 (1.02)	.007 (.18)	.003 (.08)	Coin silver Copper (OFHC)
026-XXX 027-XXX	08	.0800 (2.03)	.0400 (1.02)	± .0005 (.01)	.1600 (4.06)	.1200 (3.09)	± .0015 (.04)	.040 (1.02)	.006 (.15)	.002 (.05)	Coin silver Copper (OFHC)
029-XXX 030-XXX	06	.0650 (1.65)	.0325 (.83)	± .0005 (.01)	.1450 (3.68)	.1125 (2.86)	± .0015 (.04)	.040 (1.02)	.005 (.13)	.002 (.05)	Coin silver Copper (OFHC)
032-XXX 033-XXX	05	.0510 (1.30)	.0255 (.65)	± .0005 (.01)	.1310 (3.33)	.1055 (2.68)	± .0015 (.04)	.040 (1.02)	.005 (.13)	.002 (.05)	Coin silver Copper (OFHC)
035-XXX 036-XXX	04	.0430 (1.09)	.0215 (.55)	± .0005 (.01)	.1230 (3.12)	.1015 (2.58)	± .0015 (.04)	.040 (1.02)	.004 (.11)	.001 (.03)	Coin silver Copper (OFHC)
038-XXX 039-XXX	03	.0340 (.86)	.0170 (.43)	± .0005 (.01)	.1140 (2.90)	.0970 (2.46)	± .0015 (.04)	.040 (1.02)	.004 (.11)	.001 (.03)	Coin silver Copper (OFHC)

1/ The complete part number shall be the number shown and a three-digit number indicating length in inches (for example, M85/3-006-096). Part numbers M85/3-001 through -005, 019, 022, 025, 028, 031, 034, 037, 040 through 055 have been deleted. Material type was changed for part numbers 008, 012, 016 because previous listed composition was never made.

2/ Metric equivalents (to the nearest .01 mm) are given for general information only. Millimeters are in parentheses.

3/ Copper (OFHC) is oxygen-free high conductivity copper shall conform to ASTM-B187/B187M for bar and ASTM-B152/B152M for plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:44Z
Check the source to verify that this is the current version before use.

TABLE II. Performance characteristics.

Part number M85/3-	frequency range TE_{10} mode (GHz)	Cutoff for TE_{10} mode (GHz)	Theoretical attenuation (lowest to highest frequency) (dB/100 ft) 1/	Theoretical peak power rating (lowest to highest frequency) (kilowatts) 2/	Theoretical CW power rating (lowest to highest frequency) (watts) 3/
006-XXX	26.50 - 40.00	21.10	24.55 - 16.80	96.0 - 146	103.1 - 150.1
007-XXX			23.02 - 15.77		109.7 - 160.1
008-XXX			---		---
009-XXX			34.46 - 23.59		73.27 - 107.0
010-XXX	33.00 - 50.00	26.350	34.57 - 23.50	64.4 - 97.0	64.73 - 95.30
011-XXX			32.44 - 22.05		68.89 - 101.4
012-XXX			---		---
013-XXX			48.53 - 32.99		46.05 - 67.74
014-XXX	40.00 - 60.00	31.41	42.39 - 30.46	48 - 70	48.30 - 67.21
015-XXX			39.81 - 28.60		51.32 - 71.43
016-XXX			---		---
017-XXX	50.00 - 75.00	39.90	64.23 - 43.89	30 - 40	28.46 - 41.44
018-XXX			60.25 - 41.17		30.27 - 44.30
020-XXX	60.00 - 90.00	48.40	87.79 - 58.86	20 - 30	19.15 - 28.56
021-XXX			82.37 - 55.22		20.37 - 30.38
023-XXX	75.00 - 110.00	59.06	112.5 - 79.26	14 - 20	13.82 - 19.63
024-XXX			105.6 - 74.37		14.73 - 20.86
026-XXX	90.00 - 140.00	73.84	171.4 - 110.0	8.8 - 13	8.618 - 13.43
027-XXX			160.9 - 103.3		9.161 - 14.27
029-XXX	110.00 - 170.00	90.845	238.1 - 150.9	5.9 - 9.3	5.662 - 8.934
030-XXX			223.5 - 141.7		6.019 - 9.494
032-XXX	140.00 - 220.00	115.750	343.6 - 216.0	3.7 - 6.1	3.674 - 5.844
033-XXX			322.7 - 202.8		3.904 - 6.211
035-XXX	170.00 - 260.00	137.52	428.2 - 283.2	2.8 - 4.5	2.832 - 4.282
036-XXX			402.0 - 265.9		3.010 - 4.551
038-XXX	220.00 - 325.00	173.28	570.9 - 388.0	1.9 - 2.6	2.021 - 2.973
039-XXX			536.0 - 364.4		2.148 - 3.159

1/ At 20°C waveguide temperature.

2/ These values were determined by calculating the non-pressurized air dielectric breakdown strength produced by considering the E field within the waveguide. This determination was based on the peak value of a continuous wave (CW) signal. For further information see M. Gilden and L. Gould, “Handbook on High Power Capabilities of Waveguide Systems,” June 1963, Navy Contract Nobsr-85190, Index No. SR0080302, ST 9604.

3/ These values were determined by calculation of the rate of heat loss to the ambient, considering a non-pressurized air dielectric waveguide in air using no artificial heat sink. A maximum waveguide temperature of 71°C, 1:1 VSWR, and an ambient temperature of 30°C were assumed. For additional information see H.E. King, “Rectangular Waveguide Theoretical CW Average Power Rating,” IRE Transactions PGMTT-9, pp 349-357, July 1961.

TABLE III. Supersession data and cross index.

Part number M85/3-	Superseded part number M85/1-	Cross index		
		AN type	NATO type	EIA type
006-XXX	114-XXX	RG-96/U	NWG-6A22	WR28S
008-XXX	117-XXX	RG-271/U	---	---
010-XXX	118-XXX	RG-97/U	NWG-6A23	WR22S
012-XXX	121-XXX	RG-272/U	---	---
016-XXX	124-XXX	RG-358/U	---	---
017-XXX	125-XXX	RG-98/U	NWG-6A25	WR15S
020-XXX	129-XXX	RG-99/U	NWG-6A26	WR12S

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:44Z
Check the source to verify that this is the current version before use.

TABLE IV. Materials.

Material	Resistivity @ 20°C (max) (microhm-cm)	Conductivity (percent) 1/	Specification Reference 2/
Aluminum alloy 6061	4.00	40 to 45	ASTM-B308/B308M
Copper: OF DLP	1.77 1.793	101 up to 100	ASTM-B249/B249M ASTM-B75
Bronze (90 Cu/10 Zn)	3.9	44	ASTM-B249/B249M
Silver, coin	2.03	85	ASTM-B617

1/ 172.41 / resistivity = % IACS (International Annealed Copper Standard).
2/ Copies are available through ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania, U.S. 19428-2959 or http://www.astm.org/.

Referenced documents. In addition to MIL-DTL-85, this specification sheet references the following documents:

ASTM-B75
ASTM-B249/B249M
ASTM-B308/B308M
ASTM-B187/B187M
ASTM-B152/B152M
ASTM-B617

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-2012-004)

Review activities:
Army - AR, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19, 71, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:44Z
Check the source to verify that this is the current version before use.