INCH-POUND

MIL-C-81/5B
27 December 1989
SUPERSEDING
MIL-C-81/5A
1 February 1971


MILITARY SPECIFICATION SHEET

CAPACITORS, VARIABLE, CERAMIC, DIELECTRIC,

STYLE CV34

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-81.



Inches	mm	Inches	mm
.005	0.13	.11	2.79
.014	0.36	.12	3.05
.032	0.81	.130	3.30
.04	1.02	.260	6.60
.05	1.27	.27	6.86
.065	1.65	.37	9.40
.070	1.78	.50	12.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.02 (0.51 mm) and ±.010 (0.25 mm).
4. This hole is optional.

FIGURE 1. Dimensions and configuration.

Ⓑ denotes changes

FSC 5910
AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Capacitance value: See table I.

DC rated voltage: See table I.

Ⓑ Operating temperature and storage range: -55°C to +125°C.

Characteristic: See table I.

Dielectric withstanding voltage: Method 301 of MIL-STD-202. A dc potential of 2.2 times rated voltage applied between terminals for 3 ±2 seconds.

Barometric pressure: Method 105 of MIL-STD-202, condition D (100,000 feet).

Test potential: 100 percent of dc rated voltage.

Insulation resistance: Method 302 of MIL-STD-202, condition A, 100 V dc applied, 10,000 megohms minimum.

Capacitance: Method 305 of MIL-STD-202.

DF: At 1 MHz ±100 kHz, at maximum and minimum capacitance, shall be not more than 0.2 percent.

TABLE I. Style CV34.

Type designation	Capacitance		DC rated voltage	Characteristics				
	Min (pF)	Max (pF)		Symbol	Capacitance change from value at 25°C			
			(volts)		At -55°C		At +85°C	
					Minimum percent	Maximum percent	Minimum percent	Maximum percent
CV34A080	1.5	8.0	350	A	-4.5	+2.0	-2.5	+2.0
CV34A150	4.0	15.0	350	A	-4.5	+2.0	-2.5	+2.0
CV34D200	4.0	20.0	200	D	+1.5	+7.0	-5.0	-1.5
CV34D350	8.0	35.0	200	D	+1.5	+7.0	-5.0	-1.5
CV34E600	15.0	60.0	200	E	+3.0	+14.0	-10.0	-3.0

Temperature coefficient: Within the limits specified for the applicable characteristics.

Capacitance drift: Within 0.75 percent of initial step 1 measurement or 0.50 picofarad (pF), whichever is greater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

Terminal strength:

Pull test: Capacitor held by body and 4-pound load applied to each terminal for at least 10 seconds.

Torque: Not less than 1 nor more than 6 ounce-inches.

Fatigue:

ΔC: Shall not exceed 12 percent or 0.75 pF, whichever is greater.

Torque: Not less than 1 nor more than 10 ounce-inches.

Life:

Qualification test: 1,000 hours at +85°C, 150 percent or rated volts dc with a peak alternating voltage of 50 percent of rated volts dc (100 hertz or less) superimposed.

Insulation resistance: Initial requirement.

Capacitance change: Shall not exceed ±8 percent of initial value or 0.5 pF, whichever is greater.

Group C life: Conditions and requirements are the same as that for qualification.

Shock (specified pulse): Method 213 of MIL-STD-202, condition I (100 g's).

Vibration: Method 204 of MIL-STD-202, condition B (15 g's).

Capacitance change: Shall not exceed ±2 percent of 0.5 pF, whichever is greater.

DF: Shall be not more than 0.3 percent.

Insulation resistance: Shall be 10,000 megohms, minimum.

Moisture resistance: Method 106 of MIL-STD-202.

Insulation resistance: Shall be 10,000 megohms, minimum.

Capacitance change: Shall not exceed ±5 percent of nominal value or 0.5 pF, whichever is greater.

DF: Shall be not more than 0.5 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 17
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1662-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.