INCH POUND


MIL-PRF-81/6F
21 April 2011
SUPERSEDING
MIL-PRF-81/6E
21 April 2006

PERFORMANCE SPECIFICATION SHEET


CAPACITORS, VARIABLE, CERAMIC DIELECTRIC,
STYLES CV35 AND CV36

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-81.



Inches	mm
.008	0.20
.015	0.38
.020	0.51
.025	0.64
.040	1.02
.065	1.65
.090	2.29
.145	3.68
.195	4.95
.218	5.54
.250	6.35




RECOMMENDED
MOUNTING HOLES

Style CV35

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.



Inches	mm
.008	0.20
.015	0.38
.016	0.41
.020	0.51
.025	0.64
.030	0.76
.035	0.89
.045	1.14
.060	1.52
.080	2.03
.100	2.54
.145	3.68
.200	5.08
.218	5.54
.235	5.97
.239	6.07

Style CV36

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005.

FIGURE 2. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 or figure 2.

Capacitance value: See table I.

DC rated voltage: See table I.

Operating temperature and storage range: -55°C to +125°C.

Characteristics: See table I.

Dielectric withstanding voltage:

Method 301 of MIL-STD-202:

A dc potential of 200 V dc applied between terminals for 3 seconds ±2 seconds.

TABLE I. Style CV35 and CV36.

Type designation	Capacitance (pF)		DC rated voltage (volts)	Characteristic						
				Symbol	Capacitance change from value at 25°C					
					At -55°C		At +85°C		At +125°C	
	Min.	Max.			Min. percent	Max. percent	Min. percent	Max. percent	Min. percent	Max. percent
CV35A030	1.0	3.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV36A030	1.25	3.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-A050 2/	2.0	5.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-A090	2.5	9.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-A200	3.5	20.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-A150 2/	5.0	15.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-A250	5.0	25.0	100	A	-4.5	+2.0	-2.5	+2.0	-4.2	+3.4
CV3-C400	7.0	40.0	100	C	-1.0	+6.5	-4.0	-1.0	-6.7	-1.7
CV3-G400	7.0	40.0	25	G	-0.0	+14.0	-8.0	-3.0	-14.0	-5.0

1/ Where applicable, the complete type designation will include an additional digit to indicate CV35 or CV36.
2/ Characteristic F is hereby canceled and there is no superseding part.

Barometric pressure (reduced): Method 105 of MIL-STD-202, condition D (100,000 feet). Test potential: 100 percent of dc rated voltage.

Insulation resistance: Method 302 of MIL-STD-202, condition A, 100 volts dc applied: 10,000 megohms, minimum.

Capacitance: Method 305 of MIL-STD-202.

DF: At 1 MHz ±100 kHz, at maximum and minimum capacitance: Shall be not more than 0.2 percent for characteristic A and 0.5 percent for characteristics C and G.

Temperature coefficient: Within the limits specified for the applicable characteristic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

Capacitance drift: Within 0.75 percent of initial step 1 measurement or 0.50 (picofarad) pF, whichever is greater.

Terminal strength: Pull test: Capacitor held by body and 4-pound load applied to each terminal for at least 10 seconds.

Torque: Not less than 0.3 ounce-inch nor more than 3 ounce-inches.

Shock (specified pulse): Method 213 of MIL-STD-202, condition I (100 g's).

Vibration, high frequency: Method 204 of MIL-STD-202, condition B (15 g's).

Capacitance change: Shall not exceed ±2 percent or 0.5 pF, whichever is greater.

DF: Shall be not more than 0.2 percent for characteristic A and 0.5 percent for characteristics C and G.

Dielectric withstanding voltage: 200 volts dc, applied for 3 seconds ±2 seconds.

Insulation resistance: 10,000 megohms, minimum.

Fatigue:

Capacitance change: Shall not exceed ±12 percent of initial value or 0.75 pF, whichever is greater.

Torque: Not less than .3 ounce-inches, nor more than 3 ounce-inches.

Life:

Qualification test: 1,000 hours at 85°C, 150 percent of rated volts dc with a peak alternating voltage of 50 percent of rated volts dc (100 hertz or less) superimposed.

Insulation resistance: Initial requirement.

Capacitance change: Shall not exceed ±8 percent of initial value or 0.5 pF, whichever is greater.

Group C life: Conditions and requirements are the same as that for qualification except that capacitance change shall not exceed ±5 percent of initial value or 0.5 pF, whichever is greater.

Moisture resistance: Method 106 of MIL-STD-202.

Insulation resistance: 10,000 megohms, minimum.

Capacitance change: Shall not exceed ±5 percent of nominal value or 0.5 pF, whichever is greater.

DF: Shall not be more than 0.5 percent for characteristic A and 1.25 percent for characteristics C and G.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.

Reference documents. In addition to MIL-PRF-81, this document the following.
MIL-STD-202.

Custodians:
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activity:
Air Force – 19, 99

(Project 5910-2011-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:41Z
Check the source to verify that this is the current version before use.