MIL-C-18277B(WEP)
AMENDMENT-3
15 MAY 1964
SUPERSEDING
AMENDMENT-2
1 MARCH 1963

MILITARY SPECIFICATION

COUPLER, ANTENNA CU-351(*)/AR
AND
COUPLER, ANTENNA CU-509(*)/AR

This amendment forms a part of Military Specification MIL-C-18277B(WEP) dated 15 February 1961 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

Page 1, paragraph 1.1: Delete "50-150 watt" and substitute

"50-185 watt average and 600 watt PEP"

Make this same change wherever "50-150 watt" is used in this specification.

*Page 1, paragraph 1.2, under "Type Designation": Delete "MT-1660(*)/AR" and substitute

"MT-(*)/AR"

Make this same change wherever "MT-1660(*)/AR" is used in this specification

Page 1, paragraph 2.1, after "to the extent specified herein:" Add

"(See 6.2)"

Page 4, after paragraph 3.2.2.1: Add

"3.2.2.2 Explosion-proof and Sand and Dust - The equipment shall not be required to comply with the explosion-proof and sand and dust requirements of Specification MIL-E-5400."

Page 6, paragraph 3.2.14: Add

"except as follows:

3.2.14.1 Conducted Interference, Power Leads - The limits for Conducted Interference on the Power Leads are raised 6 db above the applicable requirements of Specification MIL-I-6181.

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:11Z
Check the source to verify that this is the current version before use.

3.2.14.2 Radiated Interference - The limits for generated radiated interference are raised to 400 microvolts in the 100 to 120 mc frequency range and to 200 microvolts for all other harmonic or spurious frequencies. The radiated interference requirements of Specification MIL-I-6181 are not applicable for radiated interference resulting from RF signals being introduced through the equipment."

*Page 6, paragraph 3.3.4, seventh line: Delete "fixed wing" and substitute

"fixed wire"

*Page 6, paragraph 3.3.4, after second sentence,: Add

"The maximum peak instantaneous voltage the equipment is required to withstand as measured at the antenna terminal shall be 5000 volts. The maximum RMS antenna current the equipment is required to withstand as measured at the antenna terminal shall be 7.5 amps between 2 and 15 mc and 5 amps between 15 and 23 mc."

Page 7, paragraph 3.3.4, fourth and seventh colums: Delete and substitute

Long Antenna	Short Antenna
Eff. %	Eff. %
45	25
65	49
74	61
80	63
67	73
80	80
60	80
63	50
75	53
80	80
67	70
80	40
80	36
49	36
50	42
75	62
46	35
10	65
33	33
27	26
40	31
39	12

*Page 10, paragraph 3.4.2.2: Delete and substitute

"3.4.2.2 Form Factor and Mounting - The case and mounting shall be in accordance with Specification MIL-C-172 except that the case dimensions shall not exceed 15 5/8 by 12 3/16 by 8 13/16 inches and the mounting

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:11Z
Check the source to verify that this is the current version before use.

base dimensions shall not exceed 15 3/4 by 13 1/8 by 2 5/8 inches. The Mounting MT-(*)/AR shall be suitable for attachment to a plane surface in an aircraft and for supporting the coupler which shall be removeable without the use of tools. The installation requirements for Mounting MT-(*)/AR shall be the same as MT-1660A/AR. The vibration and shock isolation element shall be S638 ALPCO Polyurethane Flexible Foam 1 1/2 inches thick, 3.8 pounds per cubic foot density (manufactured by American Latex Products Corporation, Hawthorne, California) or equivalent. Goodyear Aircraft Pliobond Cement #30 or equivalent shall be utilized for bonding the flexible foam to its mounting plate.

3.4.2.2.1 Shock Isolation - Mounting MT-(*)/AR, when properly loaded (e.g. with CU-509/AR Antenna Coupler) shall be capable of withstanding shock with intensities of 90G, one in each direction, in accordance with Specification MIL-T-5422 and there shall be no mechanical failure of the Mounting, vibration and shock isolation element (i.e. the polyurethane flexible foam), or any of the holding devices as a result of such impacts.

3.4.2.2.2 Transmissibility - Vibration isolation efficiency of Mounting MT-(*)/AR shall be in accordance with Specification MIL-C-172 and shock isolation efficiency shall not exceed a transmissibility of 60% with 10g input or 100% with 15g input in accordance with Specification MIL-T-5422."

Page 19, paragraph 6.2, Precedence of Documents: Add

"(4) Reordered Equipment - The following specifications shall take precedence over those concerning performance requirements listed or referenced in paragraph 2.1, where equipment is reordered, except in those areas where the contract specifies redesign or modification affecting performance:

MIL-E-5400D	30 November 1959
MIL-T-5422D	1 November 1957
MIL-I-6181B	29 May 1953"

An asterisk preceding a page number denotes a change to the specification which did not appear in Amendment-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:11Z
Check the source to verify that this is the current version before use.