MIL-D-18243B(AS)
25 September 1977
SUPERSEDING
MIL-D-18243A(AS)
6 May 1966

MILITARY SPECIFICATION

DEMONSTRATION OF AIRBORNE TARGET AND MISSILE SYSTEMS GENERAL SPECIFICATION FOR

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the contractor's formal demonstration of air launched guided missile systems and aerial target systems including the ground support equipment, test equipment, launch equipment and ancillary equipment. Whenever the word system or systems is used in this specification it shall mean air launched guided missile system or aerial target system as applicable.

1.2 Purpose. The purpose of the demonstration is as follows:

a. To demonstrate the functional compatibility of all components comprising the system and its conformity to requirements specified in the contract detail specifications. The system is comprised of the launching equipment, air launched guided missile or aerial target, air launched guided missile or aerial target components, containers and ground support equipment. For an airborne launch of a target, the aerial target system will also include the aircraft target control panel, mechanical and electrical inter-face adapter, and target delivery and retrieval equipment, as applicable.

b. To demonstrate an airborne or surface launch capability, the functional compatibility of the systiem with the system designated as the launch platform, and compatibility with the tracking and control equipment. For an airborne launch, the launch platform will consist of the launch aircraft, the launch central panel for the system, mechanical and electrical interface adapters, and the system release, jettison and retrieval equipment as applicable.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Systems Command, Headquarters (AIR-6301), Department of the Navy, Washington, D. C. 20361, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1550

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

c. To ascertain the readiness of the system to enter Government evaluation by indicating the achieved level of performance, maintainability, serviceability, and reliability of the system in comparison with performance, maintainability, serviceability, and reliability required by the contract detail specification.

2. APPLICABLE DOCUMENTS

"This section is not applicable to this specification."

3. REQUIREMENTS

3.I Prerequisites for formal demonstration When the contractor is ready to conduct a contractor's formal demonstration, he shall submit his request to NAVAIR in writing for acceptances. A demonstration plan (see 3.6.1) shall be included with the request. The contractor shall submit each system to an acceptance test at the contractor's facility. Evidence that each system has passed this test shall be presented to the cognizant Contract Administration Office (CAO). After fulfilling this requirement each system may be submitted for demonstration.

3.2 Formal demonstration. Upon NAVAIR approval of the prerequisites for formal demonstration the contractor shall conduct a formal demonstration of the system in accordance with the requirements specified herein or in the applicable addendum to this specification (see 6.1). This demonstration shall be offically witnessed by NAVAIR or a designated representative.

3.3 General

3.3.1 Deviations. Deviations from this specification will not be permitted unless specifically approved by NAVAIR. Deviations may be requested when realistic improvements are attainable and the deviations are fully justified.

3.3.2 Modifications. At the discretion of the contractor and after approval by the Government Test Activity (GTA), such system components except Government Furnished Equipment (GFE) as may have been accepted by the government at the source of manufacture, may be modified by the contractor at the test facility or another convenient modification facility for purposes of meeting safety or other specialized requirements at the test facility.

3.3.3 Alterations. NO alterations shall be permitted except after request by the contractor and after approval by NAVAIR. Any such alterations made shall be incorporated in each system or system components remaining to be demonstrated. When NAVAIR determines alterations significantly change the performance of the system, appropriate portions of the demonstration previously completed shall be required to be repeated.

3.3.4 System repair. Systems which fail the tests of 3.4 or 3.5 will be returned to the contractor at the Government expense and shall be repaired, exluding GFE, at no increase in contract price provided these systems were not damaged or improperly tested by the GTA. Systems which were damaged as a

Source: https://assist.dla.mil -- Downloaded: 2026l0-18T11:08Z
Check the source to verify that this is the current version before use.

result of improper handling, improper GFE container design, improper GFE container construction, or improper transport will be returned to the contractor and will be repaired at the Government's expense. Systems which were damaged as a result of improper testing by the GTA will be returned to the contractor and will be repaired at the Government's expense.

3.3.5 Contractor responsibility The demonstration shall be conducted under the technical direction (see 6.3.2) of the contractor. The contractor shall furnish standard best equipment as well as equipment peculiar to the requirements of the demonstration and items of a recurring nature. Any equipment procured or constructed by the contractor with governent funds shall be appropriately marked and shall be disposed of after completion of the contract according to NAVAIR instructions.

3.3.6 Government responsibility. Since demonstrations require the use of government test ranges and other test facilities, the test activity will exercise technical control (see 6.3.1) over these facilities during the demonstration and will provide the same kinds of materials, facilities and services to the contractor as have been furnished in support of the contractor’s development test program, or as otherwise stipulated in the contract.

3.3.7 Location of demonstrations. Except or specific demonstrations or portions of demonstrations; which can be more economically or expeditiously conducted at the contractor' plant or at other activities designated by NAVAIR, demonstrations will be conducted at the GTA.

3.3.8 Handling, storage and transportation. The system will be handled such that the design limits of the applicable contract detail specification will not be exceeded. The system will be transported. and stored in the containers or packaging specified in the applicable contract detail specification. Storage and transportation at the test facility will be the responsibility of the Government. All shipments of systems, system components or equipments from the contractor, during the conduct of the demonstration, will be the responsibility of the Government.

3.3.9 Aircrews. The GTA will provide qualified Naval aircrews to perform the contractor demonstrations.

3.3.10 Measurements. The data used by the GTA to determine system performance in ground test and flight test will be provided to the contractor upon request.

3.3.11 Weight and balance. During all tests which involve demonstration of a System, the contractor shall simulate the actual weight and center of gravity locations encountered in operation of the system. This may be accomplished by installation of actual equipment or by the substitution of ballast such that weight, center of gravity, and moment of inertia characteristics are simulated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

3.3.12 Manuals. All tests conducted on the airborne equipment during the demonstration shall be conducted in accordance with the contractor furnished test procedures, intstructions, and maintenance manuals that shall be delivered with the aerial target systems

3.4 Ground tests

3.4.1 General. The purpose of the ground test program is to: (1) demonstrate the operational procedures involved-in preparing the system fro flight; (2) verify that the missile or target is ready for flight; (3) demonstrate the functional compatibility of all components comprising the system; and (4) demonstrate compliance with the contract detail specification. The functional compatibility shall include the missile or target with the ground support equipment and the missile or target with the launching equipment.

3.4.2 Ground handling. Demonstrate proper methods of handling of the system; e.g., unpacking. (and packing)$_{s}$ servicing attaching to (and detaching from) launcher or launching aircraft, etc., including proper use of lift points, grips, and special devices for hoisting. Assembly, transporting, and operational checkout procedures shall be demonstrated

3.4.3 Accessibility. Demonstrate access to all components requiring adjustment or frequent replacement. The demonstration shall include operations on the system when it is on or off the launcher.

3.4.4 Interchangeability. Demonstrate interchangeability of target elements by random selection of the demonstration elements at the demonstration facility. Unless otherwise specified, the following shall be demonstrated:

a. Interchangeability of system sections, components and equipments including those of alternate manufacturing sources where required.

b. Interchangeability of units of launcher equipment.

c. Interchangeability of aircraft interface components of control panels.

d. interchangeability of units of test and check-out equipment,

3.4.5 Alignment. Demonstrate all methods employed in the alignment, adjustment, and installation o-f wings$_{s}$ control and stabilizing surfaces, engine, boosters, and other parts or components requiring accurate positioning.

3.4.6 Ordnance. Tests by the contractor with Government and contractor furnished ordnance or electro explosive devices as installed in the system shall demonstrate that the explosive components do not operate prematurely or improperly by malfunctions, within the system during check out. Safety measures shall be demonstrated. All ordnance components and electroexplosive. devices as installed in the system shall have been qualified HERO (Hazardous Electromagnetic Radiation Ordnance) safe.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

3.4.7 Ground support equipment. Demonstrate the use of all system ground support equipment necessary for checkout of the system. This includes demonstration of component test equipment, overall systems test equipment, and any special test equipment necessary for determining the readiness of the test equipment.

3.4.8 Readiness. Demonstrate the time required to achieve ready-to-launch xcondition.

3.4.9 Standby Condition. Demanstrate the time that the system can maintain a standby or ready-to-launch condition meets the requirements of the detail specification.

3.4.10 Blast. Demonstrate or determine that the blast wave and jet stream from booster or engine will have no adverse effects on ground equipment or adjacent structure of the launching aircraft or constitute undue hazard to personnel.

3.4.11 Guidance system. Demonstrate the normal ground preflight checkout procedures used to verify- satisfactory component and system operation of the guidance system.

3.4.12 Launch system. Satisfactory ope%ation of the launch system shall be demonstrated.

3.4.13 Flotation (targets). The ability of the Earget to meet the flotation requirements shall be demonstrated

3.4.14 Propulsion. Demonstrate satisfactory operation of the propulsion system and conformance with the detail specification.

3.4.15 Safety procedures. Demonstrate all emergency procedures, aborted flight parameters, fail safe jettison techniques and safety features to show compliance with safety regulations.

3.4.16 Retrieval. Demonstrate retrieval methods as specified in the applicable detail specification and safety measures to helicopter and/or recovery boat crews.

3.4.17 Refurbishment. Demonstrate the airborne vehicle ability to be refurbished and successfully flown after saltwater immersion.

3.4.18 Maintainability. Demonstrate the maintainability of the system to:

a. Determine whether the system meetx ghe maintainability and maintenance requirement parameters of the system specification.

b. Confirm the applicability of the maintenance concept to be utilized by operating and support activities.

Source: https://assist.dla.mil -- Downloaded: 2026t0-18T11:08Z
Check the source to verify that this is the currentversion before use.

c. Determine the adequacy of the support equipment and technical manuals to permit support of the maintenance concept with a minimum amount of man-hours and materials.

d. Determine the extent to which safety considerations have been addressed, in both design and procedures.

e. Determine the training and number of personnel (in quantity and skill levels) required to maintain the system under established maintenance concepts.

f. Determine the facilities requirement for planned maintenance activities, both organizational and intermediate levels.

g. Determine improvements to maintainability or related support characteristics that can be incorporated into the production design.

h. Check interchangeability and standardization of system spares and repair parts.

3.5 Flight tests

3.5.1 Purpose. The purpose of the flight test program shall be to demonstrate functional capability of the airborne vehicle to meet detail specifications under varying flight and environmental conditions. The flight test program shall demonstrate flight reliability, controllability and operational compatibility with Range Command control and telemetry facilities and other government furnished equipment. These tests shall continue until the required number of systems are tested. It shall be the prerogative of the Government to terminate these tests prior to their completion if the data obtained from the initial flights indicates that conducting the remainder of the tests would not be in the Governments interest.

3.5.2 Test articles. One group of missiles or targets will be allocated to these tests are launching. The individual serial numbers of these missiles or targets shall be forwarded to NAVAIR. Missiles or targets shall be launched under test conditions specified in the demonstration plan approved by NAVAIR to show compliance with the detail specification.

3.5.3 Testing procedures. The preflight checkout procedures used shall be similar to those satisfactorily demonstrated under the ground test phase of the demonstration and shall be limited in extent to what the contractor proposes to be performed on missiles or targets in the Government evaluation. Deviations in the preflight checkout procedures shall be allowed only after prior apptoval by the GTA and NAVAIR.

3.5.4 Captive flight. Demonstrate that the target or missile, properly attached to the launcher on the specified launch aircraft, can be carried under all catapult launch, flight, and arrested landing conditions within the operational envelope of the aircraft, can be subjected to the aircraft carrier launch and recovery environment and will function properly after being subjected to this flight environment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

3.5.5 Launch. Demonstrate that the system can be launched from the launcher at the demonstration test conditions For air launched targets demonstrate that any deviation of the target from its normal flight path, due to the effect of the airflow of the launching airplane, will not result in collision-with the launching aircraft or cause malfunction of the target and is within the capture limitations of the target system.

3.5.6 Ordnance. All explosive items, inert-loaded, live or properly simulated, as designated by NAVAIR, shall be installed Their safety features and proper operation shall be demonstrated.

3.5.7 Instrumentation. The reliability. maintainability, and functional requirements of instrumentation, including that required to assess intercept distance (miss distance), shall be demonstrated.

3.5.8 Flight plan. The free flight targets or missiles shall be tested as specified by NAVAIR within the limitations specified in the applicable contract detail specification. flight plan variables required for safety or other specialized requirements of the test facility will be selected by the test facility and supplied to the contractor.

3.5.9 Blast. Demonstrate or determine that the blast wave and jet stream from booster engine will have no adverse effects on adjacent structure or on the launching aircraft, or cause instability to the launching aircraft or constitute a hazard to personnel.

3.5.10 Simulated inflight check. Demonstrate the time required far Che system to attain a warmed-up ready ta launch condition after the ready switch has been turned on. This demonstration may be conducbed on the ground.

3.5.11 Accuracy. Demonstrate the target or missile ability to fly predetermined flight profiles from the maximum weight to the fuel depletion weight and conformance to the contract detail specification.

3.5.12 Strength. Structural adequacy shall be demonstrated for the critical design operating conditions by the performance of maneuvers in accordance with the flight plan (see 3.6.2) and the contract detail specification.

3.5.13 Transfer control (targets). The transfer of command control from one transmitter to another on the same frequency to demonstrate surface to air and air to surface transfer shall be in accordance with the contract detail specification.

3.5.14 Speed. The attainment and maintaining of speeds specified in the applicable contract detail specification shall be demonstrated.

3.5.15 Endurance. Compliance with the endurance requirements of the applicable contract detail-specification shall be demonstrated.

3.5.16 Range. Remote command control for all aspect positions of the missile or target out to the range limits specified in the applicable contract. detail specification shall be demonstrated.

Source: https://assist.dla.mil -- Downloaded: 2026t0-18T11:08Z
Check the source to verify that this is the currentversion before use.

3.5.17 Altitude. Compliance with the altitude requirements of the applicable contract detail specification shall be demonstrated.

3.5.18 Recovery (targets). Parachute landing, or other recovery systems, to meet the recovery requirements of the applicable contract detail specification shall be demonstrated.

3.5.19 Visual identification (targets). Compliance of the visual identification requirements of the applicable contract detail specification shall be demonstrated.

3.5.20 Propulsion. Satisfactory operation of the propulsion system, and conformance with the contract detail specification shall be demonstrated.

3.5.21 Augmentation devices (targets). Radar reflectivity, infrared or other augmentation systems as required by the applicable contract detail specification shall be demonstrated.

3.5.22 Free flight termination. Capability of free-flight termination or safety aero-destruct system to meet range safety requirements and the contract detail specification shall be demonstrated.

3.6 Documentation. Demonstration documentation shall be as specified on a contract data requirements list (see 6.2.2 and the Appendix). Data requirements appearing in this specification do not apply unless listed on the contract data requirements list.

3.6.1 Demonstration plan. A formal demonstration plan shall be submitted and shall. consist of the following:

a. A list of materials and services required specifically for the demonstration including test equipment, ground support equipment, launch equipment, telemetry equipment, beacons, etc., required during the demonstration.

b. Indication by the contractor that the system is ready for demonstration and that it will meet the performance requirements of the applicable contract detail specification.

c. General flight test program plan and schedules for demonstrating items required by the applicable addendum to this specification.

d. Methods for obtaining, processing, and analyzing data.

e. Methods of presenting results of post flight evaluations.

3.6.2 Flight plan. This plan shall be prepared for each block of targets to be launched and shall include the data specified below. The plan shall include data sufficient to allow the test activity to plan for each flight. The plan shall be amended by letter as found necessary prior to flight of a modified or altered target system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

a. Specific description of plans, schedules and objectives of each flight.

b. Specific description of equipment including block diagrams, wiring diagrams, general arrangement, test equipment, as changed from previous equipments.

c. Deviations from the general flight test program plan.

d. Description of reliability tests to be performed prior to launching.

e. Description of instrumentation required.

3.6.3 Post flight report. A post flight report is required within 48 hours after completion of flight, except when additional delay is essential to the presentation of data. The letter report shall be submitted after every target flight and shall be a brief description of the flight tests and results including:

a. Statement of the plans and objectives.

b. Visual observations.

c. Preliminary conclusions of test results including comparison of recorded results with expected results.

3.6.4 Demonstration report. A demonstration report shall be submitted. The report shall summarize the results of the formal demonstration including:

a. Discussion of all items required ho be demonstrated by the applicable demonstration addendum, including analysis and comparison of flight results with expected results.

b. Discussion of the ability of the target or missile to fly predetermined flight paths.

c. A comparison of Ehe required versus achieved performance and serviceability.

d. A comparison of the required versus achieved reliability and maintainability including rationale how system values were derived from the data collected during the demonstration program.

e. The time, manpower and facilities required to prepare the sysem for flight determined fxom data collected during the demonstration.

f. A complete analysis of all failures and defects which occurred in the demonstration, their causes, and their corrections.

g. Conclusions which affect system design and co&truction, and proposed plans for incorporation of design changes or for modification of the design approach.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

3.6.5 Alteration report. An individual report on each alteration (see 6.3.4) proposed for incorporation in the demonstration targets or missiles shall be submitted. Each report shall include the following information:

a. Number of alteration (numerical sequence in any particular demonstration),

b. Detailed description of alteration,

c. Reason for alteration,

d. Serial numbers of targets or missiles affected,

e. Affect on validity of tests already completed,

f. Contractor's signature.

3.6.6 Demonstration manual(s). The manual or manuals for-the demonstration shall support the contractor's demonstration at the GTA, and shall include the following coverage as applicable.

a. Introduction appropriate to the system test objectives to be demonstrated.

b. Preparation for use instructions including use of ground support equipment.

c. Description of tests to be performed or the associated test procedures.

d. Description of the preflight and postflight maintenance to be performed or the associated procedures.

e. Packaging and preparation for shipment after recovery.

3.7 Discrepancy or conflict. In the event the contractor determines that a discrepancy or conflict exists between or among the contract, this specifications the contract detail specification, the applicable addendum to this specification, or any referenced documents, it shall be the responsibility of the contractor to disclose this to the procuring activity. The contractor shall recommend changes for the discrepancies or conflicts in accordance with the contract change clause. Further,it shall be the responsibility of the contrctorto provide objective evidence and sufficient proof to the procuring activity that the requirements of this specification cannot be met or demonstrated before any deviation or waiver will be granted. Any change go the contract, this specification, contract detail specification, the applicable addendum to this specification, or any referenced document, will be considered for approval only when the above requirements have been met.

4. QUALITY ASSURANCE PROVISIONS. This section is not applicable to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

5. PACKAGING. This section is not applicable to this specification.

6. NOTES. The contents of this section are not contractually binding. Any information which should be made known as background information or as instructions to the contracting officer may be included herein.

6.1 Intended use. This general specification will be used by NAVAIR as the standard form for contract addenda for airborne target systems and airlaunched guided missile systems. Addenda to this specification will conform to the following requirement:

(1) Agree with this general specification in paragraph arrangement, numbering and headings except that where a paragraph is listed in the addendum to this specification as "not applicable", or "no required", subsequent paragraphs will be omitted provided numbering sequence is not affected.

(2) When paragraphs of this general specification are “applicable” as Written, the requirements of this general specification will be incorporated into the addendum. General specification paragraphs may be modified for a specific aerial target system.

(3) Subparagraphs will be added as required.

(4) In cases of discrepancies between this general specification and an addendum, the addendum will govern.

6.2 Ordering data. Procurement document: should -specify the following.

6.2.1 Procurement requirements.

a, Title, number and date of this specification and applicable addendum thereto. For example: Addendum No. 16 to MIL-D-18243B(AS) of 4 January 1976.

6.2.2 Data requirements. When this specification is used in a procurement the data requirements exemplified in the Appendix will be developed into an approved contract data requirements list for incorporation into the contract. Deliverable data required by this specification are cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
a. 3.6.1	Demonstration Plan	UDI-T-2003l
b. 3.6.2	Flight Plan	DI-T-3731
c. 3.6.3	Post Flight Report	DI-T-3718
d. 3.6.4	Demonstration Report	DI-T-37I8
e. 3.6.5	Alteration Report	DI-E-3114
f. 3.6.6	Demonstration Manual(s)	UDI-T-23983

6.3 Definitions. Definitions, acronyms and interpretations of terminology used herein are as follows.

Source: https://assist.dla.mil -- Downloaded: 2026l0-18T11:08Z
Check the source to verify that this is the current version before use.

6.3.1 Technical Control. Technical control refers to the specialized guidance provided, and direction exercised by the GTA in matters relating to the planning of, preparation for, conduct of, and evaluation of the results of tests specified by this document. Such control includes, but is not limited to:

a. Authority to alter or stop tests whenever:

(1) Dictated by safety considerations.

(2) There is danger of interference with projects of higher priority.

(3) Test articles do not comply with contractually invoked specifications.

(4) Continuation Of the tests would result in unwarranted expenditures of Government funds or property.

(5) Previous test results indicate this to be a prudent course of action.

6.3.2 Technical direction. Technical direction is defined as including the formulation of general test programs and detailed test plans, the preparation of articles to be tested, the prosecution of article tests, the evaluation of test data, the reporting of test results, and the reorientation of the test program and plans based on these data.

6.3.3 Modification. A modification is defined as any change representing an improvement of the target or missile to serve a new end which alters the performance of the target or missile.

6.3.4 Alteration. Alteration is defined as any change representing an improvement of the missile or target without serving a new end which does not change the performance of the missile or target.

6.3.5 Acronyms.

CAO	Contract Administration Office
GFE	Government Furnished Equipment
GTA	Government Test Activity
NAVAIR	Naval Air Systems Command Department of the Navy Washington, D.C. 20361
PACMISTENTCEN	Pacific Missile Test Center Point Mugu, California 93042

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

6. Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Navy-AS

Preparing Activity:
Navy-AS

(Project 1420-N102)

FSC 1550

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

APPENDIX

CONTRACT DATA REQUIREMENTS LIST

10. SCOPE

10.1 Scope. This appendix provides a sample Contract Data Requirements List for the documentation cited in 3.6 of MIL-D-18243B(AS) and may be used as a guide in the development of an approved DD Form 1425.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

ATCH NR _____ TO EXHIBIT _____ TO CONTRACT/PR _____

CONTRACT DATA REQUIREMENTS LIST

CATEGORY _____ _____ SYSTEM/ITEM _____ CONTRACTOR _____

1. SEQUENCE NUMBER	2. TITLE OR DESCRIPTION OF DATA / 3. SUBTITLE	4. AUTHORITY (Data Item Number)	5. CONTRACT REFERENCE	6. TECHNICAL OFFICE	7. DD/250 REQ	8. APP CODE (A)	9. INPUT TO IAC (X)	10. FREQUENCY / 11. AS OF DATE	12. DATE OF 1ST SUBMISSION / 13. DATE OF SUBSEQUENT SUBM/EVENT ID	14. DISTRIBUTION AND ADDRESSEES (Addressee—Regular Copies/Repro Copies)	
001	2. Master Test Plan 3. Demonstration Plan	UDI-T-20031C	5Par. 3.6.1 of Add. to MIL-D-18243B(AS)	AIR-	LT	AN		ONE/R	See Blk 16 13. Revision pages or changes occur	14. AIR-	2/0 15. TOTAL 2/0
16. REMARKS: Block 12: Submit within 135 days prior to initiation of the system demonstration program.											
002	2. Launch/Flight Test Directive 3. Flight Plan	DI-T-3731	5Par. 3.6.2 of Add. to MIL-D-18243B(AS)	AIR-	LT	AN		ONE/R	See Blk 16 13. Revision pages as changes occur	14. AIR-	2/0 15. TOTAL 2/0
16. REMARKS: Block 12: Submit within 75 days prior to initiation of the system flight tests.											
003	2. Test Reports - General 3. Post Flight Report	DI-T-3718, See Blk 16	5Par. 3.6.3 of Add. to MIL-D-18243B(AS)	AIR-	LT			X TIME	See Blk 16 13. See Blk 16	14. AIR-	2/0 15. TOTAL 2/0
16. REMARKS: Block 4: Prepare the "Quick Look" report of Par. 10.1.a. Blocks 12 and 13: Submit with 48 hours after completion of each flight.											
004	2. Test Reports - General 3. Demonstration Report	DI-T-3718, See Blk 16	5Par. 3.6.4 of Add. to MIL-D-18243B(AS)	AIR-	LT			0 TIME	See Blk 16 13.	14. AIR-	2/0 15. TOTAL 2/0
16. REMARKS: Block 12: Submit within 45 days after completion of the demonstration program. Block 4: Prepare the Final Test Report of par. 10.1.b.											

PREPARED BY _____ DATE _____ APPROVED BY _____ DATE _____

DD FORM 1 JUN 69 1423 S/N 0102-014-1503 REPLACES EDITION OF 1 APR 69, WHICH IS OBSOLETE. PAGE ____ OF ____ PAGES

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

ATCH NR _____ TO EXHIBIT _____ CONTRACT DATA REQUIREMENTS LIST SYSTEM/ITEM _____

TO CONTRACT/PR _____ CATEGORY _____ CONTRACTOR _____

1. SEQUENCE NUMBER	2. TITLE OR DESCRIPTION OF DATA / 3. SUBTITLE	4. AUTHORITY (Data Item Number)	5. CONTRACT REFERENCE	6. TECHNICAL OFFICE	7. DD250 REQ	8. APP CODE (A)	9. INPUT TO IAC (X)	10. FREQUENCY / 11. AS OF DATE	12. DATE OF 1ST SUBMISSION / 13. DATE OF SUBSEQUENT SUBM/EVENT ID	14. DISTRIBUTION AND ADDRESSEES (Addressee – Regular Copies/Repro Copies)	15. TOTAL
1. 005	2. System Modification Design Data and Reports 3. Alteration Report	4. DI-E-3114	5. Par 3.6.5 of Add. to MIL-D-18243B(AS)	6. AIR-	7. LT	8. AN	9.	10. X TIME 11.	12. See Blk 16 13. See Blk 16	14. AIR-	2/0 15. TOTAL 2/0
16. REMARKS: Blocks 12 and 13: Submit not later than 30 days prior to flight in each case.											
1. 006	2. Procedures, Performance Measurement Test 3. Demonstration Manual(s)	4. UDI-T-23983	5. Par. 3.6.6 of Add. to MIL-D-18243B(AS)	6. AIR-	7. LT	8.	9.	10. ONE/R 11.	12. See Blk 16 13. Revision pages as changes occur	14. AIR- Govt.Test Activity	1/0 1/0 15. TOTAL 2/0
16. REMARKS: Block 12: Submit not later than 30 days prior to initiation of the demonstration program. Submit one set with each block of systems to be demonstrated.											
1.	2. 3.	4.	5.	6.	7.	8.	9.	10. 11.	12. 13.	14.	15. TOTAL
16. REMARKS											
1.	2. 3.	4.	5.	6.	7.	8.	9.	10. 11.	12. 13.	14.	15. TOTAL
16. REMARKS											

PREPARED BY _____ DATE _____ APPROVED BY _____ DATE _____

DD FORM 1 JUN 68 1423 S/N 0102-014-1503 REPLACES EDITION OF 1 APR 63, WHICH IS OBSOLETE. PAGE ____ OF ____ PAGES

16

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

INDEX

		Page
Paragraph 2	Applicable documents	2
3.7	Discrepancy or conflict	10
3.6	Documentation	8
3.6.1	Demonstration plan	8
3.6.2	Flight plan	8
3.6.3	Post flight report	9
3.6.4	Demonstration report	9
3.6.5	Alteration report	10
3.6.6	Demonstration manual(s)	10
3.5	Flight tests	6
3.5.1	Purpose	6
3.5.2	Test articles	6
3.5.3	Testing procedures	6
3.5.4	Captive flight	6
3.5.5	Launch	7
3.5.6	Ordnance	7
3.5.7	Instrumentation	7
3.5.8	Flight plan	7
3.5.9	Blast	7
3.5.10	Simulated inflight check	7
3.5.11	Accuracy	7
3.5.12	Strength	7
3.5.13	Transfer control (targets)	7
3.5.14	Speed	7
3.5.15	Endurance	7
3.5.16	Range	7
3.5.17	Altitude	8
3.5.18	Recovery (targets)	8
3.5.19	Visual identification (targets)	8
3.5.20	Propulsion	8
3.5.21	Augmentation devices (targets]	8
3.5.22	Free flight termination	8
3.2	Formal demonstration	2
3.3	General	2
3.3.1	Deviations	2
3.3.2	Modifications	2
3.3.3	Alterations	2
3.3.4	System repair	2
3.3.5	Contractor responsibility	3
3.3.6	Government responsibility	3
3.3.7	Location of demonstrations	3
3.3.8	Handling, storage and transportation	3
3.3.9	Aircrews	3
3.3.10	Measurements	3
3.3.11	Weight and balance	3
3.3.12	Manuals	4
3.4	Ground tests	4
3.4.1	General	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

INDEX (Continued)

			Page
Paragraph	3.4.2	Ground handling	4
	3.4.3	Access ability	4
	3.4.4	Interchangeability	4
	3.4.5	Alignment	4
	3.4.6	Ordnance	4
	3.4.7	Ground support equipment	5
	3.4.8	Readiness	5
	3.4.9	Standby condition	5
	3.4.10	Blast	5
	3.4.11	Guidance system	5
	3.4.12	Launch system	5
	3.4.13	Flotation (targets)	5
	3.4.14	Propulsion	5
	3.4.15	Safety procedures	5
	3.4.16	Retrieval	5
	3.4.17	Refurbishment	5
	3.4.18	Maintainability	5
	6.	Notes	11
	6.1	Intended use	11
	6.2	Ordering data	11
	6.3	Definitions	11
	6.4	Changes from previous issue	13
	5	Packaging	11
	3.1	Prerequisites for formal demonstration	2
	1.2	Purpose	1
	4	Quality Assurance Provisions	10
	1.1	Scope	1
APPENDIX		Contract Data Requirements List	14

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-D-18243B(AS) Demonstration of Target and Missile Systems General Specification for

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Naval Air Systems Command
Target and Range Division, Code AIR-630
Department of the Navy
Washington, D. C. 20361

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:08Z
Check the source to verify that this is the current version before use.