MIL-F-18215(OS)
Amendment 3
17 May 1972

Superseding
Amendment 2
25 August 1971

MILITARY SPECIFICATION

FUSE, TIME, PLASTIC COATED

This amendment forms a part of Military Specification MIL-F-18215(NOrd) dated 23 October 1954 and has been approved for use by the Naval Ordnance Systems Command, Department of Navy.

By this amendment, MIL-F-18215(NOrd) is changed to MIL-F-18215(OS).

1. Page 2, paragraph 2.2, delete in its entirety and substitute:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Code of Federal Regulations

49 CFR 171-178 Hazardous Materials Regulations, Department of Transportation

(Applications for copies of the above publication should be addressed to Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)"

2. Page 3, paragraph 3.3: Delete Table 1, and substitute the following in lieu thereof:

"

TABLE 1

Type	Color of Center Thread
1	Red
11	Yellow
111	Green

Class	Color of Thread in Outer Wrap
1	Red
2	Yellow

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:07Z
Check the source to verify that this is the current version before use.

3. Page 8, add:

"5.4 Data cards. - Data cards shall be furnished in accordance with data item description No. D1-E-2001 and prepared in accordance with MIL-STD-1167. One card shall be placed in the each packing box, two shall accompany each shipping ticket, and six shall be furnished the Government Inspector."

4. Page 8, delete Section 6 in its entirety and add:

"6. NOTES

6.1 Intended use. - The plastic coated, water-resistant, time fuse is intended for use in pyrotechnics at temperatures ranging from -65°F to +160°F.

6.2 Ordering data - Procurement documents should specify:

6.2.1 Procurement requirements

a) Title, number, and date of specification
b) Type and class of fuse (1.2)
c) Length of fuse (3.8)
d) The Government laboratory designated to evaluate the preproduction sample (4.1.2)
e) Inspection point (4.2)
f) Packaging and shipping (5.1.1 and 5.3.2)
g) That the safety precaution requirements of the Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material, DOD 4145.26M, are applicable.

NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of Ammunition Ashore, OP 5, should be made applicable.

6.2.2 Contract data requirements. Items of deliverable data required by this specification are cited in the following paragraphs herein:

Paragraph	Data Requirement (Short Title)	Applicable DID
5.4	Ammunition Data Card	DI-E-2001

DIDS (Data Item Descriptions/DD Forms 1664) for the above data requirements are/will be (*) documented in the applicable ADL (Authorized Data List).

Such data will be delivered as identified on completed (numbered) DIDS when specified on DD Forms 1423 (Contract Data Requirements Lists) and incorporated into applicable contracts."

Preparing Activity:
NAVY - OS
(Proj. No. 1390-N101)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:07Z
Check the source to verify that this is the current version before use.