NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/57C
7 February 1984
SUPERSEDING
MIL-T-27/57B
12 May 1978


PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 50 VOLT AMPERES, 400 HZ, TF4S03YY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformers described herein shall consist of this specification and the latest issue of MIL-T-27.





INCHES	MM
.031	0.79
.164	4.17
.250	6.35
.312	7.92
.344	8.74
.390	9.91
.781	19.84
1.500	38.10
2.000	50.80

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerance on terminal position dimensions is ±.015 (0.38 mm).
4. Marking shall be on the side of the case.
5. When numbers in parentheses, i.e. (1-2), are used, they indicate the winding and the extreme terminals of the winding.
6. Secondary electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configuration.

Ⓒ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses i.e. (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings· See table I.

Primary voltage (1-2). 115 volts ±10 percent, 400 Hz ±5 percent.

Design and construction.

Dimensions and configuration See figure 1.

Weight: 11 ounces, maximum.

Duty cycle Continuous.

Case Metal enclosed.

Material Steel.

Altitude. 70,000 feet, maximum.

Operating temperature range: -55°C to +130°C maximum.

Terminals Feed thru.

Terminal height 0.390 inch, maximum.

Terminal strength· Method 211 of MIL-STD-202, test condition A, 5 pounds.

Dielectric withstanding voltage

At sea level· 2.8 times the maximum working voltage specified in table I.

At reduced barometric pressure. 1.25 times the maximum working voltage specified in table I.

Electrical characteristics

No load With 115 volts, 400 Hz across (1-2)· Current in (1-2) shall not exceed 45 mA rms.

Rated load· With 115 volts, 400 Hz across (1-2) and a resistive load with current as specified in table I in (3-5), the voltage across (3-5) shall be as specified in table I.

Efficiency 92 percent minimum at rated load

Polarity. Additive with terminals 2 and 3 connected.

Regulation $\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$ shall not exceed 3 percent.

Phase shift. 1.0 electrical degree between primary and secondary voltage at rated load, maximum.

Temperature rise 35°C, maximum with 115 volts, 400 Hz across (1-2) at an ambient temperature of 95°C.

Vibration MIL-STD-202, method 204, test condition D.

Marking location See figure 1.

© QUALITY ASSURANCE PROVISIONS·

Extent of qualification

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

Qualification testing and approval to M27/49-44 A or B, M27/51-44 A or B, M27/53-44 A or B, M27/56-44 and M27/66-27 shall be sufficient to grant qualification approval to MIL-T-27/48 through MIL-T-27/66 inclusive, all parts.

Qualification testing and approval to M27/57-44 shall be sufficient to grant qualification approval to M27/57-01 through M27/57-44.

Part number M27/57-(dash number from table I).

TABLE I. Electrical ratings.

Dash no.	Secondary voltage (3-5) (V rms) ±3%	Secondary current (3-5) (amps rms)	Working voltage (V rms max)
01	6	8.333	325
02	6.3	7.937	"
03	7	7.143	"
04	7.5	6.667	"
05	8	6.250	"
06	9	5.556	"
07	10	5.000	"
08	11	4.545	"
09	12	4.167	"
10	12.6	3.968	"
11	13	3.846	"
12	15	3.333	"
13	16	3.125	"
14	18	2.778	"
15	20	2.500	"
16	22	2.273	"
17	24	2.083	"
18	26	1.923	"
19	28	1.786	"
20	30	1.667	"
21	33	1.515	"
22	36	1.389	"
23	39	1.282	"
24	43	1.163	"
25	47	1.064	"
26	51	0.980	"
27	56	0.893	"
28	62	0.806	"
29	68	0.735	"
30	75	0.667	"
31	82	0.610	"
32	91	0.549	"
33	100	0.500	"
34	110	0.455	"
35	115	0.435	"
36	120	0.417	"
37	130	0.385	"
38	150	0.333	"
39	180	0.278	"
40	200	0.250	440
41	220	0.227	440
42	240	0.208	440
43	270	0.185	580
44	300	0.167	580

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - ME
Navy - MC, AS
Air Force - 19

Agent.
DLA - ES

Preparing activity
Army - ER

(Project 5950-0623-23)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.