MILITARY SPECIFICATION

SLING ASSEMBLY: FLAKING BOX, LIFTING

6-INCH HOSELINE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a four leg lifting sling equipped with a spreader bar.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-E-52798	- Enamel, Alkyd, Camouflage.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4610

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13226E1582	- Sling Assembly, Four Leg with Spreader Bar.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The sling assembly (hereinafter called "sling") shall be in accordance with TA13226E1582 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the sling. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (first produced sling). The contractor shall furnish one or more slings as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods will produce slings that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials shall be as specified herein and as shown on the applicable drawings. Material not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.4 Performance. The sling shall lift and hold a load of 6000 pounds (1500 pounds on each hook) without slippage of wire rope in mechanical splices or bending or breaking of any weld or component.

3.5 Treatment and painting. All components of the sling, except the wire rope assemblies shall be treated and painted in accordance with MIL-T-704, Type C, with a finish coat in accordance with MIL-E-52798, Type I, color sand.

3.6 Identification marking. The sling shall be identified in accordance with MIL-STD-130.

3.7 Workmanship. The sling shall be free of all burrs, sharp edges, rust, or scale.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and material used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First produced sling inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First produced sling inspection.

4.3.1 Examination. The first produced sling shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first produced sling shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105. A lot shall consist of all slings offered for acceptance at one time. The sample unit shall be one fully assembled sling.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for defects specified in 4.5.1. AQL shall be 2.5 percent defective.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. The inspection level shall be S-2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The sling shall be examined as specified herein for the following defects:

101. Material not as specified.
102. Dimensions not as specified.
103. Identification marking missing, incomplete or illegible.
104. Treatment and painting not as specified.
105. Workmanship not as specified.

4.5.2 Test. A 1500 pound load shall be attached to each of the four hooks. The total load (6000 pounds) shall be lifted at least 1 foot above the floor and suspended in this position for not less than 1 minute. Any evidence of slippage of the wire rope in the mechanical splices, or bending or breaking of welds or other components shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106. Unpainted surfaces not preserved as specified for level A.
107. Slings not packed as specified for level A or level B.
108. Marking missing, illegible, incorrect or incomplete for level A, level B or commercial.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Unpainted metal surfaces of the sling assembly requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with P-1 or P-19 preservative. The preservative shall conform to the applicable specification listed in, and shall be applied in accordance with, MIL-P-116.

5.1.2 Commercial. Each sling shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

5.2.1 Level A. Each sling assembly shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional. The sling shall be blocked and braced within the box to prevent movement. Box closure strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. Packing shall be as specified for level A except the box shall be domestic type.

5.2.3 Commercial. Sling assemblies shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or level B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The sling is intended to lift the flaking boxes containing the 6-inch collapsible hoseline. The hoseline and flaking box conform to PD 80342.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Time frame required for submission of first produced sling and number of slings to be furnished (see 3.2).
c. Degree of preservation and degree of packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

6.3 First produced sling. Any changes or deviations of production slings from the approved first produced sling during production will be subject to the approval of the contracting officer. Approval of the first produced sling will not relieve the contractor of his obligation to furnish slings conforming to this specification.

6.4 Recycled materials. Unless otherwise specified herein all equipment, material and articles incorporated in the products covered by this specification shall be new, and shall be fabricated using materials produced from recycled materials to the maximum extent practicable without jeopardizing the intended use. The term "recycled materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically authorized (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4610-A079

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982 0 — 505-022/4666

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-S-53014(ME) Sling Assembly: Flaking Box, Lifting 6-Inch Hoseline

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R & D Command
Attn: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.