The documentation and process conversion measures necessary to comply with this amendment shall be completed by 16 November 2001.

INCH-POUND

MIL-PRF-19500/428D
AMENDMENT 2
16 August 2001
SUPERSEDING
AMENDMENT 1
22 February 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, FIELD-EFFECT TRANSISTOR, N-CHANNEL SILICON,
TYPE 2N4416A
JAN, JANTX, JANTXV AND JANS

This amendment forms a part of MIL-PRF-19500/428D, dated 30 August 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

* 4.5, screen table, screen 11, measurement columns: Delete "|yfs|2", two places.

PAGE 6

TABLE I, subgroup 4, delete and substitute:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Magnitude of small-signal, common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0 V dc; f = 1 kHz; pulse width = 100 ms; duty cycle = 10 percent	$\|y_{fs}\|_2$	4.5	7.5	mS
Small-signal, common-source short-circuit input capacitance	3431	V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz	C_{iss}		4	pF
Small-signal, common-source short-circuit reverse transfer capacitance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz	C_{rss}		0.8	pF
Small-signal, common-source short-circuit output capacitance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz (see 4.5.6)	C_{oss}		2	pF

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - continued						
Small-signal, common-source short-circuit input susceptance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3) f = 100 MHz	b_{is}		2.5	mS
Small-signal, common-source short-circuit output susceptance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3) f = 100 MHz	b_{os}		1	mS
Small-signal, common-source short-circuit input conductance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3) f = 100 MHz	g_{is}		0.3	mS
Small-signal, common-source short-circuit output conductance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3) f = 100 MHz	g_{os}		75	µS
Small signal, common source insertion power gain		V_{DS} = 15 Vdc; ID = 5 mA dc; R_G = 1 kΩ (see 4.5.5) f = 100 MHz			18	dB
Common source spot capacitance		f = 100 MHz			2	dB

"

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Navy - NW
Air Force - 11
DLA - CC

Review activities:
Navy - MC
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2473)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.