The documentation and process conversion measures necessary to comply with this amendment shall be completed by 20 December 1998

INCH-POUND

MIL-PRF-19500/486E
AMENDMENT 1
20 September 1998

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, COUPLER, OPTOELECTRIC, SOLID STATE;
TYPES 4N22, 4N22A, 4N23, 4N23A, 4N24, 4N24A, 4N22U, 4N22AU,
4N23U, 4N23AU, 4N24U, 4N24AU; JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/486E, dated 10 June 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 12

Table I, subgroup 3; delete and substitute as follows:

"

Subgroup 3						
High temperature operation:		T_A = +100°C				
(Transistor characteristics)						
Off-state collector current (phototransistor mode)	3041	Bias condition D; V_{CE} = 20 V dc; I_B = 0, I_F = 0 (see 4.5.3)	$I_{C(OFF)2}$		100	µA dc
(Coupler characteristics)						
On-state collector current 2/ (phototransistor mode)	3041	V_{CE} = 5 V dc; I_F = 10 mA dc	$I_{C(ON)3}$			mA dc
4N22, 4N22A				1.0		
4N23, 4N23A				2.5		
4N24, 4N24A				4.0		
(LED characteristics)						
Forward volltage	4011	I_F = 10 mA dc (see 4.5.2)	V_{F2}	0.7	1.2	V dc
Low temperature operation:		T_A = -55°C				
On-state collector current 2/ (phototransistor mode)	3041	V_{CE} = 5 V dc; I_F = 10 mA dc	$I_{C(ON)4}$			mA dc
4N22, 4N22A				1.0		
4N23, 4N23A				2.5		
4N24, 4N24A				4.0		
(LED characteristics)						
Forward volltage	4011	I_F = 10 mA dc (see 4.5.2)	V_{F3}	1.0	1.5	V dc

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:25Z
Check the source to verify that this is the current version before use.

Table I, subgroup 4, Input to output internal resistance, method column; add “1016”.

Custodians:
Air Force - 17
NASA - NA

Review activities:
Air Force - 19, 85, 99

Preparing activity:
DLA - CC

(Project 5980- 0020)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:25Z
Check the source to verify that this is the current version before use.