The documentation and process conversion measures necessary to comply with this amendment shall be completed by 6 July 1998

INCH-POUND

MIL-PRF-19500/500C
AMENDMENT 1
6 April 1998

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, TRANSIENT VOLTAGE SUPPRESSOR
UNIPOLAR TYPES 1N5555 THROUGH 1N5558, 1N5907, 1N5629A THROUGH 1N5665A
JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/500C, dated 8 July 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.3 $P_{M(AV)}$; delete "(see 6.3)".

PAGE 2

3.3 Delete and substitute as follows:

"3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows:

$I_{(BR)}$ - - - - - - - - - - - -Reverse breakdown current at a specified condition."

PAGE 3

Figure 1, internal construction of drawing, following 6; add "7".

Figure 1, dimension table; delete and substitute as follows:

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.215	.235	5.46	5.97	
BL	.293	.357	7.44	9.07	3
BLT	---	.570	---	14.48	
CD	.045	.100	1.14	2.54	5
LD	.025	.035	0.64	0.89	
LL	1.000	1.625	25.40	41.28	
LU	---	.188	---	4.78	4

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:29Z
Check the source to verify that this is the current version before use.

PAGE 4

Add the following paragraph:

"4.1.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-19500 and as specified herein except, lot accumulation period shall be 6 months in lieu of 6 weeks."

4.3, screen table, heading; delete "table II" and substitute "table IV".

4.3, screen 13; delete and substitute as follows:

"

13	Group A, subgroup 2 and 3 electrical parameters not applicable for this screen (performed in screen 12).	Group A, subgroup 2 and 3 electrical parameters not applicable for this screen (performed in screen 12).

"

PAGE 5

4.4.3.1, Group C inspection; C7, conditions column, end of conditions column; add "22 devices, c = 0."

4.4.3.1, Group C inspection; C8, conditions column, end of conditions column; add "22 devices, c = 0."

4.5.1, paragraph e; delete and substitute as follows:

"e. Read and record I_D and $V_{(BR)}$ at T_A = +25°C. Devices with ΔI_D > 50 percent (100 percent for steady-state operation life) of the initial reading or 1 μA dc, whichever is greater, or $\Delta V_{(BR)}$ > ±2 percent (±5 percent for steady-state operation life) initial value shall be considered defective. Remove defective devices and record the number of failures. (For steady-state operation life, I_D maximum limit shall be two times the group A limit)."

PAGE 8

Table II, step 1, symbol column; delete "I_R" and substitute "I_D".

PAGES 9 and 10

Table III, characteristics and ratings, column 5; delete "I_R" two places and substitute "I_D" two places.

PAGE 10

Add table title as follows: "TABLE III. Characteristics and ratings."

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI, SM
Navy _ AS, CG, MC
Air Force - 19, 85, 99

Preparing activity:
DLA - CC

(Project 5961-1966)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:29Z
Check the source to verify that this is the current version before use.