The documentation and process conversion measures necessary to comply with this revision shall be completed by 4 January 2002.

INCH-POUND

MIL-PRF-19500/511D
AMENDMENT 1
4 October 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, SWITCHING
TYPE 2N4261, 2N4261UB, JAN, JANTX, JANTXV AND JANS, JANHC AND JANKC

This amendment forms a part of MIL-PRF-19500/511D, dated 19 January 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 10

TABLE I, subgroup 2, emitter-base cutoff current, unit column, delete "nA dc" and substitute "∝A dc"

PAGE 11

TABLE I, subgroup 2, following collector to emitter saturated voltage, symbol $V_{CE(sat)2}$, insert:

"

Subgroup 3						
High-temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 2.0 V dc V_{CE} = 10 V dc	I_{CEX3}		5.0	∝A dc
Low-temperature operation :		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc I_C = 10 mA dc; pulsed (see 4.5.1)	h_{FE4}	15		
Subgroup 4						
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = 4.0 V dc; I_C = 5.0 mA dc; f = 100 MHz	$\|h_{fe1}\|$	15		

"

Custodians:
Army - CR
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

Review activities:
ARMY - MI
Air Force – 19, 71, 99

(Project 5961-2514)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.