The documentation and process conversion measures necessary to comply with this amendment shall be completed by 15 February 2000.

INCH POUND

MIL-PRF-19500/556F
AMENDMENT 1
15 November 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, FIELD EFFECT TRANSISTOR, N-CHANNEL, SILICON
TYPES 2N6782, 2N6782U, 2N6784, 2N6784U, 2N6786, AND 2N6786U
JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This amendment forms a part of MIL-PRF-19500/556F, dated 24 December 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 9

3.3.1, delete in its entirety and substitute as follows:

"3.3.1 Lead finish. Unless otherwise specified, lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2)."

PAGE 10

4.3.1, screen 12, JANTX and JANTXV levels column, add "or accelerated test, $T_A$ = +175°C, t = 48 hours".

PAGE 15

TABLE I, subgroup 7, On state gate charge test, 2N6784 device, limits Max column, delete "6.24" and substitute "6.5".

PAGE 16

TABLE I, subgroup 7, Gate to source charge test, 2N6784 device, limits Max column, delete "1.24" and substitute "1.5"; gate to drain charge test, 2N6784 device, limits Max column, delete "4.95" and substitute "5.0".

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2115)

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:17Z
Check the source to verify that this is the current version before use.