The documentation and process conversion measures necessary to comply with this document shall be completed by 28 February, 2002.

INCH POUND

MIL-PRF-19500/567B
AMENDMENT 1
28 November 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON,
SCHOTTKY BARRIER, FAST RECOVERY
TYPE 1N6492, JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/567B, dated 20 July 2001 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.3, step 11, measurements JANS, JANTX, and JANTXV, delete “Subgroup 2 of table I herein.”.

4.3, step 13, measurements JANS, JANTX, and JANTXV, add “Subgroup 2 of table I herein.”.

4.3, step 13, measurements JANS, JANTX, and JANTXV, delete “ΔI_{R1}” and substitute “ΔI_{RM1}”.

PAGE 5

4.3.1, delete and substitute “4.3.1 Power burn-in conditions. Power burn-in conditions are as follows (utilizing method 1038 of MIL-STD-750, test condition B): T_A = +50°C maximum, any clips or heat sink configuration maybe utilized provided that I_O and T_A are adjusted to achieve T_A = +135°C minimum, V_R = 45 V (pk), I_O = 0.75 A dc. f = 60 Hz.

4.4.2.2, subgroup B2, delete method “1056” and substitute “1051”.

4.4.2.2, subgroup B2, delete condition and substitute “Temperature cycle, test condition C.”.

4.4.2.2, subgroup B3, delete “V_{RN}” and substitute with “V_{RM}”.

PAGE 7

TABLE I, subgroup 3, low temperature operation, reverse current leakage, delete “I_{RM3}” and substitute “I_{RM4}”.

TABLE I, subgroup 4, reverse current leakage at peck reverse voltage, delete “I_{RM4}” and substitute “I_{RM5}”.

Custodians:
Army - CR
Navy - NW
Air Force - 11
DLA - CC

Preparing activity
DLA - CC

(Project 5961-2533)

Review activities:
Army - AR, MI
Navy - SH, MC
Air Force - 19, 71, 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:29Z
Check the source to verify that this is the current version before use.