The documentation and process conversion measures necessary to comply with this amendment shall be completed by 25 July 2000.

INCH-POUND

MIL-PRF-19500/585A
AMENDMENT 1
25 April 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, ULTRA-FAST RECOVERY,
HIGH VOLTAGE, POWER RECTIFIER
1N6620 THROUGH 1N6625 AND U-SUFFIX VERSIONS
JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/585A, dated 30 August 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.4, column 17, unit of measure; delete "°C" and substitute "V".

PAGE 5

3.5; delete and substitute:

"3.5 Polarity. The polarity of all types shall be indicated with a contrasting color band to denote the cathode end. Alternatively, for U suffix devices, a minimum of three contrasting color dots spaced around the periphery on the cathode end of the device may be used."

4.3, following table add:

"1/ Thermal impedance shall be performed any time before screen 13."

4.4.2, delete and substitute:

"4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables VIa (JANS) and VIb (JAN, JANTX and JANTXV) of MIL-PRF-19500 and paragraphs 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein except thermal impedance. Delta measurements shall be in accordance with table III herein."

PAGE 6

4.4.2.2, subgroup 6, conditions; delete and substitute, "T_A = +200°C, t = 340 hours".

4.4.3, at end of last sentence; add: "except for thermal impedance".

4.4.3 subgroup 6, conditions; add: "T_A = + 25°C."

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA – NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961- 2266)

Review activities:
Army - AR, MI, SM
Navy – AS, CG, MC
Air Force – 13, 19

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:42Z
Check the source to verify that this is the current version before use.