The documentation and process conversion measures necessary to comply with this amendment shall be completed by 3 February, 2001.

INCH-POUND

MIL-PRF-19500/585A
AMENDMENT 2
3 November 2000
SUPERSEDING
AMENDMENT 1
25 April 2000

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, ULTRA-FAST RECOVERY, HIGH VOLTAGE, POWER RECTIFIER, 1N6620 THROUGH 1N6625 AND U-SUFFIX VERSIONS, JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/585A, dated 30 August 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.4, column 17, unit of measure; delete "°C" and substitute "V".

PAGE 5

3.5; delete and substitute:

"3.5 Polarity. The polarity of all types shall be indicated with a contrasting color band to denote the cathode end. Alternatively, for U suffix devices, a minimum of three contrasting color dots spaced around the periphery on the cathode end of the device may be used."

4.3, following table add:

"1/ Thermal impedance shall be performed any time before screen 13."

4.4.2, delete and substitute:

"4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables VIa (JANS) and VIb (JAN, JANTX and JANTXV) of MIL-PRF-19500 and paragraphs 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein except thermal impedance. Delta measurements shall be in accordance with table III herein."

PAGE 6

* 4.4.2.1, subgroup 5, method 1027, conditions, delete and substitute:

"T_A = room ambient as defined in the general requirements of MIL-STD-750 (see 4.5 of MIL-STD-750), no heat sink allowed. I_F = 1.5 x $I_{F(AV)2}$ minimum; adjust T_A or I_F, as required to achieve T_J = +275°C, minimum, t = 96 hours frequency of test is per inspection lot,

or

Option I_F = 1.5 x $I_{F(AV)2}$ minimum; adjust T_A or I_F, as required to achieve T_J = +200°C minimum for t = 1,000 hours at double the sample size. Frequency of test is per inspection lot.

(NOTE: If a failure occurs, resubmission shall be at the test conditions of the original sample.) "

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:42Z
Check the source to verify that this is the current version before use.

4.4.2.2, subgroup 6, conditions; delete and substitute, "T_A = +200°C, t = 340 hours".

4.4.3, at end of last sentence; add: "except for thermal impedance".

4.4.3 subgroup 6, conditions; add: "T_A = +25°C."

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19

Preparing activity:
DLA - CC

(Project 5961-2347)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:42Z
Check the source to verify that this is the current version before use.