The documentation and process conversion measures necessary to comply with this amendment shall be completed by 27/9/96

INCH POUND

MIL-S-19500/586B
AMENDMENT 1
27 June 1996

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, HERMETIC, DIODE, SILICON, SCHOTTKY BARRIER
TYPES 1N5819-1, 1N5819UR-1, 1N6650-1 AND 1N6650UR-1
JAN, JANTX, JANTXV, JANS, JANHC AND JANKC

This amendment forms a part of MIL-S-19500/586B, dated 22 July 1994 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.4, Max I_{RM2}, 1N5819-1 and 1N5819UR-1, delete "4.0" two places and substitute "5.0" two places.

PAGE 8

4.3.2 First line, following 1.0 A dc; add "(min), T_A = Room ambient as defined in the general requirements of MIL-STD-750."

4.3.2.1, second line delete "$T_J \geq 110^\circ$ C" and substitute $T_J = 110^\circ C \pm 15^\circ C$".

4.4.2.1, subgroup 4 delete and substitute as follows:

"4	1036	I_F = 1.0 A; T_A = Room ambient as defined in the general requirements of MIL-STD-750 (see 4.5); $t_{on} = t_{off}$ 3 minutes for 2,000 cycles."

4.4.2.1, subgroup 5, conditions, delete and substitute as follows:

"5	1027	$T_A = +75^\circ C \pm 25^\circ C$; I_F= 1.0 (min) with I_F adjusted as required to achieve an average lot $T_J = 125^\circ C + 0^\circ C, - 10^\circ C$, $T_J = +125^\circ C +0^\circ - 10^\circ C$."

PAGE 10

Table I, Subgroup 3, max limits column, I_{RM2} for 1N5819-1, 1N5819UR-1; delete "4.0" and substitute "5.0".

Table I, Subgroup 3, max limits column, I_{RM3} for 1N5819-1, 1N5819UR-1; delete "3.5" and substitute "4.5".

CONCLUDING MATERIAL

Custodian:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Preparing activity:
DLA - ES

Agent:
DLA - ES

(Project 5961- 1835)

Review activities:
Army - AR, MI, SM
Air Force - 19, 85, 99
Navy - AS, CG, MC

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:45Z
Check the source to verify that this is the current version before use.