The documentation and process conversion measures necessary to comply with this amendment shall be completed by 3 February, 2001.

INCH-POUND

MIL-PRF-19500/590B
AMENDMENT 1
3 November 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, ULTRA-FAST RECOVERY, HIGH VOLTAGE, POWER RECTIFIER, 1N6626 THROUGH 1N6631 AND U SUFFIX VERSIONS, JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/590B, dated 6 May 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

4.4.2.1, delete and substitute,

"4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500, B5, conditions. T_A = room ambient as defined in the general requirements of MIL-STD-750, no heat sink allowed. $I_F = 1.5 \times I_{F(AV)2}$ minimum; adjust T_A or I_F, as required to achieve T_J = +275°C, minimum, t = 96 hours frequency of test is in accordance with inspection lot, or: Option: $I_F = 1.5 \times I_{F(AV)2}$ minimum; adjust T_A or I_F, as required to achieve T_J = +200°C minimum for t = 1,000 hours at double the sample size, frequency of test is in accordance with inspection lot. (NOTE: If a failure occurs, resubmission shall be at the test conditions of the original sample.)" .

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19

Preparing activity:
DLA - CC

(Project 5961-2293)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:48Z
Check the source to verify that this is the current version before use.