The documentation and process conversion measures necessary to comply with this amendment shall be completed by 19 February 1998.

INCH POUND

MIL-PRF-19500/596D
AMENDMENT 1
19 November 1997

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, REPETITIVE AVALANCHE, FIELD EFFECT,
TRANSISTOR, N-CHANNEL, SILICON,
TYPES 2N7218, 2N7219, 2N7221, 2N7222, 2N7218U, 2N7219U,
2N7221U, 2N7222U, JANTX, JANTXV, JANS, JANHC, AND JANKC

This amendment forms a part of MIL-PRF-19500/596D, dated 13 September 1996, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.3, maximum ratings, type 2N7221: Delete “300 V” and substitute “400 V”: Type 2N7222, delete “400 V” and substitute “500 V”.

PAGE 3

Figure 1, LL dimension, min. column : Delete “1.195” and substitute “.510”. Max column: Delete “1.235” and substitute “.570”.

PAGE 9

4.4.2 and 4.4.3, add the following: “and see 4.5.3, c = 0, n = 22 “

PAGE 10

4.5.3, delete in its entirety and substitute:

“4.5.3 Thermal impedance ($Z_{\Theta JC}$ measurements). The $Z_{\Theta JC}$ measurements shall be performed in accordance with method 3161 of MIL-STD-750. The maximum limit (not to exceed .9°C/W or figure 4 thermal impedance curve) for $Z_{\Theta JC}$ in screening (table IV of MIL-PRF-19500) shall be derived by each vendor by means of statistical process control. When the process has exhibited control and capability, the capability data shall be used to establish the fixed screening limit. In addition to screening, once a fixed limit has been established, monitor all future sealing lots using a random five piece sample from each lot to be plotted on the applicable X, R chart. If a lot exhibits an out of control condition, the entire lot shall be removed from the line and held for engineering evaluation and disposition. This procedure may be used in lieu of an in line monitor. The following parameter measurements shall apply:”

PAGE 14

TABLE I, subgroup 7, gate to source charge test, limits max column, delete "12", "10.6", and "10.0" and substitute "16", "14.6", and "14.0" respectively.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:52Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army -CR
Navy -EC
Air Force -17
NASA -NA

Review activities:
Army -AR, MI, SM
Navy -AS, CG, MC
Air Force -13, 19, 85, 99

Preparing activity:
DLA -CC

(Project 5961-1929)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:52Z
Check the source to verify that this is the current version before use.