The documentation and process conversion measures necessary to comply with this revision shall be completed by 22 May 2001.

INCH POUND

MIL-PRF-19500/660
AMENDMENT 1
21 February 2001

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED
(TOTAL DOSE ONLY) TRANSISTOR, P-CHANNEL
SILICON TYPES 2N7424, 2N7425 AND 2N7426
JANTXVR, JANTXVF, JANSR AND JANSF

This amendment forms a part of MIL-PRF-19500/660, dated 27 May 1998 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.3, type 2N7426 I_{D1}, delete "-23" and substitute "-27".

1.3, type 2N7426 I_{D2}, delete "-15" and substitute "-17".

1.3, type 2N7426 I_S, delete "-23" and substitute "-27".

1.3, type 2N7426 I_{DM}, delete "-92" and substitute "-108".

1.4, 2N7426 $r_{ds(on)}$, delete "0.230Ω" and substitute "0.160Ω".

1.4, 2N7426 $r_{ds(on)}$, delete "0.530Ω" and substitute "0.340Ω".

PAGE 7

4.5.2, drain heating current (I_H) delete "8A" and substitute "10A".

4.5.2, drain-source heating voltage (V_H), delete "25V" and substitute "20V".

PAGE 8

Table I, subgroup 2 static drain to source "ON" state resistance, $r_{ds(on)1}$, type 2N7426, max limits, delete "0.230Ω" and substitute "0.160Ω".

Table I, subgroup 2 static drain to source "ON" state resistance, $r_{ds(on)2}$, type 2N7426, max limits, delete "0.240Ω" and substitute "0.170Ω".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:34Z
Check the source to verify that this is the current version before use.

PAGE 9

Table I, group A inspection, subgroup 3, static drain to source "ON" state resistance, $r_{ds(on)3}$, type 2N7426 max limits, delete "0.46Ω" and substitute "0.315Ω".

Table I, subgroup, turn-on delay time, type 2N7426 max limits, delete "70" and substitute "37".

Table I, subgroup, rise time, type 2N7426 max limits, delete "240" and substitute "83".

Table I, subgroup, turn-off delay time, type 2N7426 max limits, delete "220" and substitute "140".

Table I, subgroup, fall time, type 2N7426 max limits, delete "220" and substitute "172".

Table I, subgroup 4: add:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Forward transconductance	3475	I_D = rated I_{D2}, V_{DD} = 15 V (see 4.5.1)	G_{FS}			
2N7424				18		S
2N7425				15		S
2N7426				13		S

"

PAGE 10

Table I, subgroup 7, gate to source charge, type 2N7426, delete "75" and substitute "60".

Table I, subgroup 7, gate to drain charge, type 2N7426, delete "90" and substitute "70".

Table I, subgroup 7, gate to source charge, type 2N7426, delete "775" and substitute "600".

PAGE 12

Table II, subgroup 2, static drain to source "ON" state voltage, type 2N7426, delete "-3.45" and substitute "-2.72" three places.

PAGE 18

4.5.3, drain to source heating voltage (V_H), delete "25V" and substitute "20V".

4.5.3, drain heating current (I_H) delete "8A" and substitute "10A".

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA – CC

Preparing activity:
DLA - CC

(Project 5961-2419)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:34Z
Check the source to verify that this is the current version before use.